

## Epson TM-H6000V-203 180 x 180 DPI Wired & Wireless Dot matrix POS printer

**Brand :** Epson

**Product code:** C31CG62203

**Product name :** TM-H6000V-203



- Integrated point-of-sale printer: Capable of receipt printing, slip printing and cheque processing
- Boost efficiency: Fast prints speeds up to 350mm/s<sup>1</sup>, cheque processing and auto-cutter
- Flexible connectivity: Built-in USB and Ethernet in all models
- An investment for the future: ePOS-Print, ePOS-display and NFC
- Great value: Low total cost of ownership

180 x 180DPI, 350mm/sec, NFC, USB 1.1, USB 2.0, Ethernet, Serial, White

Epson TM-H6000V-203. Print technology: Dot matrix, Type: POS printer, Maximum resolution: 180 x 180 DPI. Maximum roll diameter: 8.3 cm, Supported paper width: 80 mm, Maximum paper size (slip): 230 x 297 mm. Connectivity technology: Wired & Wireless, USB connector: USB Type-A / USB Type-B, Serial interface type: RS-232. Sound pressure level (printing): 55 dB, Sound pressure level (standby): 55 dB, Mean time between failures (MTBF): 180000 h. Product colour: White

Printing		Design	
Colour	✗	Product colour *	White
Maximum resolution	180 x 180 DPI	<b>Power</b>	
Print speed	5.7 lps	AC input voltage	24 V
Print speed (receipt)	350 mm/sec	<b>Operational conditions</b>	
Character size	1.24 x 3.11 mm	Operating temperature (T-T)	5 - 45 °C
Character density	17.8 cpi	Storage temperature (T-T)	-10 - 50 °C
Printing characters	Text, Graphic, Barcode	Operating relative humidity (H-H)	10 - 90%
Character sets	ANK	Storage relative humidity (H-H)	10 - 90%
Print technology *	Dot matrix	<b>System requirements</b>	
Type *	POS printer	Pre-installed software	Server Direct Print, ePOS-Display, ePOS-Print
<b>Paper handling</b>		<b>Weight &amp; dimensions</b>	
Maximum roll diameter	8.3 cm	Width	186 mm
Supported paper width	80 mm	Depth	278 mm
Maximum paper size (slip)	230 x 297 mm	Height	181 mm
<b>Ports &amp; interfaces</b>		Weight	4.4 kg
USB port *	✓	<b>Packaging data</b>	
USB connector	USB Type-A / USB Type-B	Quantity per pack	1 pc(s)
Serial interface *	✓	Package width	293 mm
Serial interface type	RS-232	Package depth	382 mm
Connectivity technology *	Wired & Wireless	Package height	287 mm
Near Field Communication (NFC)	✓	Package weight	5.52 kg
Standard interfaces	Ethernet, NFC, RS-232, USB 1.1, USB 2.0	<b>Packaging content</b>	
<b>Network</b>		AC adapter included	✓
Ethernet LAN *	✓	<b>Print technology</b>	
<b>Features</b>		Column capacity	45 cps / 60 cps
Sound pressure level (printing)	55 dB	<b>Logistics data</b>	
Sound pressure level (standby)	55 dB	Pallet weight (UK)	0 g
Mean time between failures (MTBF)	180000 h	Harmonized System (HS) code	84433210
Cutter	✓	Products per pallet	56 pc(s)
Half-cutter	✓	Products per pallet layer	8 pc(s)
Autocutter durability	3 million cuts		

Features		Logistics data	
Paper save function	✓	Pallet gross width	80 cm
Print head life	200 km	Pallet gross length	120 cm
Country of origin	China	Pallet gross height	2.18 m
Maximum number of copies (slip)	3 copies	Pallet gross weight	0 g
Printer receipt unit life	20000000 lines	Products per pallet (UK)	70 pc(s)
Printer slip unit life	27000000 lines	Products per pallet layer (UK)	10 pc(s)
Ribbon life (slip)	4 million characters	Pallet width (UK)	100 cm
Built-in sensors details	Middle of Paper pass sensor, Front cover open sensor, Roll paper cover open sensor, Paper End Sensor, Top of Form sensor, Bottom of Form sensor, Slip eject sensor, Receipt near-end sensor	Pallet length (UK)	120 cm
	CE, EN55024, EN55032 Class A, IEC61000-4-2, IEC61000-4-3, IEC61000-4-4, IEC61000-4-5, IEC61000-4-6, IEC61000-4-11, Directive 2014/30/EU	Pallet height (UK)	2.18 m
Certification		Technical details	
		Font size	1.41 mm (W) x 3.39 mm (H) / 0.99 mm (W) x 2.4 mm (H)
		Changeable interface	✓
		Other features	
		Buffer size	4 KB
		Mean cycles between failures (MCBF)	65000000
		Print head life	200000000 million characters



8715946651118

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-FEB-2025. Prints or copies of Information are only valid on the printed Publication date