

## Epson TM-H6000V-213: Serial, MICR, White, No PSU

**Tuotemerkki :** Epson

**Tuotekoodi:** C31CG62213

**Tuotteen nimi :** TM-H6000V-213: Serial, MICR, White, No PSU

- Integroitu POS-tulostin: Kuittitulostus, lipuketulostus ja sekkien käsittely
- Parantaa tehokkuutta: Tulostusnopeus jopa 350 mm/s<sup>2</sup>, sekkien käsittely ja automaattinen leikkuri
- Joustavat liitännät: Sisäänrakennettu USB- ja Ethernet-liitäntä kaikissa malleissa
- Investointi tulevaisuuteen: ePOS-Print-tulostus, ePOS-Display-näyttö ja NFC
- Paljon vastinetta rahoille: Edulliset elinkaarikustannukset

TM-H6000V-213: Serial, MICR, White, No PSU

Epson TM-H6000V-213: Serial, MICR, White, No PSU. Tulostustekniikka: Pistematriisi, Malli: Maksupäätetulostin, Suurin resoluutio: 180 x 180 DPI. Suurin rullan halkaisija: 8,3 cm, Tuetut paperin leveydet: 80 mm, Paperin enimmäiskoko (lipuke): 230 x 297 mm. Yhteysteknologia: Langallinen & langaton, USB-liitin: USB Type-A / USB Type-B, Sarjaliitännän tyyppi: RS-232. Äänenpainetaso (tulostus): 55 dB, Äänenpainetaso (valmius): 55 dB, Keskimääräinen vikaantumisaika: 180000 h. Tuotteen väri: Valkoinen



| Printing                          |   | Features               |  |
|-----------------------------------|---|------------------------|--|
| Colour                            | ✘                                       | Certification          | CE, EN55024, EN55032 Class A, IEC61000-4-2, IEC61000-4-3, IEC61000-4-4, IEC61000-4-5, IEC61000-4-6, IEC61000-4-11, Directive 2014/30/EU                                  |
| Maximum resolution                | 180 x 180 DPI                           |                        |  |
| Print speed                       | 5.7 lps                                 |                        |  |
| Print speed                       | 350 mm/sec                              |                        |  |
| Print speed (receipt)             | 350 mm/sec                              | Design                 | Product colour * White   |
| Character size                    | 1.24 x 3.11 mm                          |                        |  |
| Character density                 | 17.8 cpi                                | Power                  | AC input voltage 24 V  |
| Printing characters               | Text, Graphic, Barcode                  |                        |  |
| Character sets                    | ANK                                     | Operational conditions | Operating temperature (T-T) 5 - 45 °C<br>Storage temperature (T-T) -10 - 50 °C<br>Operating relative humidity (H-H) 10 - 90%<br>Storage relative humidity (H-H) 10 - 90% |
| Print technology *                | Dot matrix                              |                        |  |
| Type *                            | POS printer                             |                        |  |
| Paper handling                    |   | System requirements    | Pre-installed software Server Direct Print, ePOS-Display, ePOS-Print   |
| Maximum roll diameter             | 8.3 cm                                  |                        |  |
| Supported paper width             | 80 mm                                   |                        |  |
| Maximum paper size (slip)         | 230 x 297 mm                            | Weight & dimensions    | Width 186 mm<br>Depth 278 mm<br>Height 181 mm<br>Weight 4.4 kg   |
| Ports & interfaces                |   |                        |  |
| USB port *                        | ✔                                       | Packaging data         | Quantity per pack 1 pc(s)<br>Package width 294 mm<br>Package depth 382 mm<br>Package height 292 mm<br>Package weight 5.67 kg   |
| USB connector                     | USB Type-A / USB Type-B                 |                        |  |
| Serial interface *                | ✔                                       | Packaging content      | AC adapter included ✔  |
| Serial interface type             | RS-232                                  |                        |  |
| Connectivity technology *         | Wired & Wireless                        | Print technology       | Column capacity 45 cps / 60 cps  |
| Near Field Communication (NFC)    | ✔                                       |                        |  |
| Standard interfaces               | Ethernet, NFC, RS-232, USB 1.1, USB 2.0 |                        |  |
| Network                           |   |                        |  |
| Ethernet LAN *                    | ✔                                       |                        |  |
| Features                          |   |                        |  |
| Sound pressure level (printing)   | 55 dB                                   |                        |  |
| Sound pressure level (standby)    | 55 dB                                   |                        |  |
| Mean time between failures (MTBF) | 180000 h                                |                        |  |
| Cutter                            | ✔                                       |                        |  |
| Half-cutter                       | ✔                                       |                        |  |

| Features                        |   | Logistics data                      |  |
|---------------------------------|---|-------------------------------------|--|
| Autocutter durability           | 3 million cuts  | Pallet weight (UK)                  | 0 g  |
| Built-in MICR                   | ✓   | Harmonized System (HS) code         | 84433210   |
| Paper save function             | ✓   | Products per pallet                 | 56 pc(s)   |
| Print head life                 | 200 km  | Products per pallet layer           | 8 pc(s)  |
| Country of origin               | China   | Pallet gross width                  | 80 cm  |
| Maximum number of copies (slip) | 3 copies  | Pallet gross length                 | 120 cm   |
| Printer receipt unit life       | 20000000 lines  | Pallet gross height                 | 2.18 m   |
| Printer slip unit life          | 27000000 lines  | Pallet gross weight                 | 0 g  |
| Ribbon life (slip)              | 4 million characters  | Products per pallet (UK)            | 70 pc(s)   |
| Built-in sensors details        | Middle of Paper pass sensor, Front cover open sensor, Roll paper cover open sensor, Paper End Sensor, Top of Form sensor, Bottom of Form sensor, Slip eject sensor, Receipt near-end sensor | Products per pallet layer (UK)      | 10 pc(s)   |
|                                 |   | Pallet width (UK)                   | 100 cm   |
|                                 |   | Pallet length (UK)                  | 120 cm   |
|                                 |   | Pallet height (UK)                  | 2.18 m   |
|                                 |   | Technical details                   |  |
|                                 |   | Font size                           | 1.41 mm (W) x 3.39 mm (H) / 0.99 mm (W) x 2.4 mm (H) |
|                                 |   | Changeable interface                | ✓  |
|                                 |   | Other features                      |  |
|                                 |   | Buffer size                         | 4 KB   |
|                                 |   | Mean cycles between failures (MCBF) | 65000000   |
|                                 |   | Print head life                     | 200000000 million characters                         |



8715946651132

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-FEB-2025. Prints or copies of Information are only valid on the printed Publication date