

Epson TM-H6000V-214: Serial, MICR, Black, No PSU

Tuotemerkki : Epson

Tuotekoodi: C31CG62214

Tuotteen nimi : TM-H6000V-214: Serial, MICR, Black, No PSU

- Integroitu POS-tulostin: Kuittitulostus, lipuketulostus ja sekkien käsittely
- Parantaa tehokkuutta: Tulostusnopeus jopa 350 mm/s², sekkien käsittely ja automaattinen leikkuri
- Joustavat liitännät: Sisäänrakennettu USB- ja Ethernet-liitäntä kaikissa malleissa
- Investointi tulevaisuuteen: ePOS-Print-tulostus, ePOS-Display-näyttö ja NFC
- Paljon vastinetta rahoille: Edulliset elinkaarikustannukset

TM-H6000V-214: Serial, MICR, Black, No PSU

Epson TM-H6000V-214: Serial, MICR, Black, No PSU. Tulostustekniikka: Pistematriisi, Malli: Maksupäätetulostin, Suurin resoluutio: 180 x 180 DPI. Suurin rullan halkaisija: 8,3 cm, Tuetut paperin leveydet: 80 mm, Paperin enimmäiskoko (lipuke): 230 x 297 mm. Yhteysteknologia: Langallinen & langaton, USB-liitin: USB Type-A / USB Type-B, Sarjaliitännän tyyppi: RS-232. Äänenpainetaso (tulostus): 55 dB, Äänenpainetaso (valmius): 55 dB, Keskimääräinen vikaantumisaika: 180000 h. Tuotteen väri: musta



Printing		Features	
Colour	✘	Certification	CE, EN55024, EN55032 Class A, IEC61000-4-2, IEC61000-4-3, IEC61000-4-4, IEC61000-4-5, IEC61000-4-6, IEC61000-4-11, Directive 2014/30/EU
Maximum resolution	180 x 180 DPI		
Print speed	5.7 lps		
Print speed	350 mm/sec		
Print speed (receipt)	350 mm/sec	Design	
Character size	1.24 x 3.11 mm	Product colour *	Black
Character density	17.8 cpi	Power	
Printing characters	Text, Graphic, Barcode	AC input voltage	24 V
Character sets	ANK	Operational conditions	
Print technology *	Dot matrix	Operating temperature (T-T)	5 - 45 °C
Type *	POS printer	Storage temperature (T-T)	-10 - 50 °C
Paper handling		Operating relative humidity (H-H)	10 - 90%
Maximum roll diameter	8.3 cm	Storage relative humidity (H-H)	10 - 90%
Supported paper width	80 mm	System requirements	
Maximum paper size (slip)	230 x 297 mm	Pre-installed software	Server Direct Print, ePOS-Display, ePOS-Print
Ports & interfaces		Weight & dimensions	
USB port *	✓	Width	186 mm
USB connector	USB Type-A / USB Type-B	Depth	278 mm
Serial interface *	✓	Height	181 mm
Serial interface type	RS-232	Weight	4.4 kg
Connectivity technology *	Wired & Wireless	Packaging data	
Near Field Communication (NFC)	✓	Quantity per pack	1 pc(s)
Standard interfaces	Ethernet, NFC, RS-232, USB 1.1, USB 2.0	Package width	297 mm
Network		Package depth	382 mm
Ethernet LAN *	✓	Package height	294 mm
Features		Package weight	5.64 kg
Sound pressure level (printing)	55 dB	Packaging content	
Sound pressure level (standby)	55 dB	AC adapter included	✓
Mean time between failures (MTBF)	180000 h	Print technology	
Cutter	✓	Column capacity	45 cps / 60 cps
Half-cutter	✓		
Autocutter durability	3 million cuts		

Features		Logistics data	
Built-in MICR	✓	Pallet weight (UK)	0 g
Paper save function	✓	Harmonized System (HS) code	84433210
Print head life	200 km	Products per pallet	56 pc(s)
Country of origin	China	Products per pallet layer	8 pc(s)
Maximum number of copies (slip)	3 copies	Pallet gross width	80 cm
Printer receipt unit life	20000000 lines	Pallet gross length	120 cm
Printer slip unit life	27000000 lines	Pallet gross height	2.18 m
Ribbon life (slip)	4 million characters	Pallet gross weight	0 g
Built-in sensors details	Middle of Paper pass sensor, Front cover open sensor, Roll paper cover open sensor, Paper End Sensor, Top of Form sensor, Bottom of Form sensor, Slip eject sensor, Receipt near-end sensor	Products per pallet (UK)	70 pc(s)
		Products per pallet layer (UK)	10 pc(s)
		Pallet width (UK)	100 cm
		Pallet length (UK)	120 cm
		Pallet height (UK)	2.18 m
		Technical details	
		Font size	1.41 mm (W) x 3.39 mm (H) / 0.99 mm (W) x 2.4 mm (H)
		Changeable interface	✓
		Other features	
		Buffer size	4 KB
		Mean cycles between failures (MCBF)	65000000
		Print head life	200000000 million characters



8715946651149

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-FEB-2025. Prints or copies of Information are only valid on the printed Publication date