

Lexmark CS820dte Colour 1200 x 1200 DPI A4

Brand : Lexmark

Product code: 21K0184

Product name : CS820dte

Lexmark CS820dte. Print technology: Laser, Colour. Number of print cartridges: 4, Maximum duty cycle: 200000 pages per month. Maximum resolution: 1200 x 1200 DPI. Maximum ISO A-series paper size: A4. Print speed (black, normal quality, A4/US Letter): 57 ppm, Duplex printing. Network ready. Product colour: Black, White

Printing		Network	
Print resolution colour	2400 x 600 DPI	Supported network protocols (IPv6)	TCP/IP, TCP, UDP
Print speed (colour, normal quality, A4/US Letter)	57 ppm	Management protocols	HTTP, HTTPs (SSL / TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, BOOTP, RARP, APIPA (AutoIP), DHCP, ICMP, DNS, Bonjour, DDNS, mDNS, ARP, NTP, telnet, Finger
Colour *	✓	Performance	
Print technology *	Laser	Internal memory *	1024 MB
Duplex printing *	✓	Maximum internal memory	3072 MB
Maximum resolution *	1200 x 1200 DPI	Built-in processor	✓
Print speed (black, normal quality, A4/US Letter) *	57 ppm	Processor frequency	1330 MHz
Time to first page (black, normal)	7 s	Sound pressure level (printing)	56 dB
Time to first page (colour, normal)	7 s	Sound pressure level (duplex printing)	57 dB
Features		Sound pressure level (quiet mode)	52 dB
Maximum duty cycle *	200000 pages per month	Design	
Recommended duty cycle	2500 - 25000 pages per month	Product colour *	Black, White
Printing colours *	Black, Cyan, Magenta, Yellow	Built-in display *	✓
Number of print cartridges *	4	Display diagonal	10.9 cm (4.3")
Page description languages *	PCL 5c, PCL 6, PPDS, PostScript 3	Touchscreen	✓
Input & output capacity		Control type	Touch
Total number of input trays *	3	ENERGY STAR, ICES-003 Class A, BSMI Class A, VCCI Class A, FCC Class A, NOM-032, UL, cUL, NOM, US FDA/CDRH, IEC 60825-1, CB Report, ISO-532B, CE (EU) DoC, EFTA (CE), KC logo, CCC, C-tick DoC, EuP, CECP, CEL, EC 1275/2008, ECMA-370, TED, SII, TER, SABS, UL-AR, GS Mark, Green Dot, ISO-9296, COC, CCD-035 EcoLogo, Green Mark, EPEAT, Blue Angel (Blauer Engel)	
Total input capacity *	1200 sheets	Certification	
Total output capacity *	500 sheets	ENERGY STAR, ICES-003 Class A, BSMI Class A, VCCI Class A, FCC Class A, NOM-032, UL, cUL, NOM, US FDA/CDRH, IEC 60825-1, CB Report, ISO-532B, CE (EU) DoC, EFTA (CE), KC logo, CCC, C-tick DoC, EuP, CECP, CEL, EC 1275/2008, ECMA-370, TED, SII, TER, SABS, UL-AR, GS Mark, Green Dot, ISO-9296, COC, CCD-035 EcoLogo, Green Mark, EPEAT, Blue Angel (Blauer Engel)	
Multi-Purpose tray	✓	Power	
Multi-Purpose tray input capacity	100 sheets	Power consumption (printing) *	800 W
Maximum number of input trays	6	Energy Star Typical Electricity Consumption (TEC)	3.3 kWh/week
Maximum input capacity	4500 sheets	System requirements	
Maximum output capacity	500 sheets	Windows operating systems supported	✓
Paper handling		Mac operating systems supported	✓
Maximum ISO A-series paper size *	A4	Linux operating systems supported	✓
Paper tray media types *	Card stock, Envelopes, Labels, Plain paper	Operational conditions	
ISO A-series sizes (A0...A9) *	A4, A5, A6	Operating temperature (T-T)	10 - 32 °C
ISO B-series sizes (B0...B9)	B5	Operating relative humidity (H-H)	15 - 80%
ISO C-series sizes (C0...C9)	C4, C5	Operating altitude	0 - 2896 m
Non-ISO print media sizes	Folio, Letter, Oficio, Statement, Universal	Ports & interfaces	
JIS B-series sizes (B0...B9)	B5	USB 2.0 ports quantity	3
Paper tray media weight (imperial)	27.2 - 79.8 kg (60 - 176 lbs)	Optional connectivity	Wireless LAN
Multi-Purpose Tray media weight (imperial)	27.2 - 79.8 kg (60 - 176 lbs)	Network	
Ports & interfaces		Network ready	✓
USB 2.0 ports quantity	3		
Optional connectivity	Wireless LAN		
Network			
Network ready	✓		

Network		Sustainability	
Ethernet LAN *	✓	Sustainability certificates	Blue Angel, ENERGY STAR
Cabling technology	10/100/1000Base-T(X)	Weight & dimensions	
Ethernet LAN data rates	10,100,1000 Mbit/s	Width	558.8 mm
Security algorithms	802.1x RADIUS, LEAP, MD5, PEAP, SSL/TLS	Depth	522.4 mm
Supported network protocols (IPv4)	TCP/IP, TCP, UDP	Height	655 mm
		Weight	71.7 kg
		Packaging data	
		Package width	700 mm
		Package depth	760 mm
		Package weight	88.2 kg
		Other features	
		Power LED	✓
		Stand-by LED	✓



0734646616249



734646616249

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.