

Lexmark CS820de Väri 1200 x 1200 DPI A4

Tuotemerkki : Lexmark

Tuotekoodi: 21K0234

Tuotteen nimi : CS820de

- Color Laser
 - Kaksipuolinen tulostus: Sisäänrakennettu kaksipuolisuus
 - Tulostusnopeus: 57 s/min
 - Suositeltava kuukausittainen käyttö sivuina: 2500 - 25000 sivua†
 Quad Core 1.33 GHz, 1024 MB, 1200 x 1200 dpi, 535.9 x 558.8 x 522.4 mm, 62.3 kg, 57 dBA, 2500 - 25000 Sider, USB 2.0
 Lexmark CS820de. Tulostustekniikka: Laser, Väri. Värikasettien määrä: 4, Suurin toimintajakso: 200000 sivua kuukaudessa. Suurin resoluutio: 1200 x 1200 DPI. Suurin ISO A-luokan paperikoko: A4. Tulostusnopeus (musta, normaallaatu, A4/US Letter): 57 ppm, Kaksipuolinen tulostus. Verkkovalmius. Tuotteen väri: musta, Valkoinen

Printing		Network	
Print resolution colour	2400 x 600 DPI	Mobile printing technologies	Apple AirPrint
Print speed (colour, normal quality, A4/US Letter)	57 ppm	Performance	
Colour *	✓	Internal memory *	1024 MB
Print technology *	Laser	Maximum internal memory	3072 MB
Duplex printing *	✓	Built-in processor	✓
Maximum resolution *	1200 x 1200 DPI	Processor frequency	1330 MHz
Print speed (black, normal quality, A4/US Letter) *	57 ppm	Sound pressure level (printing)	56 dB
Time to first page (black, normal)	7 s	Sound pressure level (duplex printing)	57 dB
Time to first page (colour, normal)	7 s	Sound pressure level (quiet mode)	52 dB
Features		Design	
Maximum duty cycle *	200000 pages per month	Product colour *	Black, White
Recommended duty cycle	2500 - 25000 pages per month	Built-in display *	✓
Printing colours *	Black, Cyan, Magenta, Yellow	Display diagonal	10.9 cm (4.3")
Number of print cartridges *	4	Touchscreen	✓
Page description languages *	PCL 5c, PCL 6, PPDS, PostScript 3	Control type	Touch
Input & output capacity		ENERGY STAR, ICES-003 Class A, BSMI Class A, VCCI Class A, FCC Class A, NOM-032, UL, cUL, NOM, US FDA/CDRH, IEC 60825-1, CB Report, ISO-532B, CE (EU) DoC, EFTA (CE), KC logo, CCC, C-tick DoC, EuP, CECP, CEL, EC 1275/2008, ECMA-370, TED, SII, TER, SABS, UL-AR, GS Mark, Green Dot, ISO-9296, COC, CCD-035 EcoLogo, Green Mark, EPEAT, Blue Angel (Blauer Engel)	
Total number of input trays *	2	Certification	
Total input capacity *	650 sheets	Power	
Total output capacity *	500 sheets	Power consumption (printing) *	800 W
Paper input type	Paper tray	Power consumption (ready)	80 W
Multi-Purpose tray	✓	Power consumption (standby)	0.3 W
Multi-Purpose tray input capacity	100 sheets	Energy Star Typical Electricity Consumption (TEC)	3.3 kWh/week
Maximum number of input trays	6	System requirements	
Maximum input capacity	4500 sheets	Windows operating systems supported	✓
Maximum output capacity	500 sheets	Mac operating systems supported	✓
Paper handling		Linux operating systems supported	✓
Maximum ISO A-series paper size *	A4	Operational conditions	
Paper tray media types *	Card stock, Envelopes, Labels, Plain paper	Operating temperature (T-T)	10 - 32 °C
ISO A-series sizes (A0...A9) *	A4, A5, A6	Operating relative humidity (H-H)	15 - 80%
ISO B-series sizes (B0...B9)	B5		
ISO C-series sizes (C0...C9)	C4, C5		
Non-ISO print media sizes	Folio, Letter, Oficio, Statement, Universal		
JIS B-series sizes (B0...B9)	B5		
Paper tray media weight (imperial)	27.2 - 79.8 kg (60 - 176 lbs)		
Multi-Purpose Tray media weight (imperial)	27.2 - 79.8 kg (60 - 176 lbs)		

Ports & interfaces		Operational conditions	
Standard interfaces	Ethernet, USB 2.0	Operating altitude	0 - 2896 m
USB 2.0 ports quantity	3	Sustainability	
Optional connectivity	Wireless LAN	Sustainability certificates	Blue Angel, ENERGY STAR
Network		Weight & dimensions	
Network ready	✓	Width	558.8 mm
Ethernet LAN *	✓	Depth	522.4 mm
Security algorithms	802.1x RADIUS, IPsec, LEAP, MD5, PEAP, SSL/TLS, TTLS	Height	535.9 mm
Supported network protocols (IPv4)	TCP/IP, TCP, UDP	Weight	62.3 kg
Supported network protocols (IPv6)	TCP/IP, TCP, UDP	Packaging data	
Management protocols	HTTP, HTTPs (SSL / TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, BOOTP, RARP, APIPA (AutoIP), DHCP, ICMP, DNS, Bonjour, DDNS, mDNS, ARP, NTP, telnet, Finger	Package width	700 mm
		Package depth	760 mm
		Package height	835 mm
		Package weight	75 kg
		Other features	
		Power LED	✓
		Stand-by LED	✓



0734646616157



734646616157

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.