

Lexmark CX923dxe Laser A3 1200 x 1200 DPI 55 ppm

Tuotemerkki : Lexmark

Tuotekoodi: 32C0239

Tuotteen nimi : CX923dxe

Lexmark CX923dxe. Tulostustekniikka: Laser, Tulostus: Väritulostus, Suurin resoluutio: 1200 x 1200 DPI, Tulostusnopeus (väri, normaalilaatu, A4/US Letter): 55 ppm. Kopiointi: Värikopiointi. Skannaus: Väriskannaus, Optinen skannauserottelutarkkuus: 600 x 600 DPI. Faksaus: Värifaksaus. Suurin ISO A-luokan paperikoko: A3. Tuotteen väri: musta, Valkoinen

Printing		Ports & interfaces	
Print technology *	Laser	USB connector	USB Type-A / USB Type-B
Printing *	Colour printing	Network	
Duplex printing *	✓	Ethernet LAN *	✓
Maximum resolution *	1200 x 1200 DPI	Cabling technology	10/100/1000Base-T(X)
Print speed (black, normal quality, A4/US Letter) *	55 ppm	Ethernet LAN data rates	10,100,1000 Mbit/s
Print speed (colour, normal quality, A4/US Letter)	55 ppm	Security algorithms	IPSec, LEAP, MD5, MSCHAPv2, PEAP, SNMPv3, TTLS
Duplex print speed (black, normal quality, A4/US Letter)	55 ppm	Supported network protocols (IPv4)	TCP/IP
Time to first page (black, normal)	5 s	Supported network protocols (IPv6)	TCP/IP
Time to first page (colour, normal)	5 s	Mobile printing technologies	Apple AirPrint
Copying		Performance	
Copying *	Colour copying	Maximum internal memory	4096 MB
Copy speed (black, normal quality, A4)	55 cpm	Internal memory *	2048 MB
Copy speed (colour, normal quality, A4)	55 cpm	Built-in processor	✓
Time to first copy (black, normal)	4.9 s	Processor frequency	1200 MHz
Time to first copy (colour, normal)	5.8 s	Processor cores	4
Copier resize	25 - 400%	Sound pressure level (printing)	52 dB
Scanning		Sound pressure level (duplex printing)	54 dB
Duplex scanning *	✓	Sound pressure level (copying)	56 dB
Scanning *	Colour scanning	Sound pressure level (scanning)	53 dB
Optical scanning resolution *	600 x 600 DPI	Sound power level (standby)	29 dB
Maximum scan area	297 x 432 mm	Design	
Scanner type *	Flatbed & ADF scanner	Product colour *	Black, White
Scan technology	CCD	Market positioning *	Business
Scan to	E-mail, FTP, USB	Built-in display *	✓
Scan speed (colour)	80 ppm	Display diagonal	25.4 cm (10")
Scan speed (black)	80 ppm	Touchscreen	✓
Duplex scan speed (colour)	160 ppm	Control type	Touch
Duplex scan speed (black)	160 ppm	Colour display	✓
Image formats supported	JPG, TIF	Power	
Document formats supported	PDF, XPS	Power consumption (printing)	1075 W
Fax		Power consumption (copying)	1100 W
Faxing *	Colour faxing	Power consumption (scanning)	250 W
Fax transmission speed	3 sec/page	Power consumption (ready)	230 W
Modem speed	33.6 Kbit/s	Power consumption (sleep)	2.9 W
Features		Energy Star Typical Electricity Consumption (TEC)	4.6 kWh/week
Recommended duty cycle	7000 - 50000 pages per month	System requirements	
Maximum duty cycle *	250000 pages per month	Windows operating systems supported	✓
Printing colours *	Cyan, Magenta, Yellow	Mac operating systems supported	✓
Input & output capacity		Linux operating systems supported	✓
Total number of input trays *	3		

Input & output capacity		Operational conditions	
Total input capacity *	3650 sheets	Operating relative humidity (H-H)	15 - 85%
Total output capacity *	250 sheets	Operating temperature (T-T)	10 - 30 °C
Paper input type	Paper tray	Operating altitude	0 - 2500 m
Auto document feeder (ADF)	✓	Certificates	
Auto document feeder (ADF) input capacity	100 sheets	Certification	ICES-003 A, BSMI A, VCCI A, FCC A, NOM-032, UL, cUL, NOM, US FDA/CDRH, IEC 60825-1, CB, ISO-532B, CE (EU) DoC, EFTA (CE), KC, CCC, C-tick DoC, EuP, CECP, CEL, EC 1275/2008, ECMA-370, TED, SII, TER, SABS, UL-AR, GS Mark, Green Dot, ISO-9296, COC, CCD-035 EcoLogo, Green Mark, EPEAT
Maximum number of input trays	4		
Maximum input capacity	6650 sheets		
Maximum output capacity	3500 sheets		
Paper handling		Sustainability	
Maximum ISO A-series paper size *	A3	Sustainability certificates	Blue Angel, ENERGY STAR
Paper tray media types *	Banner, Card stock, Envelopes, Labels, Plain paper	Weight & dimensions	
ISO A-series sizes (A0...A9) *	A3, A4, A5, A6	Width	615 mm
Non-ISO print media sizes	Executive, Folio, Legal, Letter, Oficio, Statement, Universal	Depth	697 mm
Envelopes sizes	7 3/4, 9, 10, B5, C5, DL	Height	1225 mm
Paper tray media weight	60 - 256 g/m ²	Weight	134.5 kg
Multi-Purpose Tray media weight	60 - 256 g/m ²	Packaging data	
Ports & interfaces		Package width	758 mm
Standard interfaces	Ethernet, USB 2.0	Package depth	911 mm
USB port	✓	Package height	1505 mm
		Package weight	168 kg

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 28-DEC-2024. Prints or copies of Information are only valid on the printed Publication date