

## Lexmark CX924dxe Laser A3 1200 x 1200 DPI 65 ppm

**Brand :** Lexmark

**Product code:** 32C0241

**Product name :** CX924dxe

Lexmark CX924dxe. Print technology: Laser, Printing: Colour printing, Maximum resolution: 1200 x 1200 DPI, Print speed (colour, normal quality, A4/US Letter): 65 ppm. Copying: Colour copying. Scanning: Colour scanning, Optical scanning resolution: 600 x 600 DPI. Faxing: Colour faxing. Maximum ISO A-series paper size: A3. Direct printing. Product colour: Black, Grey

|   |   |   |  |
|---|---|---|--|
| <b>Printing</b>                                     |   | <b>Ports &amp; interfaces</b>                     |  |
| Print technology *                                  | Laser   | Standard interfaces                               | Ethernet, USB 2.0                                      |
| Printing *  | Colour printing                                 | Direct printing *                                 | ✓  |
| Duplex printing *                                   | ✓   | USB port  | ✓  |
| Maximum resolution *                                | 1200 x 1200 DPI                                 | USB connector                                     | USB Type-A / USB Type-B                                |
| Print speed (black, normal quality, A4/US Letter) * | 65 ppm  | Optional connectivity                             | Serial (RS-422), Wireless LAN                          |
| Print speed (colour, normal quality, A4/US Letter)  | 65 ppm  | <b>Network</b>                                    |  |
| Duplex print speed (ISO/IEC 24734) mono             | 65 ipm  | Ethernet LAN *                                    | ✓  |
| Time to first page (black, normal)                  | 4.9 s   | Cabling technology                                | 10/100/1000Base-T(X)                                   |
| Time to first page (colour, normal)                 | 4.9 s   | Ethernet LAN data rates                           | 10,100,1000 Mbit/s                                     |
| <b>Copying</b>                                      |   | Security algorithms                               | HTTPS, IPSec, LEAP, MD5, MSCHAPv2, PEAP, SSL/TLS, TTLS |
| Copying *   | Colour copying                                  | Mobile printing technologies                      | Apple AirPrint   |
| Copy speed (black, normal quality, A4)              | 65 cpm  | <b>Performance</b>                                |  |
| Copy speed (colour, normal quality, A4)             | 65 cpm  | Maximum internal memory                           | 4096 MB  |
| Time to first copy (black, normal)                  | 4.8 s   | Internal memory *                                 | 2048 MB  |
| Time to first copy (colour, normal)                 | 5.5 s   | Built-in processor                                | ✓  |
| Copier resize                                       | 25 - 400%                                       | Processor frequency                               | 1200 MHz   |
| <b>Scanning</b>                                     |   | Processor cores                                   | 4  |
| Duplex scanning *                                   | ✓   | Sound pressure level (printing)                   | 55 dB  |
| Scanning *  | Colour scanning                                 | Sound pressure level (duplex printing)            | 55 dB  |
| Optical scanning resolution *                       | 600 x 600 DPI                                   | Sound pressure level (copying)                    | 57 dB  |
| Maximum scan area                                   | 297 x 432 mm                                    | Sound pressure level (scanning)                   | 53 dB  |
| Scanner type *                                      | Flatbed & ADF scanner                           | Sound pressure level (quiet mode)                 | 50 dB  |
| Scan technology                                     | CCD   | Sound power level (standby)                       | 28 dB  |
| Scan to   | E-mail, FTP, PC, USB                            | <b>Design</b>                                     |  |
| Scan speed (colour)                                 | 80 ppm  | Product colour *                                  | Black, Grey  |
| Scan speed (black)                                  | 80 ppm  | Market positioning *                              | Business   |
| Duplex scan speed (colour)                          | 160 ppm   | Built-in display *                                | ✓  |
| Duplex scan speed (black)                           | 160 ppm   | Display diagonal                                  | 6.35 cm (2.5")   |
| Image formats supported                             | JPEG XR, JPG, TIF                               | Touchscreen                                       | ✓  |
| Document formats supported                          | PDF, XPS  | Control type                                      | Touch  |
| <b>Fax</b>  |   | Colour display                                    | ✓  |
| Faxing *  | Colour faxing                                   | <b>Power</b>                                      |  |
| Fax transmission speed                              | 3 sec/page                                      | Power consumption (printing)                      | 1250 W   |
| Modem speed   | 33.6 Kbit/s                                     | Power consumption (copying)                       | 1275 W   |
| <b>Features</b>                                     |   | Power consumption (scanning)                      | 250 W  |
| Recommended duty cycle                              | 8000 - 50000 pages per month                    | Power consumption (ready)                         | 230 W  |
| Maximum duty cycle *                                | 275000 pages per month                          | Power consumption (sleep)                         | 2.9 W  |
| Page description languages                          | PCL 5c, PCL 6, PDF 1.7, PPDS, PostScript 3, XPS | Energy Star Typical Electricity Consumption (TEC) | 5 kWh/week   |
|   |   | <b>System requirements</b>                        |  |
|   |   | Windows operating systems supported               | ✓  |

|  |   |                                   |  |
|--|---|-----------------------------------|--|
| <b>Input &amp; output capacity</b>         |   | <b>System requirements</b>        |  |
| Total number of input trays *              | 4   | Linux operating systems supported | ✓  |
| Total input capacity *                     | 3650 sheets   | <b>Operational conditions</b>     |  |
| Total output capacity *                    | 250 sheets  | Operating relative humidity (H-H) | 15 - 85%   |
| Paper input type                           | Paper tray  | Operating temperature (T-T)       | 10 - 30 °C   |
| Auto document feeder (ADF)                 | ✓   | Operating altitude                | 0 - 2500 m   |
| Auto document feeder (ADF) input capacity  | 100 sheets  | <b>Certificates</b>               |  |
| Auto document feeder (ADF) output capacity | 100 sheets  | Certification                     | ICES-003 Class A, BSMI Class A, VCCI Class A, FCC Class A, NOM-032, UL, cUL, NOM, US FDA/CDRH, IEC 60825-1, CB Report, ISO-532B, CE (EU) DoC, EFTA (CE), KC logo, CCC, C-tick DoC, EuP, CECF, CEL, EC 1275/2008, ECMA-370, TED, SII, TER, SABS, UL-AR, GS Mark, Green Dot, ISO-9296, COC, CCD-035 EcoLogo, Green Mark, EPEAT |
| Maximum number of input trays              | 5   | <b>Sustainability</b>             |  |
| Maximum input capacity                     | 6650 sheets   | Sustainability certificates       | Blue Angel, ENERGY STAR  |
| Maximum output capacity                    | 3500 sheets   | <b>Weight &amp; dimensions</b>    |  |
| <b>Paper handling</b>                      |   | Width                             | 615 mm   |
| Maximum ISO A-series paper size *          | A3  | Depth                             | 697 mm   |
| Paper tray media types *                   | Banner, Card stock, Envelopes, Labels, Plain paper            | Height                            | 1225 mm  |
| Multi-purpose tray media types             | Envelopes, Labels, Plain paper                                | Weight                            | 134.5 kg   |
| ISO A-series sizes (A0...A9) *             | A3, A4, A5, A6  | <b>Packaging data</b>             |  |
| Non-ISO print media sizes                  | Executive, Folio, Legal, Letter, Oficio, Statement, Universal | Package width                     | 758 mm   |
| JIS B-series sizes (B0...B9)               | B5  | Package depth                     | 911 mm   |
| Envelopes sizes                            | 7 3/4, 9, 10, B5, C5, DL                                      | Package height                    | 1505 mm  |
| Paper tray media weight                    | 60 - 256 g/m <sup>2</sup>                                     | Package weight                    | 168 kg   |
| Multi-Purpose Tray media weight            | 60 - 256 g/m <sup>2</sup>                                     | <b>Other features</b>             |  |
|  |   | Duplex                            | ✓  |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 28-DEC-2024. Prints or copies of Information are only valid on the printed Publication date