

Lexmark CX860dte Laser A4 1200 x 1200 DPI 60 ppm

Tuotemerkki : Lexmark

Tuotekoodi: 42K0686

Tuotteen nimi : CX860dte

Lexmark CX860dte. Tulostustekniikka: Laser, Tulostus: Väritulostus, Suurin resoluutio: 1200 x 1200 DPI, Tulostusnopeus (väri, normaalilaatu, A4/US Letter): 60 ppm. Kopiointi: Värikopiointi. Skannaus: Väriskannaus, Optinen skannauserottelutarkkuus: 600 x 1200 DPI. Faksaus: Värifaksaus. Suurin ISO A-luokan paperikoko: A4. Suoratulostus. Tuotteen väri: musta, Valkoinen

Printing		Network	
Print technology *	Laser	Wi-Fi *	✗
Printing *	Colour printing	Ethernet LAN *	✓
Duplex printing *	✓	Cabling technology	10/100/1000Base-T(X)
Maximum resolution *	1200 x 1200 DPI	Ethernet LAN data rates	10,100,1000 Mbit/s
Print speed (black, normal quality, A4/US Letter) *	60 ppm	Security algorithms	LEAP, MD5, PEAP, SSL/TLS
Print speed (colour, normal quality, A4/US Letter)	60 ppm	Supported network protocols (IPv4)	TCP/IP, AppleTalk
Duplex print speed (colour, normal quality, A4/US Letter)	60 ppm	Supported network protocols (IPv6)	TCP/IP, TCP, UDP
Time to first page (black, normal)	6.5 s	Management protocols	HTTP, HTTPs (SSL/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, BOOTP, RARP, APIPA (AutoIP), DHCP, ICMP, DNS, Bonjour, DDNS, mDNS, ARP, NTP, Telnet, Finger
Time to first page (colour, normal)	6.5 s	Security features	SNMPv3
Copying		Performance	
Copying *	Colour copying	Maximum internal memory	4096 MB
Copy speed (black, normal quality, A4)	60 cpm	Internal memory *	2048 MB
Copy speed (colour, normal quality, A4)	60 cpm	Built-in processor	✓
Time to first copy (black, normal)	6.5 s	Processor frequency	1600 MHz
Time to first copy (colour, normal)	7 s	Sound pressure level (printing)	56 dB
Copier resize	25 - 400%	Sound pressure level (duplex printing)	57 dB
Scanning		Sound pressure level (copying)	59 dB
Duplex scanning *	✓	Sound pressure level (scanning)	55 dB
Scanning *	Colour scanning	Sound pressure level (quiet mode)	52 dB
Optical scanning resolution *	600 x 1200 DPI	Sound power level (standby)	14 dB
Maximum scan area	216 x 356 mm	Design	
Scanner type *	Flatbed & ADF scanner	Product colour *	Black, White
Scan technology	CCD	Market positioning *	Business
Scan to	E-mail, FTP, USB	Built-in display *	✓
Scan speed (colour)	60 ppm	Display	LCD
Scan speed (black)	60 ppm	Display diagonal	25.4 cm (10")
Duplex scan speed (colour)	120 ppm	Touchscreen	✓
Duplex scan speed (black)	120 ppm	Control type	Touch
Image formats supported	JPEG XR, JPG	Colour display	✓
Document formats supported	PDF, XPS	Power	
Fax		Power consumption (printing)	870 W
Faxing *	Colour faxing	Power consumption (copying)	650 W
Fax transmission speed	3 sec/page	Power consumption (scanning)	115 W
Modem speed	33.6 Kbit/s	Power consumption (ready)	115 W
		Power consumption (sleep)	3.3 W
Features		Energy Star Typical Electricity Consumption (TEC)	3.5 kWh/week
Recommended duty cycle	5000 - 50000 pages per month		
Maximum duty cycle *	350000 pages per month		
Digital sender	✗		
Number of print cartridges *	1		
Printing colours *	Black, Cyan, Magenta, Yellow		

Features		System requirements	
Page description languages	Microsoft XPS, PCL 5c, PCL 6, PDF 1.7, PPDS, PostScript 3		Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Pro, Windows 10 Pro x64, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8.1, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
All-In-One-multitasking	✓		Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Input & output capacity			Debian 7.0, Debian 8.0, SuSE Linux 10.2, SuSE Linux 10.3, SuSE Linux 11, SuSE Linux 11.1, SuSE Linux 11.2, SuSE Linux 12.0, Ubuntu 12.04, Ubuntu 14.04, Ubuntu 15.04
Total number of input trays *	4		Windows Server 2008, Windows Server 2008 R2, Windows Server 2008 x64, Windows Server 2012, Windows Server 2012 R2
Total input capacity *	1750 sheets	Windows operating systems supported	
Total output capacity *	500 sheets		
Paper input type	Paper tray		
Auto document feeder (ADF)	✓		
Auto document feeder (ADF) input capacity	150 sheets		
Auto document feeder (ADF) output capacity	150 sheets		
Maximum number of input trays	6		
Maximum input capacity	4500 sheets		
Maximum output capacity	1950 sheets		
Paper handling			
Maximum ISO A-series paper size *	A4		
Paper tray media types *	Banner, Card stock, Envelopes, Labels, Plain paper		
ISO A-series sizes (A0...A9) *	A4, A5		
JIS B-series sizes (B0...B9)	B5		
Envelopes sizes	7 3/4, 9, 10, B5, C4, C5, DL		
Ports & interfaces		Mac operating systems supported	
Standard interfaces	Ethernet, USB 2.0		
Direct printing *	✓		
USB port	✓		
USB 2.0 ports quantity	3	Linux operating systems supported	
Optional connectivity	Wireless LAN	Server operating systems supported	
Operational conditions			
Operating relative humidity (H-H)	15 - 80%		
Operating temperature (T-T)	10 - 32 °C		
Operating altitude	0 - 2896 m		
Certificates			
Certification			ENERGY STAR, ICES-003 Class A, BSMI Class A, VCCI Class A, FCC Class A, NOM-032, UL, cUL, NOM, US FDA/CDRH, IEC 60825-1, CB Report, ISO-532B, CE (EU) DoC, EFTA (CE), KC logo, CCC, C-tick DoC, EuP, CECP, CEL, EC 1275/2008, ECMA-370, TED, SII, TER, SABS, UL-AR, GS Mark, Green Dot, ISO-9296, COC, CCD-035 EcoLogo, Green Mark, EPEAT, Blue Angel (Blauer Engel)
Sustainability			
Sustainability certificates			ENERGY STAR
Weight & dimensions			
Width	559 mm		
Depth	588 mm		
Height	1162 mm		
Weight	131.3 kg		
Packaging data			
Package width	762 mm		
Package depth	830 mm		
Package height	1380 mm		

Packaging data

Package weight	157.4 kg
----------------	----------

Other features

Finishing option	✓
------------------	---



0734646617079



734646617079

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.