

## Lexmark MS825dn 1200 x 1200 DPI A4

**Brand :** Lexmark

**Product code:** 50G0321

**Product name :** MS825dn

Lexmark MS825dn. Print technology: Laser. Maximum duty cycle: 350000 pages per month. Maximum resolution: 1200 x 1200 DPI. Maximum ISO A-series paper size: A4. Print speed (black, normal quality, A4/US Letter): 66 ppm, Duplex printing. Display: LCD, Product colour: Black, White

Printing		Performance	
Colour *	✗	Sound pressure level (printing)	58 dB
Print technology *	Laser	Sound pressure level (duplex printing)	58 dB
Duplex printing *	✓	<b>Design</b>	
Maximum resolution *	1200 x 1200 DPI	Product colour *	Black, White
Print speed (black, normal quality, A4/US Letter) *	66 ppm	Built-in display *	✓
Duplex print speed (black, normal quality, A4/US Letter)	40 ppm	Display	LCD
Time to first page (black, normal)	4 s	Colour display	✓
<b>Features</b>		Display diagonal	6.35 cm (2.5")
Maximum duty cycle *	350000 pages per month	Touchscreen	✓
Recommended duty cycle	5000 - 100000 pages per month	Control type	Touch
Printing colours *	Black	Certification	AL-UZ 205, ICES-003 Class A, BSMI Class A, VCCI Class A, US FDA, UL 60950-1, FCC Class A, cUL CAN / CSA-C22.2 60950-1, NOM, CB, EN / IEC 60950-1, CB EN / IEC 60825-1, CE DoC (EN 62301 Class A, EN 62311, CE EN / IEC 60950-1, CE EN / IEC 60825-1, EN 61000-3, EN 55022 Class A, EuP, EN 55024, UL), EFTA (CE), KCC, CCC, CECP, CEL, C-tick DoC, UL-AR, KC mark, UL GS mark, EC 1275, MET-I, ISO 532B , ECMA-370, TED, GOST-R, SII, TER
Page description languages *	Microsoft XPS, PCL 5e, PCL 6, PDF 1.7, PPDS, PostScript 3, XHTML		
<b>Input &amp; output capacity</b>		<b>Power</b>	
Total number of input trays *	2	Power consumption (ready)	38.4 W
Total input capacity *	650 sheets	Power consumption (standby)	0.2 W
Total output capacity *	550 sheets	Energy Star Typical Electricity Consumption (TEC)	0.95 kWh/week
Paper input type	Paper tray	<b>System requirements</b>	
Maximum number of input trays	6	Windows operating systems supported	✓
Maximum input capacity	4400 sheets	Mac operating systems supported	✓
Maximum output capacity	2550 sheets	Linux operating systems supported	✓
<b>Paper handling</b>		Server operating systems supported	SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 11, SUSE Linux Enterprise Server 12, Windows 2000 Server
Maximum ISO A-series paper size *	A4	<b>Operational conditions</b>	
Paper tray media types *	Card stock, Envelopes, Labels, Plain paper, Transparencies	Operating temperature (T-T)	10 - 32 °C
Multi-purpose tray media types	Envelopes, Executive, Labels, Legal, Letter, Plain paper, Transparencies	Operating relative humidity (H-H)	8 - 80%
ISO A-series sizes (A0...A9) *	A4, A5, A6	Operating altitude	0 - 2896 m
Non-ISO print media sizes	Executive, Folio, Legal, Letter, Oficio, Statement, Universal	<b>Sustainability</b>	
JIS B-series sizes (B0...B9)	B5	Sustainability certificates	Blue Angel, ENERGY STAR
Envelopes sizes	7 3/4, 9, 10, B5, C5, DL	<b>Weight &amp; dimensions</b>	
Paper tray media weight	60 - 176 g/m <sup>2</sup>	Width	445 mm
<b>Ports &amp; interfaces</b>		Depth	510 mm
Direct printing *	✓	Height	428 mm
USB port *	✓		
USB connector	USB Type-A / USB Type-B		
Optional connectivity	Parallel, Wireless LAN		
<b>Network</b>			
Ethernet LAN *	✓		
Cabling technology	10/100/1000Base-T(X)		
Ethernet LAN data rates	10,100,1000 Mbit/s		

Network		Weight & dimensions	
Security algorithms	HTTPS, IPSec, LEAP, MD5, MSCHAPv2, PEAP, SNMP, SNMPv3, SSL/TLS, TTLS	Weight	25.4 kg
Performance		Packaging data	
Internal memory *	512 MB	Package width	565 mm
Maximum internal memory	4608 MB	Package depth	650 mm
Built-in processor	✓	Package height	550 mm
Processor frequency	1000 MHz	Package weight	29.9 kg
Processor cores	2		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 28-DEC-2024. Prints or copies of Information are only valid on the printed Publication date