KYOCERA ECOSYS P5026cdw Väri 9600 x 600 DPI A4 Wi-Fi

Tuotemerkki : KYOCERA   **Tuoteperhe:** ECOSYS   **Tuotekoodi:** 1102RB3NL0

Tuotteen nimi : P5026cdw

KYOCERA ECOSYS P5026cdw. Tulostustekniikka: Laser, Väri. Värikasettien määrä: 4, Suurin toimintajakso: 50000 sivua kuukaudessa. Suurin resoluutio: 9600 x 600 DPI. Suurin ISO A-luokan paperikoko: A4. Tulostusnopeus (musta, normaalilaatu, A4/US Letter): 26 ppm, Kaksipuolinen tulostus. Näyttö: LCD. Verkkovalmius, Wi-Fi. Tuotteen väri: musta, Valkoinen

Printing

Duplex printing mode	Auto
Print resolution colour	1200 x 1200 DPI
Print resolution black	1200 x 1200 DPI
Print speed (colour, normal quality, A4/US Letter)	26 ppm
Colour *	✔
Print technology *	Laser
Duplex printing *	✔
Maximum resolution *	9600 x 600 DPI
Print speed (black, normal quality, A4/US Letter) *	26 ppm
Duplex print speed (black, normal quality, A4/US Letter)	13 ppm
Duplex print speed (colour, normal quality, A4/US Letter)	13 ppm
Warm-up time	29 s
Time to first page (black, normal)	9.5 s
Time to first page (colour, normal)	10.5 s
Economical printing	✔

Features

Maximum duty cycle *	50000 pages per month
Recommended duty cycle	1000 - 2000 pages per month
Printing colours *	Black, Cyan, Magenta, Yellow
Number of print cartridges *	4
Page description languages *	Microsoft XPS, PCL 5c, PCL 6, PCL XL, PostScript 3

Performance

Internal memory *	512 MB
Maximum internal memory	512 MB
Card reader integrated	✔
Compatible memory cards	SD, SDHC
Built-in processor	✔
Processor family	ARM Cortex
Processor model	A9
Processor frequency	800 MHz
Sound pressure level (printing)	47.4 dB
Noise level (ready)	30 dB
Sound pressure level (quiet mode)	43.4 dB

Design

Market positioning *	Home & office
Product colour *	Black, White
Built-in display *	✔
Display	LCD
Colour display	✘
Control type	Buttons
Certification	GS, TüV, CE

Certificates

Waste Electrical and Electronic Equipment (WEEE) compliance	✔

Power

Power consumption (printing) *	375 W
Power consumption (standby)	33 W

Features

Replacement cartridges	TK-5240K (4.000 pagina's) TK-5240CMY (3.000 pagina's)

Input & output capacity

Total number of input trays *	1
Total input capacity *	250 sheets
Total output capacity *	150 sheets
Paper tray 1 input capacity	250 sheets
Paper input type	Cassette, Paper tray
Multi-Purpose tray	✔
Multi-Purpose tray input capacity	50 sheets
Maximum number of input trays	2
Maximum input capacity	550 sheets
Maximum output capacity	150 sheets

Paper handling

Maximum ISO A-series paper size *	A4
Maximum print size	216 x 356 mm
Paper tray media types *	Plain paper
ISO A-series sizes (A0...A9) *	A4, A5, A6
ISO B-series sizes (B0...B9)	B5, B6
Non-ISO print media sizes	Legal, Letter
Custom media width	70 - 216 mm
Custom media length	148 - 356 mm
Paper tray media weight	60 - 163 g/m²
Multi-Purpose Tray media weight	60 - 220 g/m²
Duplex media weight	60 - 120 g/m²

Ports & interfaces

Standard interfaces	Ethernet, USB 2.0, Wireless LAN
Direct printing *	✔
USB port *	✔
USB 2.0 ports quantity	2

Network

Network ready	✔
Wi-Fi *	✔
Ethernet LAN *	✔
Cabling technology	10/100/1000Base-T(X)
Ethernet LAN data rates	10,100,1000 Mbit/s
Wi-Fi Direct	✔
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Near Field Communication (NFC)	✘
Bluetooth	✘
Security algorithms	802.1x RADIUS, HTTPS, IPPS, IPSEC, SNMPv3
Mobile printing technologies	Apple AirPrint, Google Cloud Print, Kyocera Mobile Print, Mopria Print Service

Power

Power consumption (PowerSave)	0.9 W
Power consumption (off)	0.2 W
Energy Star Typical Electricity Consumption (TEC)	0.94 kWh/week
AC input voltage	220 - 240 V
AC input frequency	50 - 60 Hz

System requirements

Windows operating systems supported	✔
Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Linux operating systems supported	✔

Operational conditions

Operating temperature (T-T)	10 - 32.5 °C
Storage temperature (T-T)	-20 - 40 °C
Operating relative humidity (H-H)	10 - 80%
Storage relative humidity (H-H)	10 - 90%
Operating altitude	0 - 3500 m
Non-operating altitude	0.6 - 15000 m

Sustainability

Sustainability certificates	Blue Angel, EPEAT Silver, ENERGY STAR

Weight & dimensions

Width	410 mm
Depth	410 mm
Height	329 mm
Weight	21 kg

Packaging data

Package width	592 mm
Package depth	567 mm
Package height	460 mm
Package weight	27 kg

Packaging content

Cartridge(s) included	✔
Included cartridge capacity (black)	1200 pages
Included cartridge capacity (CMY)	1200 pages
Cables included	AC

Logistics data

Harmonized System (HS) code	84433210

Technical details

Compliance certificates	CE, REACH, RoHS

0632983036631

632983036631

6329830366310