

## Epson TM-L90 (465): Ethernet E04+Built-in USB, PS, EDG

**Tuotemerkki :** Epson

**Tuotekoodi:** C31C412465

**Tuotteen nimi :** TM-L90 (465): Ethernet E04+Built-in USB, PS, EDG

Epson TM-L90 (465): Ethernet E04+Built-in USB, PS, EDG. Tulostustekniikka: Suoralämpö, Suurin resoluutio: 203 x 203 DPI, Tulostusnopeus: 150 mm/s. Tuetut paperin leveydet: 80 mm. Yhteysteknologia: Langallinen. Tuotteen väri: Harmaa



Printing		Operational conditions	
Print technology *	Direct thermal	Storage relative humidity (H-H)	10 - 90%
Colour *	✗	Operating temperature (T-T)	5 - 45 °C
Maximum resolution *	203 x 203 DPI	Storage temperature (T-T)	-10 - 50 °C
Print speed *	150 mm/sec	<b>Weight &amp; dimensions</b>	
Printing characters	Barcode	Width	140 mm
<b>Paper handling</b>		Depth	148 mm
Autocutter	✓	Height	203 mm
Half-cutter	✗	Weight	1.9 kg
Maximum roll diameter	9 cm	<b>Packaging data</b>	
Media thickness	0.06 - 0.08 mm	Quantity per pack	1 pc(s)
Supported paper width	80 mm	Package width	193 mm
Autocutter durability	2 million cuts	Package depth	250 mm
<b>Ports &amp; interfaces</b>		Package height	240 mm
Connectivity technology *	Wired	Package weight	2.8 kg
Ethernet LAN *	✓	<b>Packaging content</b>	
USB port *	✓	Manual	✓
USB 2.0 ports quantity	1	<b>Logistics data</b>	
<b>Performance</b>		Products per pallet layer	16 pc(s)
Tape cutting	Automatic	Products per pallet layer (UK)	24 pc(s)
Character pitch	22.6,16.9 cpi	Products per pallet (UK)	168 pc(s)
Mean time between failures (MTBF)	260000 h	Pallet weight (UK)	0 g
Mean cycles between failures (MCBF)	70000000	Pallet length (UK)	120 cm
Cutter	✓	Pallet width (UK)	100 cm
Certification	VCCI-Class A, FCC-Class A, CE, AS / NZS 3548	Pallet height (UK)	2.5 m
<b>Design</b>		Harmonized System (HS) code	84433210
Product colour *	Grey	Pallet gross width	80 cm
<b>Power</b>		Pallet gross length	120 cm
AC input voltage	24 V	Pallet gross height	2.5 m
Power consumption	1800 mA	Pallet gross weight	0 g
		Products per pallet	112 pc(s)
		<b>Other features</b>	

Operational conditions		Other features	
Operating relative humidity (H-H)	10 - 90%	Safety	UL, CSA, TÜV
		Buffer size	4 KB
		Character sets	ANK
		Country of origin	China



8715946616988

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-FEB-2025. Prints or copies of Information are only valid on the printed Publication date