

TP-Link TL-SG1005P Hallitsematon Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki musta

Tuotemerkki : TP-Link Tuotekoodi: TL-SG1005P V1

Tuotteen nimi: TL-SG1005P



TP-Link TL-SG1005P. Kytkin tyyppi: Hallitsematon. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 5. MAC-osoitetaulukko: 2000 entries, Kytkentäkapasiteetti: 10 Gbit/s. Verkkostandardit: IEEE 802.1p, IEEE 802.3, IEEE 802.3af, IEEE 802.3u, IEEE 802.3x. DC-syöttöjännite: 48 V. Power over Ethernet -tuki



Management features		Power	
Switch type *	Unmanaged	Power source *	DC/PoE
Quality of Service (QoS) support	✓	Power supply included *	✓
Ports & interfaces		DC input voltage	48 V
Basic switching RJ-45 Ethernet ports quantity *	5	Input current Power consumption (max)	1.25 A 64.44 W
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power over Ethernet (PoE)	
Gigabit Ethernet (copper) ports quantity	5	Power over Ethernet (PoE) * Power over Ethernet (PoE) ports	4
Network		quantity Total Power over Ethernet (PoE)	
Networking standards *	IEEE 802.1p, IEEE 802.3, IEEE	budget	56 W
3	802.3af, IEEE 802.3u, IEEE 802.3x	Operational conditions	
10G support *	×	Operating temperature (T-T)	0 - 40 °C
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T	Storage temperature (T-T)	-40 - 70 °C
Cable types supported	Cat3, Cat4, Cat5, Cat5e, Cat6	Operating relative humidity (H-H)	10 - 90%
Flow control support	1	Storage relative humidity (H-H)	5 - 90%
Auto MDI/MDI-X		Heat dissipation	219.87 BTU/h
Auto-negotiation	✓	Weight & dimensions	
MAC address auto-learning supported	✓	Width Depth	99.8 mm 98 mm
MAC address auto-aging supported	✓	Height	25 mm
Data transmission		Packaging content	
Switching capacity *	10 Gbit/s	User guide	✓
Forwarding rate	7.44 Mpps 2000 entries	Packaging data	
MAC address table * Store-and-forward		AC adapter included	✓
		Package type	Вох

Security		Packaging data
IGMP snooping	✓	Package width 131 mm
Design		Package depth 196 mm Package height 121 mm
Rack mounting *	×	Package weight 800 g
tackable * roduct colour	X	Sustainability
LED indicators		Sustainability compliance ✓
Performance		Certificates
Maximum cable length 100 m Fanless ✓	100 m	Compliance certificates CE, Federal Communications Commission (FCC), RoHS
	✓	Logistics data
		Harmonized System (HS) code 85176990









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.