## **ATEN**

## ATEN KA8288-AX-G KVM-kytkin Telineasennus musta

Tuotemerkki : ATEN Tuotekoodi: KA8288-AX-G

Tuotteen nimi: KA8288-AX-G







Ports & interfaces		Sustainability	
Keyboard port type *	USB	Compliance certificates	RoHS
Video port type * H HDMI ports quantity 2 USB connector type U	USB HDMI 2 USB Type-A DE-9 (DB-9)	Operational conditions	
		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C -20 - 60 °C 0 - 80%
Serial ports quantity	1	Weight & dimensions	
dio connections  adphone outputs  imber of microphone inputs  in jack	Width Depth Height Weight	155.4 mm 174.2 mm 28.8 mm 1.29 kg	
Network		Packaging data	
Ethernet LAN Ethernet LAN (RJ-45) ports Performance	1	Package width Package depth Package height Package weight	98 mm 325 mm 210 mm 1.49 kg
HD type *	Full HD+	Packaging content	
Maximum resolution * Video bandwidth	1920 x 1200 pixels 60 Hz	Cables included Manual	AC ✓
Design		AC adapter included	· •
Rack mounting *		Logistics data	
Product colour * Housing material LED indicators Push button	using material Metal D indicators Power	Master (outer) case net weight Harmonized System (HS) code Master (outer) case width Master (outer) case length	6.45 kg 85176200 342 mm 512 mm
Display		Master (outer) case height	232 mm
Built-in display *	×	Master (outer) case gross weight	8.19 kg
Power		Products per master (outer) case	5 pc(s)
Power source Input voltage Power consumption (typical)	DC 5.3 V 6.53 W		

