## **ATEN**

## ATEN CN8000A-AT-G KVM-kytkin Telineasennus musta

Tuotemerkki : ATEN

Tuotekoodi: CN8000A-AT-G

Tuotteen nimi : CN8000A-AT-G


ATEN CN8000A-AT-G. Näppäimistöportin liitin: USB, PS/2, Hiiriportin liitin: USB, PS/2, Videoportin tyyppi: VGA. Tietoturva-algoritmit: TLS. Enimmäiserottelutarkkuus: 1920 x 1200 pikseliä, Videokaistanleveys: 60 Hz, Käyttäjien määrä: 64 käyttäjä (t). Tuotteen väri: musta, Kotelon materiaali: Metalli. Voimanlähde: DC, Tulojännite: 5.3 V, Virrankulutus: 7,26 W



Ports & interfaces		System requirements	
Number of computers controlled * Keyboard port type * Mouse port type * Video port type * Console ports * USB connector type Serial port type Serial ports quantity DC-in jack	1 USB, PS/2 USB, PS/2 VGA USB B, VGA (D-Sub) Mini-USB B RS-232 1	Linux operating systems supported Mac operating systems supported	1
		Sustainability	
		Compliance certificates	RoHS
		Operational conditions	
		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	0 - 50 °C -20 - 60 °C 0 - 80%
Network		Weight & dimensions	
Ethernet LAN Ethernet LAN (RJ-45) ports Security algorithms <b>Performance</b>	✓ 1 TLS	Width Depth Height Weight	81.4 mm 25 mm 200 mm 1.05 kg
Maximum resolution *	1920 x 1200 pixels	Packaging data	
Video bandwidth	60 Hz	Package width	100 mm
DDC2B support	✓	Package depth	283 mm
Number of users	64 user(s)	Package height	173 mm
Firmware upgradeable	✓	Package weight	1.23 kg
Design		Packaging content	
Rack mounting *	✓	Cables included	USB
Product colour *	Black	Manual	
Housing material	Metal	AC adapter included	
LED indicators	<ul> <li>Image: A start of the start of</li></ul>	Rack mount kit	1
Push button	1	Logistics data	
Display		Master (outer) case net weight	5.25 kg
Built-in display *	×	Harmonized System (HS) code Master (outer) case width	85176200 292 mm
Power		Master (outer) case length	517 mm
Power source	DC	Master (outer) case height	194 mm
Input voltage	5.3 V	Master (outer) case gross weight	6.66 kg
Power consumption (typical)	7.26 W	Products per master (outer) case	5 pc(s)
External power adapter	✓		

Windows operating systems supported

1



4719264644979

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.