

# KYOCERA ECOSYS M4125idn Laser A3 1200 x 1200 DPI 25 ppm

**Tuotemerkki :** KYOCERA

**Tuoteperhe:** ECOSYS

**Tuotekoodi:** 1102P23NLO

**Tuotteen nimi :** M4125idn

KYOCERA ECOSYS M4125idn. Tulostustekniikka: Laser, Tulostus: Yksittäistulostus, Suurin resoluutio: 1200 x 1200 DPI. Kopiointi: Yksittäiskopiointi, Kopioinnin enimmäistarkkuus: 600 x 600 DPI. Skannaus: Väriskannaus, Optinen skannauserottelutarkkuus: 600 x 600 DPI. Kaksipuolinen toiminto: Kopiointi, Faksi, Tulosta, Skannaus. Suurin ISO A-luokan paperikoko: A3. Suoratulostus. Tuotteen väri: musta, Valkoinen

| Printing   |                 | Paper handling                          |  |
|--|-----------------|---|--|
| Duplex printing mode                                     | Auto/Manual     | Multi-Purpose Tray media weight         | 45 - 256 g/m <sup>2</sup>  |
| Print technology *                                       | Laser           | Auto Document Feeder (ADF) media weight | 45 - 160 g/m <sup>2</sup>  |
| Printing *   | Mono printing   | Duplex media weight                     | 60 - 163 g/m <sup>2</sup>  |
| Duplex printing *  | ✓               | Media thickness (min)                   | 0.11 mm  |
| Maximum resolution *                                     | 1200 x 1200 DPI | Ports & interfaces                      |  |
| Print speed (black, normal quality, A4/US Letter) *      | 25 ppm          | Standard interfaces                     | Ethernet, USB 2.0  |
| Print speed (black, normal quality, A3)                  | 12 ppm          | Direct printing *                       | ✓  |
| Duplex print speed (black, normal quality, A4/US Letter) | 22 ppm          | USB port                                | ✓  |
| Warm-up time   | 20 s            | USB 2.0 ports quantity                  | 3  |
| Time to first page (black, normal)                       | 5.8 s           | Optional connectivity                   | Ethernet, Wireless LAN   |
| N-in-1 print function                                    | ✓               | Network                                 |  |
| Skip blank page function                                 | ✓               | Wi-Fi *                                 | ✗  |
| N-up printing  | 2, 4            | Ethernet LAN *                          | ✓  |
| Barcode printing   | ✓               | Cabling technology                      | 10/100/1000Base-T(X)   |
| Watermark printing                                       | ✓               | Ethernet LAN data rates                 | 10,100,1000 Mbit/s   |
| Secure printing  | ✓               | Bluetooth                               | ✗  |
| Poster printing function                                 | ✓               | Near Field Communication (NFC)          | ✗  |
| Secure PDF printing function                             | ✓               | Mobile printing technologies            | Apple AirPrint, Google Cloud Print, Kyocera Mobile Print, Mopria Print Service |
| Eco printing function                                    | ✓               | Performance                             |  |
| Copying  |                 | Maximum internal memory                 | 3000 MB  |
| Duplex copying *   | ✓               | Internal memory *                       | 1000 MB  |
| Duplex copying mode                                      | Auto            | Compatible memory cards                 | SD   |
| Copying *  | Mono copying    | Built-in processor                      | ✓  |
| Maximum copy resolution *                                | 600 x 600 DPI   | Processor family                        | ARM Cortex-A9  |
| Copy speed (black, normal quality, A4)                   | 25 cpm          | Processor frequency                     | 1200 MHz   |
| Copy speed (black, normal quality, A3)                   | 12 cpm          | Processor cores                         | 2  |
| Time to first copy (black, normal)                       | 7 s             | Sound pressure level (printing)         | 49 dB  |
| Maximum number of copies                                 | 999 copies      | Sound pressure level (copying)          | 49 dB  |
| Copier resize  | 25 - 400%       | Sound power level (standby)             | 34 dB  |
| N-in-1 copy function                                     | ✓               | Design                                  |  |
| N-in-1 copy function (N=)                                | 2, 4            | Product colour *                        | Black, White   |
| Copy programming function                                | ✓               | Market positioning *                    | Business   |
| ID-card copy function                                    | ✓               | Built-in display *                      | ✓  |
| Scanning   |                 | Display                                 | TFT  |
| Duplex scanning *  | ✓               | Display diagonal                        | 10.9 cm (4.3")   |
| Duplex scanning mode                                     | Auto            | Touchscreen                             | ✓  |
| Scanning *   | Colour scanning | Control type                            | Touch  |
| Optical scanning resolution *                            | 600 x 600 DPI   | Colour display                          | ✓  |
| Maximum scan area  | 297 x 420 mm    |   |  |

|   |   |   |  |
|---|---|---|--|
| <b>Scanning</b>                           |   | <b>Power</b>  |  |
| Scanner type *                            | Flatbed & ADF scanner                                       | Power consumption (average operating)                       | 410 W  |
| Scan technology                           | CIS/CCD   | Power consumption (PowerSave)                               | 45 W   |
| Scan to                                   | E-mail, FTP, SMB, USB                                       | Power consumption (printing)                                | 410 W  |
| Scan speed (colour)                       | 50 ppm  | Power consumption (copying)                                 | 410 W  |
| Scan speed (black)                        | 50 ppm  | Power consumption (ready)                                   | 65 W   |
| Image formats supported                   | JPG, MMR, TIF   | Power consumption (sleep)                                   | 0.5 W  |
| Document formats supported                | PDF, XPS  | Power consumption (off)                                     | 0.1 W  |
| Greyscale levels                          | 256   | Energy Star Typical Electricity Consumption (TEC)           | 0.96 kWh/week  |
| Scan drivers                              | TWAIN, WIA  | AC input voltage  | 220 - 240 V  |
| <b>Fax</b>                                |   | AC input frequency  | 50 - 60 Hz   |
| Duplex faxing                             | ✓   | <b>System requirements</b>                                  |  |
| Faxing *                                  | ✗   | Windows operating systems supported                         | ✓  |
| Fax resolution (black)                    | 400 x 400 DPI   |   | Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks |
| Fax transmission speed                    | 33.6 sec/page   | Mac operating systems supported                             |  |
| Modem speed                               | 33.6 Kbit/s   |   |  |
| Fax memory                                | 700 pages   | Linux operating systems supported                           | ✓  |
| Fax coding methods                        | JBIG, MH, MMR, MR   | <b>Operational conditions</b>                               |  |
| <b>Features</b>                           |   | Operating relative humidity (H-H)                           | 10 - 80%   |
| Recommended duty cycle                    | 4000 - 8000 pages per month                                 | Storage temperature (T-T)                                   | -20 - 40 °C  |
| Maximum duty cycle *                      | 15000 pages per month                                       | Operating temperature (T-T)                                 | 10 - 32.5 °C   |
| Duplex functions *                        | Copy, Fax, Print, Scan                                      | Storage relative humidity (H-H)                             | 10 - 90%   |
| Digital sender                            | ✓   | Operating altitude  | 0 - 3500 m   |
| Number of print cartridges *              | 1   | Non-operating altitude                                      | 0.6 - 15000 m  |
| Printing colours *                        | Black   | <b>Certificates</b>   |  |
| Page description languages                | Microsoft XPS, OpenXPS, PCL 5e, PCL 6, PCL XL, PostScript 3 | Waste Electrical and Electronic Equipment (WEEE) compliance | ✓  |
| Number of printer fonts                   | 101   | Certification   | TÜV/GS, CE   |
| Optional functions                        | Fax   | <b>Sustainability</b>                                       |  |
| Replacement cartridges                    | TK-6115 (15.000 pagina's)                                   | Sustainability certificates                                 | Blue Angel, EPEAT Silver, ENERGY STAR  |
| <b>Input &amp; output capacity</b>        |   | <b>Weight &amp; dimensions</b>                              |  |
| Total number of input trays *             | 1   | Width   | 590 mm   |
| Total input capacity *                    | 500 sheets  | Depth   | 590 mm   |
| Total output capacity *                   | 300 sheets  | Height  | 688 mm   |
| Paper tray 1 input capacity               | 500 sheets  | Weight  | 49 kg  |
| Multi-Purpose tray                        | ✓   | <b>Packaging data</b>                                       |  |
| Multi-Purpose tray input capacity         | 100 sheets  | Package width   | 760 mm   |
| Paper input type                          | Cassette, Paper tray  | Package depth   | 760 mm   |
| Auto document feeder (ADF)                | ✓   | Package height  | 911 mm   |
| Auto document feeder (ADF) input capacity | 50 sheets   | Package weight  | 72 kg  |
| Maximum number of input trays             | 3   | <b>Packaging content</b>                                    |  |
| Maximum input capacity                    | 1600 sheets   | Cartridge(s) included                                       | ✓  |
| Maximum output capacity                   | 300 sheets  | Included cartridge capacity (black)                         | 3000 pages   |
| <b>Paper handling</b>                     |   | Imaging unit included                                       | ✓  |
| Maximum ISO A-series paper size *         | A3  | Cables included   | AC   |
| Maximum print size                        | 297 x 432 mm  | Drivers included  | ✓  |
| Paper tray media types *                  | Plain paper   | Power cord included   | ✓  |
| Multi-purpose tray media types            | Legal, Letter   | Quick installation guide                                    | ✓  |
| ISO A-series sizes (A0...A9) *            | A3, A4, A5, A6  | <b>Logistics data</b>                                       |  |
| ISO B-series sizes (B0...B9)              | B5  | Harmonized System (HS) code                                 | 84433100   |
| Non-ISO print media sizes                 | Folio, Ledger (media size), Legal, Letter                   |   |  |
| Custom media width                        | 98 - 297 mm   |   |  |
| Custom media length                       | 148 - 432 mm  |   |  |
| Paper tray media weight                   | 60 - 163 g/m <sup>2</sup>                                   |   |  |

**Technical details**

|                         |             |
|-------------------------|-------------|
| Compliance certificates | REACH, RoHS |
|-------------------------|-------------|

**Other features**

|                    |   |
|--------------------|---|
| Finishing option   | ✘ |
| Energy saving mode | ✔ |



0632983041512



632983041512

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.