## KYOCERA ECOSYS M8130cidn Laser A3 9600 x 600 DPI 30 ppm

Tuotemerkki : KYOCERA Tuoteperhe: ECOSYS Tuotekoodi: 1102P33NL0

Tuotteen nimi: M8130cidn

KYOCERA ECOSYS M8130cidn. Tulostustekniikka: Laser, Tulostus: Väritulostus, Suurin resoluutio: 9600 x 600 DPI, Tulostusnopeus (väri, normaalilaatu, A4/US Letter): 30 ppm. Kopiointi: Värikopiointi, Kopioinnin enimmäistarkkuus: 600 x 600 DPI. Skannaus: Väriskannaus, Optinen skannauserottelutarkkuus: 600 x 600 DPI. Kaksipuolinen toiminto: Kopiointi, Tulosta, Skannaus. Suurin ISO A-luokan paperikoko: A3. Suoratulostus. Tuotteen väri: musta, Valkoinen

Printing		Paper handling	
Printing  Duplex printing mode  Print resolution colour  Print resolution black  Print technology *  Printing *  Duplex printing *  Maximum resolution *  Print speed (black, normal quality, A4/US Letter) *  Print speed (colour, normal quality, A4/US Letter)  Print speed (black, normal quality, A3)  Print speed (colour, normal quality, A3)	Auto/Manual 1200 x 1200 DPI 1200 x 1200 DPI Laser Colour printing  9600 x 600 DPI 30 ppm 30 ppm 15 ppm	Paper handling  Multi-purpose tray media types ISO A-series sizes (A0A9) * ISO B-series sizes (B0B9)  Non-ISO print media sizes  Custom media width  Custom media length  Paper tray media weight  Multi-Purpose Tray media weight  Duplex media weight  Media thickness (min)  Ports & interfaces  Standard interfaces	Legal, Letter A3, A4, A5, A6 B5 Folio, Ledger (media size), Legal, Letter 98 - 297 mm 148 - 432 mm 60 - 256 g/m² 60 - 256 g/m² 60 - 220 g/m² 0.11 mm
Print speed (colour, normal quality, A3)  Duplex print speed (black, normal quality, A4/US Letter)	15 ppm 26 ppm	Direct printing * USB port	✓ ✓
Duplex print speed (colour, normal quality, A4/US Letter)	26 ppm	USB 2.0 ports quantity Optional connectivity	3 Ethernet, Wireless LAN
Warm-up time Time to first page (black, normal) Time to first page (colour, normal) N-in-1 print function N-up printing Barcode printing Watermark printing Economical printing Secure printing Poster printing function Secure PDF printing function	30 s 6.5 s 8.3 s  2, 4  4  4  4  4  4  4  4  4  4  4  4  4	Network Wi-Fi * Ethernet LAN * Cabling technology Ethernet LAN data rates Bluetooth Near Field Communication (NFC) Email protocols Email over SSL Mobile printing technologies	X  10/100/1000Base-T(X)  10,100,1000 Mbit/s  X  POP3, SMTP  Apple AirPrint, Google Cloud Print, Kyocera Mobile Print, Mopria Print Service
Copying		Performance	
Duplex copying * Duplex copying mode Copying * Maximum copy resolution * Copy speed (black, normal quality, A4) Copy speed (colour, normal quality,	Auto Colour copying 600 x 600 DPI 30 cpm	Maximum internal memory Card reader integrated Internal memory * Compatible memory cards Built-in processor Processor family	3000 MB  ✓ 1500 MB  SD  ✓ ARM Cortex-A9
A4) Copy speed (black, normal quality, A3) Copy speed (colour, normal quality, A3)	30 cpm 15 cpm 15 cpm	Processor frequency Processor cores Sound pressure level (printing) Sound pressure level (copying)	1200 MHz 2 54 dB 54 dB
Duplex copy speed (black, US Letter)	26 ppm	Sound pressure level (standby)  Design	34 dB
Time to first copy (black, normal)	6.5 s	Product colour *	Black, White

Copying		Design	
Time to first copy (colour, normal)	8.3 s	Market positioning *	Business
Maximum number of copies	999 copies	Built-in display *	✓
Copier resize	25 - 400%	Display	TFT
N-in-1 copy function	✓	Display diagonal	17.8 cm (7")
N-in-1 copy function (N=)	2, 4	Touchscreen	✓
Copy programming function	✓	Control type	Touch
ID-card copy function	✓	Colour display	✓
Scanning		Power	
Duplex scanning *	•	Power consumption (average operating)	580 W
Duplex scanning mode	Auto	Power consumption (printing)	600 W
Scanning *	Colour scanning	Power consumption (copying)	600 W
Optical scanning resolution *	600 x 600 DPI	Power consumption (ready)	70 W
Maximum scan area	297 x 420 mm	Power consumption (sleep)	0.5 W
Scanner type *	Flatbed & ADF scanner	Power consumption (off)	0.1 W
Scan technology	CIS/CCD	Energy Star Typical Electricity	1.20 kWh (wools
Scan to	E-mail, FTP, SMB, TWAIN, USB, WIA	Consumption (TEC)	1.39 kWh/week
Scan speed (colour)	50 ppm	AC input voltage	220 - 240 V
Scan speed (black) Duplex scan speed (colour)	50 ppm 16 ppm	AC input frequency	50 - 60 Hz
Duplex scan speed (black)	16 ppm	System requirements	
Image formats supported	JPEG, MMR, TIFF	Windows operating systems	<b>✓</b>
Document formats supported	PDF, XPS	supported	
Greyscale levels	256		Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12
Scan drivers	TWAIN, WIA		Sierra, Mac OS X 10.13 High Sierra,
Fax			Mac OS X 10.14 Mojave, Mac OS X
	,	Mac operating systems supported	10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow
Duplex faxing	<b>✓</b>		Leopard, Mac OS X 10.7 Lion, Mac
Faxing *	×		OS X 10.8 Mountain Lion, Mac OS X
Fax resolution (black)	400 x 400 DPI		10.9 Mavericks
Fax transmission speed	3 sec/page	Linux operating systems supported	10.9 Mavericks ✓
Fax transmission speed Modem speed	3 sec/page 33.6 Kbit/s	Linux operating systems supported  Operational conditions	
Fax transmission speed Modem speed Fax coding methods	3 sec/page	Operational conditions Operating relative humidity (H-H)	
Fax transmission speed Modem speed	3 sec/page 33.6 Kbit/s	Operational conditions	✓
Fax transmission speed Modem speed Fax coding methods Features Recommended duty cycle	3 sec/page 33.6 Kbit/s JBIG, MH, MMR, MR 3000 - 8000 pages per month	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T)	10 - 80% -20 - 40 °C 10 - 32.5 °C
Fax transmission speed Modem speed Fax coding methods Features Recommended duty cycle Maximum duty cycle *	3 sec/page 33.6 Kbit/s JBIG, MH, MMR, MR  3000 - 8000 pages per month 100000 pages per month	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H)	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90%
Fax transmission speed Modem speed Fax coding methods  Features  Recommended duty cycle Maximum duty cycle * Duplex functions *	3 sec/page 33.6 Kbit/s JBIG, MH, MMR, MR  3000 - 8000 pages per month 100000 pages per month Copy, Print, Scan	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m
Fax transmission speed Modem speed Fax coding methods  Features  Recommended duty cycle Maximum duty cycle * Duplex functions * Number of print cartridges *	3 sec/page 33.6 Kbit/s JBIG, MH, MMR, MR  3000 - 8000 pages per month 100000 pages per month Copy, Print, Scan 4	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H)	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90%
Fax transmission speed Modem speed Fax coding methods  Features  Recommended duty cycle Maximum duty cycle * Duplex functions *	3 sec/page 33.6 Kbit/s JBIG, MH, MMR, MR  3000 - 8000 pages per month 100000 pages per month Copy, Print, Scan 4 Black, Cyan, Magenta, Yellow	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m
Fax transmission speed Modem speed Fax coding methods  Features  Recommended duty cycle Maximum duty cycle * Duplex functions * Number of print cartridges *	3 sec/page 33.6 Kbit/s JBIG, MH, MMR, MR  3000 - 8000 pages per month 100000 pages per month Copy, Print, Scan 4 Black, Cyan, Magenta, Yellow Microsoft XPS, OpenXPS, PCL 5e,	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Waste Electrical and Electronic	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m
Fax transmission speed Modem speed Fax coding methods  Features  Recommended duty cycle Maximum duty cycle * Duplex functions * Number of print cartridges * Printing colours * Page description languages	3 sec/page 33.6 Kbit/s JBIG, MH, MMR, MR  3000 - 8000 pages per month 100000 pages per month Copy, Print, Scan 4 Black, Cyan, Magenta, Yellow Microsoft XPS, OpenXPS, PCL 5e, PCL 6, PCL XL, PostScript 3	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Certificates Waste Electrical and Electronic Equipment (WEEE) compliance	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m
Fax transmission speed Modem speed Fax coding methods  Features  Recommended duty cycle Maximum duty cycle * Duplex functions * Number of print cartridges * Printing colours * Page description languages Printer fonts	3 sec/page 33.6 Kbit/s JBIG, MH, MMR, MR  3000 - 8000 pages per month 100000 pages per month Copy, Print, Scan 4 Black, Cyan, Magenta, Yellow Microsoft XPS, OpenXPS, PCL 5e,	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Waste Electrical and Electronic	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m
Fax transmission speed Modem speed Fax coding methods  Features  Recommended duty cycle Maximum duty cycle * Duplex functions * Number of print cartridges * Printing colours * Page description languages	3 sec/page 33.6 Kbit/s JBIG, MH, MMR, MR  3000 - 8000 pages per month 100000 pages per month Copy, Print, Scan 4 Black, Cyan, Magenta, Yellow Microsoft XPS, OpenXPS, PCL 5e, PCL 6, PCL XL, PostScript 3 Barcode, Bitmap, PCL, Windows	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Certificates Waste Electrical and Electronic Equipment (WEEE) compliance	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m
Fax transmission speed Modem speed Fax coding methods  Features  Recommended duty cycle Maximum duty cycle * Duplex functions * Number of print cartridges * Printing colours *  Page description languages  Printer fonts Number of printer fonts Optional functions	3 sec/page 33.6 Kbit/s JBIG, MH, MMR, MR  3000 - 8000 pages per month 100000 pages per month Copy, Print, Scan 4 Black, Cyan, Magenta, Yellow Microsoft XPS, OpenXPS, PCL 5e, PCL 6, PCL XL, PostScript 3 Barcode, Bitmap, PCL, Windows 101 Fax TK-8115K, TK-8115C, TK-8115M,	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification Sustainability	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m
Fax transmission speed Modem speed Fax coding methods  Features Recommended duty cycle Maximum duty cycle * Duplex functions * Number of print cartridges * Printing colours * Page description languages Printer fonts Number of printer fonts	3 sec/page 33.6 Kbit/s JBIG, MH, MMR, MR  3000 - 8000 pages per month 100000 pages per month Copy, Print, Scan 4 Black, Cyan, Magenta, Yellow Microsoft XPS, OpenXPS, PCL 5e, PCL 6, PCL XL, PostScript 3 Barcode, Bitmap, PCL, Windows 101 Fax	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification Sustainability Sustainability certificates	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m
Fax transmission speed Modem speed Fax coding methods  Features  Recommended duty cycle Maximum duty cycle * Duplex functions * Number of print cartridges * Printing colours *  Page description languages  Printer fonts Number of printer fonts Optional functions	3 sec/page 33.6 Kbit/s JBIG, MH, MMR, MR  3000 - 8000 pages per month 100000 pages per month Copy, Print, Scan 4 Black, Cyan, Magenta, Yellow Microsoft XPS, OpenXPS, PCL 5e, PCL 6, PCL XL, PostScript 3 Barcode, Bitmap, PCL, Windows 101 Fax TK-8115K, TK-8115C, TK-8115M,	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification Sustainability	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m
Fax transmission speed Modem speed Fax coding methods  Features  Recommended duty cycle Maximum duty cycle * Duplex functions * Number of print cartridges * Printing colours * Page description languages  Printer fonts Number of printer fonts Optional functions  Replacement cartridges  Input & output capacity  Total number of input trays *	3 sec/page 33.6 Kbit/s JBIG, MH, MMR, MR  3000 - 8000 pages per month 100000 pages per month Copy, Print, Scan 4 Black, Cyan, Magenta, Yellow Microsoft XPS, OpenXPS, PCL 5e, PCL 6, PCL XL, PostScript 3 Barcode, Bitmap, PCL, Windows 101 Fax TK-8115K, TK-8115C, TK-8115M,	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification Sustainability Sustainability certificates Weight & dimensions Width	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m   *  TÜV/GS, CE  Blue Angel, EPEAT Silver, ENERGY STAR
Fax transmission speed Modem speed Fax coding methods  Features  Recommended duty cycle Maximum duty cycle * Duplex functions * Number of print cartridges * Printing colours * Page description languages Printer fonts Number of printer fonts Optional functions  Replacement cartridges  Input & output capacity  Total number of input trays * Total input capacity *	3 sec/page 33.6 Kbit/s JBIG, MH, MMR, MR  3000 - 8000 pages per month 100000 pages per month Copy, Print, Scan 4 Black, Cyan, Magenta, Yellow Microsoft XPS, OpenXPS, PCL 5e, PCL 6, PCL XL, PostScript 3 Barcode, Bitmap, PCL, Windows 101 Fax TK-8115K, TK-8115C, TK-8115M, TK-8115Y	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification  Sustainability Sustainability certificates  Weight & dimensions  Width Depth	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m   TÜV/GS, CE  Blue Angel, EPEAT Silver, ENERGY STAR
Fax transmission speed Modem speed Fax coding methods  Features  Recommended duty cycle Maximum duty cycle * Duplex functions * Number of print cartridges * Printing colours * Page description languages Printer fonts Number of printer fonts Optional functions Replacement cartridges  Input & output capacity Total number of input trays * Total input capacity * Total output capacity *	3 sec/page 33.6 Kbit/s JBIG, MH, MMR, MR  3000 - 8000 pages per month 100000 pages per month Copy, Print, Scan 4 Black, Cyan, Magenta, Yellow Microsoft XPS, OpenXPS, PCL 5e, PCL 6, PCL XL, PostScript 3 Barcode, Bitmap, PCL, Windows 101 Fax TK-8115K, TK-8115C, TK-8115M, TK-8115Y	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification  Sustainability Sustainability certificates  Weight & dimensions  Width Depth Height	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m   *  TÜV/GS, CE  Blue Angel, EPEAT Silver, ENERGY STAR  590 mm 590 mm 753 mm
Fax transmission speed Modem speed Fax coding methods  Features  Recommended duty cycle Maximum duty cycle * Duplex functions * Number of print cartridges * Printing colours * Page description languages Printer fonts Number of printer fonts Optional functions Replacement cartridges  Input & output capacity Total number of input trays * Total input capacity * Paper tray 1 input capacity	3 sec/page 33.6 Kbit/s JBIG, MH, MMR, MR  3000 - 8000 pages per month 100000 pages per month Copy, Print, Scan 4 Black, Cyan, Magenta, Yellow Microsoft XPS, OpenXPS, PCL 5e, PCL 6, PCL XL, PostScript 3 Barcode, Bitmap, PCL, Windows 101 Fax TK-8115K, TK-8115C, TK-8115M, TK-8115Y	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification  Sustainability Sustainability certificates  Weight & dimensions  Width Depth	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m   TÜV/GS, CE  Blue Angel, EPEAT Silver, ENERGY STAR
Fax transmission speed Modem speed Fax coding methods  Features Recommended duty cycle Maximum duty cycle * Duplex functions * Number of print cartridges * Printing colours * Page description languages Printer fonts Number of printer fonts Optional functions Replacement cartridges  Input & output capacity Total number of input trays * Total input capacity * Paper tray 1 input capacity Paper tray 2 input capacity	3 sec/page 33.6 Kbit/s JBIG, MH, MMR, MR  3000 - 8000 pages per month 100000 pages per month Copy, Print, Scan 4 Black, Cyan, Magenta, Yellow Microsoft XPS, OpenXPS, PCL 5e, PCL 6, PCL XL, PostScript 3 Barcode, Bitmap, PCL, Windows 101 Fax TK-8115K, TK-8115C, TK-8115M, TK-8115Y	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification  Sustainability Sustainability certificates  Weight & dimensions  Width Depth Height	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m   *  TÜV/GS, CE  Blue Angel, EPEAT Silver, ENERGY STAR  590 mm 590 mm 753 mm
Fax transmission speed Modem speed Fax coding methods  Features  Recommended duty cycle Maximum duty cycle * Duplex functions * Number of print cartridges * Printing colours * Page description languages Printer fonts Number of printer fonts Optional functions Replacement cartridges  Input & output capacity Total number of input trays * Total input capacity * Paper tray 1 input capacity	3 sec/page 33.6 Kbit/s JBIG, MH, MMR, MR  3000 - 8000 pages per month 100000 pages per month Copy, Print, Scan 4 Black, Cyan, Magenta, Yellow Microsoft XPS, OpenXPS, PCL 5e, PCL 6, PCL XL, PostScript 3 Barcode, Bitmap, PCL, Windows 101 Fax TK-8115K, TK-8115C, TK-8115M, TK-8115Y	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification  Sustainability Sustainability certificates  Weight & dimensions Width Depth Height Weight Packaging data	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m   *  TÜV/GS, CE  Blue Angel, EPEAT Silver, ENERGY STAR  590 mm 590 mm 753 mm
Fax transmission speed Modem speed Fax coding methods  Features Recommended duty cycle Maximum duty cycle * Duplex functions * Number of print cartridges * Printing colours * Page description languages Printer fonts Number of printer fonts Optional functions Replacement cartridges  Input & output capacity Total number of input trays * Total input capacity * Paper tray 1 input capacity Paper tray 2 input capacity	3 sec/page 33.6 Kbit/s JBIG, MH, MMR, MR  3000 - 8000 pages per month 100000 pages per month Copy, Print, Scan 4 Black, Cyan, Magenta, Yellow Microsoft XPS, OpenXPS, PCL 5e, PCL 6, PCL XL, PostScript 3 Barcode, Bitmap, PCL, Windows 101 Fax TK-8115K, TK-8115C, TK-8115M, TK-8115Y	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification  Sustainability Sustainability certificates  Weight & dimensions  Width Depth Height Weight  Packaging data Package width	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m   TÜV/GS, CE  Blue Angel, EPEAT Silver, ENERGY STAR  590 mm 590 mm 753 mm 79 kg
Fax transmission speed Modem speed Fax coding methods  Features Recommended duty cycle Maximum duty cycle * Duplex functions * Number of print cartridges * Printing colours * Page description languages Printer fonts Number of printer fonts Optional functions Replacement cartridges  Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Paper tray 2 input capacity Paper tray 3 input capacity	3 sec/page 33.6 Kbit/s JBIG, MH, MMR, MR  3000 - 8000 pages per month 100000 pages per month Copy, Print, Scan 4 Black, Cyan, Magenta, Yellow Microsoft XPS, OpenXPS, PCL 5e, PCL 6, PCL XL, PostScript 3 Barcode, Bitmap, PCL, Windows 101 Fax TK-8115K, TK-8115C, TK-8115M, TK-8115Y	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification Sustainability Sustainability certificates  Weight & dimensions Width Depth Height Weight Packaging data Package width Package depth	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m   TÜV/GS, CE  Blue Angel, EPEAT Silver, ENERGY STAR  590 mm 590 mm 753 mm 79 kg
Fax transmission speed Modem speed Fax coding methods  Features  Recommended duty cycle Maximum duty cycle * Duplex functions * Number of print cartridges * Printing colours * Page description languages  Printer fonts Number of printer fonts Optional functions  Replacement cartridges  Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Paper tray 2 input capacity Paper tray 3 input capacity Multi-Purpose tray	3 sec/page 33.6 Kbit/s JBIG, MH, MMR, MR  3000 - 8000 pages per month 100000 pages per month Copy, Print, Scan 4 Black, Cyan, Magenta, Yellow Microsoft XPS, OpenXPS, PCL 5e, PCL 6, PCL XL, PostScript 3 Barcode, Bitmap, PCL, Windows 101 Fax TK-8115K, TK-8115C, TK-8115M, TK-8115Y	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification  Sustainability Sustainability certificates  Weight & dimensions  Width Depth Height Weight  Packaging data Package width	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m    TÜV/GS, CE  Blue Angel, EPEAT Silver, ENERGY STAR  590 mm 590 mm 753 mm 79 kg
Fax transmission speed Modem speed Fax coding methods  Features  Recommended duty cycle Maximum duty cycle * Duplex functions * Number of print cartridges * Printing colours * Page description languages  Printer fonts Number of printer fonts Optional functions  Replacement cartridges  Input & output capacity  Total number of input trays * Total input capacity * Paper tray 1 input capacity Paper tray 2 input capacity Paper tray 3 input capacity Multi-Purpose tray Multi-Purpose tray Multi-Purpose tray input capacity	3 sec/page 33.6 Kbit/s JBIG, MH, MMR, MR  3000 - 8000 pages per month 100000 pages per month Copy, Print, Scan 4 Black, Cyan, Magenta, Yellow Microsoft XPS, OpenXPS, PCL 5e, PCL 6, PCL XL, PostScript 3 Barcode, Bitmap, PCL, Windows 101 Fax TK-8115K, TK-8115C, TK-8115M, TK-8115Y  1 500 sheets 280 sheets 500 sheets 500 sheets 500 sheets	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width Package depth Package height Package weight	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m    TÜV/GS, CE  Blue Angel, EPEAT Silver, ENERGY STAR  590 mm 590 mm 753 mm 79 kg  760 mm 760 mm 760 mm 995 mm
Fax transmission speed Modem speed Fax coding methods  Features Recommended duty cycle Maximum duty cycle * Duplex functions * Number of print cartridges * Printing colours * Page description languages Printer fonts Number of printer fonts Optional functions Replacement cartridges  Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Paper tray 2 input capacity Paper tray 3 input capacity Multi-Purpose tray Multi-Purpose tray Multi-Purpose tray input capacity Paper input type Auto document feeder (ADF) Auto document feeder (ADF) Auto document feeder (ADF)	3 sec/page 33.6 Kbit/s JBIG, MH, MMR, MR  3000 - 8000 pages per month 100000 pages per month Copy, Print, Scan 4 Black, Cyan, Magenta, Yellow Microsoft XPS, OpenXPS, PCL 5e, PCL 6, PCL XL, PostScript 3 Barcode, Bitmap, PCL, Windows 101 Fax TK-8115K, TK-8115C, TK-8115M, TK-8115Y  1 500 sheets 280 sheets 500 sheets 500 sheets 500 sheets 500 sheets Cassette, Paper tray	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification Sustainability Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width Package depth Package height Package weight Packaging content	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m    TÜV/GS, CE  Blue Angel, EPEAT Silver, ENERGY STAR  590 mm 590 mm 753 mm 79 kg  760 mm 760 mm 760 mm 995 mm 106 kg
Fax transmission speed Modem speed Fax coding methods  Features Recommended duty cycle Maximum duty cycle * Duplex functions * Number of print cartridges * Printing colours * Page description languages Printer fonts Number of printer fonts Optional functions Replacement cartridges  Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Paper tray 2 input capacity Paper tray 3 input capacity Multi-Purpose tray Multi-Purpose tray Multi-Purpose tray input capacity Paper input type Auto document feeder (ADF)	3 sec/page 33.6 Kbit/s JBIG, MH, MMR, MR  3000 - 8000 pages per month 100000 pages per month Copy, Print, Scan 4 Black, Cyan, Magenta, Yellow Microsoft XPS, OpenXPS, PCL 5e, PCL 6, PCL XL, PostScript 3 Barcode, Bitmap, PCL, Windows 101 Fax TK-8115K, TK-8115C, TK-8115M, TK-8115Y  1 500 sheets 280 sheets 500 sheets 500 sheets 500 sheets 500 sheets Cassette, Paper tray	Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Waste Electrical and Electronic Equipment (WEEE) compliance Certification Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width Package depth Package height Package weight	10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m    TÜV/GS, CE  Blue Angel, EPEAT Silver, ENERGY STAR  590 mm 590 mm 753 mm 79 kg  760 mm 760 mm 760 mm 995 mm

Input & output capacity		Packaging content	
Maximum input capacity	1600 sheets	Included cartridge capacity (CMY)	1500 pages
Maximum output capacity	280 sheets	Imaging unit included	✓
Paper handling		Cables included	AC
Maximum ISO A-series paper size *	A3	Drivers included	✓
Maximum print size	297 x 432 mm	Manual	✓
Paper tray media types *	Plain paper	Power cord included	<b>✓</b>
		Quick installation guide	✓
		Logistics data	
		Harmonized System (HS) code	84433100
		Technical details	
		Compliance certificates	REACH, RoHS
		Other features	
		Finishing option	✓





632983046609

0632983046609

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.