KYOCERA ECOSYS M2135dn Laser A4 1200 x 1200 DPI 35 ppm

Tuotemerkki : KYOCERA

Tuoteperhe: ECOSYS

Tuotekoodi: 1102S03NL0

Tuotteen nimi : M2135dn

KYOCERA ECOSYS M2135dn. Tulostustekniikka: Laser, Tulostus: Yksittäistulostus, Suurin resoluutio: 1200 x 1200 DPI. Kopiointi: Yksittäiskopiointi, Kopioinnin enimmäistarkkuus: 600 x 600 DPI. Skannaus: Väriskannaus, Optinen skannauserottelutarkkuus: 600 x 600 DPI. Kaksipuolinen toiminto: Tulosta. Suurin ISO A-luokan paperikoko: A4. Suoratulostus. Tuotteen väri: musta, Valkoinen





Printing		Ports & interfaces	
Duplex printing mode Print technology * Printing * Duplex printing * Maximum resolution *	Auto Laser Mono printing ✓ 1200 x 1200 DPI	Standard interfaces Direct printing * USB port USB 2.0 ports quantity	Ethernet, USB 2.0 ✓ 2
Print speed (black, normal quality, A4/US Letter) *	35 ppm	Network Wi-Fi *	×
Duplex print speed (black, normal quality, A4/US Letter) Warm-up time Time to first page (black, normal) N-in-1 print function N-up printing Barcode printing Watermark printing	17.5 ppm 17 s 6.8 s ✓ 2, 4 ✓	Ethernet LAN * Cabling technology Ethernet LAN data rates Bluetooth Near Field Communication (NFC) Mobile printing technologies	✓ 10/100/1000Base-T(X) 10,100,1000 Mbit/s × × Apple AirPrint, Google Cloud Print, Kyocera Mobile Print, Mopria Print Service
Secure printing	✓	Performance	
Booklet printing function Poster printing function Borderless printing	✓ ✓ ×	Maximum internal memory Card reader integrated Internal memory *	1536 MB ✓ 512 MB
Copying Duplex copying * Copying *	× Mono copying	Compatible memory cardsSD, SDHCBuilt-in processorImage: Compatible memory cardsProcessor familyARM Cortex-A9Processor frequency800 MHz	×
Maximum copy resolution *	600 x 600 DPI	riocessor requercy	

Copying		Performance	
Copy speed (black, normal quality,		Sound pressure level (printing)	51 dB
A4)	35 cpm	Sound pressure level (copying)	51 dB
Time to first copy (black, normal)	6.9 s	Sound pressure level (quiet mode)	47 dB
Maximum number of copies	999 copies	Sound power level (standby)	29 dB
Copier resize	25 - 400%	Design	
N-in-1 copy function		Product colour *	Black, White
N-in-1 copy function (N=) Copy programming function	2,4	Market positioning *	Business
ID-card copy function		Built-in display *	1
1,5	•	Display	LCD
Scanning		Display number of lines	5 lines
Duplex scanning *	×	Power	
Scanning *	Colour scanning	Power consumption (average	661 W
Optical scanning resolution * Scan technology	600 x 600 DPI CIS	operating) Power consumption (printing)	661 W
Scan to	E-mail, FTP, SMB, TWAIN, USB, WIA	Power consumption (copying)	661 W
Scan speed (colour)	23 ppm	Power consumption (ready)	21 W
Scan speed (black)	40 ppm	Power consumption (sleep)	1 W
Image formats supported	JPEG, TIF	Energy Star Typical Electricity	1.47 kWh/week
Document formats supported	PDF, XPS	Consumption (TEC) AC input voltage	220 - 240 V
Scan drivers	TWAIN, WIA	AC input frequency	50 - 60 Hz
Fax		System requirements	
Faxing *	×	Windows operating systems	
Features		supported	1
Recommended duty cycle	1000 - 2500 pages per month		Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan Mac OS X 10.12
Maximum duty cycle *	20000 pages per month		10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra,
Duplex functions *	Print	Mac operating systems supported	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5
Digital sender		Mac operating systems supported	Leopard, Mac OS X 10.5 Snow
Number of print cartridges * Printing colours *	1 Black		Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X
	Microsoft XPS, PCL 5e, PCL 6, PCL		10.9 Mavericks
Page description languages	XL, PostScript 3	Linux operating systems supported	1
Number of printer fonts	93 TK 1150 (2.000 paginala)	Operational conditions	
Replacement cartridges	TK-1150 (3.000 pagina's)	Operating relative humidity (H-H)	10 - 80%
Input & output capacity	-	Storage temperature (T-T)	-20 - 40 °C
Total number of input trays *	1	Operating temperature (T-T)	10 - 32.5 °C
Total input capacity * Total output capacity *	250 sheets 150 sheets	Storage relative humidity (H-H)	10 - 90%
Paper tray 1 input capacity	250 sheets	Operating altitude Non-operating altitude	0 - 3500 m 0.6 - 15000 m
Multi-Purpose tray	 ✓ 		0.0 - 15000 m
Multi-Purpose tray input capacity	100 sheets	Certificates	
Paper input type	Cassette, Paper tray	Waste Electrical and Electronic Equipment (WEEE) compliance	1
Auto document feeder (ADF)	✓	Certification	GS, TÜV, CE, ISO 9001, ISO 14001
Auto document feeder (ADF) input	50 sheets	Sustainability	
capacity Maximum number of input trays	3		Blue Angel, EPEAT Silver, ENERGY
Maximum input capacity	850 sheets	Sustainability certificates	STAR
Maximum output capacity	150 sheets	Weight & dimensions	
Paper handling		Width	417 mm
Maximum ISO A-series paper size *	Α4	Depth	412 mm
Maximum print size	216 x 356 mm	Height	437 mm
Paper tray media types *	Plain paper	Weight	19 kg
ISO A-series sizes (A0A9) *	A4, A5, A6	Packaging data	
ISO B-series sizes (B0B9)	B5, B6	Package width	541 mm
Non-ISO print media sizes Custom media width	Legal, Letter 70 - 216 mm	Package depth Package beight	555 mm 572 mm
Custom media length	148 - 356 mm	Package height Package weight	25 kg
Paper tray media weight			
ruper and measure	60 - 163 g/m²		
Multi-Purpose Tray media weight	60 - 163 g/m² 60 - 220 g/m²		


Paper handling


Duplex media weight

60 - 163 g/m²

Packaging content

r ackaging content				
Cartridge(s) included	1			
Included cartridge capacity (black)	1000 pages			
Imaging unit included	1			
Cables included	AC			
Logistics data				
Harmonized System (HS) code	84433100			
Technical details				
Compliance certificates	REACH, RoHS			
Other features				
Cartridge type	TK-1150			







Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.