

KYOCERA ECOSYS M3655idn Laser A4 1200 x 1200 DPI 55 ppm

Tuotemerkki : KYOCERA

Tuoteperhe: ECOSYS

Tuotekoodi: 1102TB3NLO

Tuotteen nimi : M3655idn

KYOCERA ECOSYS M3655idn. Tulostustekniikka: Laser, Tulostus: Yksittäistulostus, Suurin resoluutio: 1200 x 1200 DPI. Kopiointi: Yksittäiskopiointi, Kopioinnin enimmäistarkkuus: 600 x 600 DPI. Skannaus: Väriskannaus, Optinen skannauserottelutarkkuus: 600 x 600 DPI. Faksaus: Yksittäisfaksin lähetyks. Kaksipuolinen toiminto: Kopiointi, Faksi, Tulosta, Skannaus. Suurin ISO A-luokan paperikoko: A4. Suoratulostus. Tuotteen väri: musta, Valkoinen



Printing		Paper handling	
Duplex printing mode	Auto	Custom media length	148 - 356 mm
Print technology *	Laser	Paper tray media weight	60 - 120 g/m ²
Printing *	Mono printing	Multi-Purpose Tray media weight	60 - 220 g/m ²
Duplex printing *	✓	Auto Document Feeder (ADF) media weight	50 - 120 g/m ²
Maximum resolution *	1200 x 1200 DPI	Duplex media weight	60 - 120 g/m ²
Print speed (black, normal quality, A4/US Letter) *	55 ppm	Ports & interfaces	
Duplex print speed (black, normal quality, A4/US Letter)	39.5 ppm	Standard interfaces	Ethernet, USB 2.0
Warm-up time	25 s	Direct printing *	✓
Time to first page (black, normal)	4.9 s	USB port	✓
N-in-1 print function	✓	USB 2.0 ports quantity	3
N-up printing	2, 4	Optional connectivity	Ethernet, Wireless LAN
Watermark printing	✓	Network	
Economical printing	✓	Wi-Fi *	✗
Secure printing	✓	Ethernet LAN *	✓
Poster printing function	✓	Cabling technology	10/100/1000Base-T(X)
Borderless printing	✗	Ethernet LAN data rates	10,100,1000 Mbit/s
Copying		Bluetooth	✗
Duplex copying *	✓	Near Field Communication (NFC)	✗
Duplex copying mode	Auto	Mobile printing technologies	Apple AirPrint, Google Cloud Print, Kyocera Mobile Print, Mopria Print Service
Copying *	Mono copying	Performance	
Maximum copy resolution *	600 x 600 DPI	Maximum internal memory	3000 MB
Copy speed (black, normal quality, A4)	55 cpm	Internal memory *	1000 MB
Time to first copy (black, normal)	6 s	Compatible memory cards	SD, SDHC
Maximum number of copies	999 copies	Built-in processor	✓
Copier resize	25 - 400%	Processor family	ARM Cortex-A9
N-in-1 copy function	✓	Processor frequency	1200 MHz
N-in-1 copy function (N=)	2, 4	Processor cores	2
Copy programming function	✓	Coprocessor frequency	1.2 GHz
ID-card copy function	✓	Sound pressure level (printing)	56 dB
Scanning		Sound pressure level (copying)	56 dB
Duplex scanning *	✓	Sound power level (standby)	30 dB
Duplex scanning mode	Auto		

Scanning		Design	
Scanning *	Colour scanning	Product colour *	Black, White
Optical scanning resolution *	600 x 600 DPI	Market positioning *	Business
Scan technology	CIS	Built-in display *	✓
Scan to	E-mail, FTP, SMB, TWAIN, USB, WIA	Display diagonal	17.8 cm (7")
Scan speed (colour)	40 ppm	Touchscreen	✓
Scan speed (black)	60 ppm	Control type	Touch
Duplex scan speed (colour)	64 ppm	Colour display	✓
Duplex scan speed (black)	100 ppm	Power	
Image formats supported	JPEG, TIFF	Power consumption (average operating)	711 W
Document formats supported	PDF, XPS	Power consumption (printing)	711 W
Greyscale levels	256	Power consumption (copying)	731 W
Scan drivers	TWAIN, WIA	Power consumption (ready)	54 W
Fax		Power consumption (standby)	30 W
Duplex faxing	✓	Power consumption (sleep)	0.5 W
Faxing *	Mono faxing	Energy Star Typical Electricity Consumption (TEC)	2.91 kWh/week
Fax resolution (black)	400 x 400 DPI	AC input voltage	220 - 240 V
Fax transmission speed	3 sec/page	AC input frequency	50 - 60 Hz
Modem speed	33.6 Kbit/s	System requirements	
Fax memory	256 pages	Windows operating systems supported	✓
Speed dialling	✓	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Fax coding methods	JBIG, MH, MMR, MR	Linux operating systems supported	✓
Features		Operational conditions	
Recommended duty cycle	5000 - 15000 pages per month	Operating relative humidity (H-H)	15 - 80%
Maximum duty cycle *	27500 pages per month	Storage temperature (T-T)	-20 - 40 °C
Duplex functions *	Copy, Fax, Print, Scan	Operating temperature (T-T)	10 - 32.5 °C
Digital sender	✓	Storage relative humidity (H-H)	10 - 90%
Number of print cartridges *	1	Operating altitude	0 - 3500 m
Printing colours *	Black	Non-operating altitude	0.6 - 15000 m
Page description languages	Epson LQ, IBM ProPrinter XL24E, OpenXPS, PCL 6, PCL XL, TIFF, XPS	Certificates	
Printer fonts	Barcode, Bitmap, Windows	Waste Electrical and Electronic Equipment (WEEE) compliance	✓
Number of printer fonts	93	Certification	TÜV/GS, CE, ISO 9001, ISO 14001.
All-In-One-multitasking	✓	Sustainability	
Replacement cartridges	TK-3190 (25.000 pagina's)	Sustainability certificates	Blue Angel, EPEAT Silver, ENERGY STAR
Input & output capacity		Weight & dimensions	
Total number of input trays *	1	Width	480 mm
Total input capacity *	500 sheets	Depth	495 mm
Total output capacity *	500 sheets	Height	590 mm
Paper tray 1 input capacity	500 sheets	Weight	24.7 kg
Multi-Purpose tray	✓	Packaging data	
Multi-Purpose tray input capacity	100 sheets	Package width	633 mm
Paper input type	Cassette, Paper tray	Package depth	570 mm
Auto document feeder (ADF)	✓	Package height	710 mm
Auto document feeder (ADF) input capacity	75 sheets	Package weight	31.2 kg
Maximum number of input trays	5	Packaging content	
Maximum input capacity	2600 sheets	Cartridge(s) included	✓
Maximum output capacity	500 sheets	Included cartridge capacity (black)	10000 pages
Paper handling		Imaging unit included	✓
Maximum ISO A-series paper size *	A4		
Maximum print size	216 x 356 mm		
Paper tray media types *	Plain paper		
Multi-purpose tray media types	Legal		
ISO A-series sizes (A0...A9) *	A4, A5, A6		
ISO B-series sizes (B0...B9)	B5, B6		
Non-ISO print media sizes	Folio, Legal, Letter		
Custom media width	70 - 216 mm		

Packaging content

Cables included	AC
-----------------	----

Logistics data

Harmonized System (HS) code	84433100
-----------------------------	----------

Technical details

Compliance certificates	REACH, RoHS
-------------------------	-------------



0632983051016



632983051016

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.