

## QNAP REXP-1620U-RP disk array 0 TB Rack (3U) Black

**Brand :** QNAP

**Product code:** REXP-1620U-RP

**Product name :** REXP-1620U-RP



- Plug and use, seamless capacity expansion
- Missing mode protection
- High density, high efficiency and high scalability
- Flexible management with the QTS Storage Manager
- Backup storage for the QNAP NAS
- Supports SAS 12 Gbps, SAS/SATA 6 Gbps HDD and SSD
- Backward compatible with a 6 Gbps SAS-enabled NAS / REXP expansion unit and 6 Gbps SAS HBA by using the 12Gb/s SAS for 6Gb/s SAS cable (CAB-SAS10M-8644-8088)

16x 3.5"/2.5", SAS/SATA, HDD/SSD, 4x SAS 12Gbps, 3U, 650W, ATX Power Supply, 18.14kg  
 QNAP REXP-1620U-RP. Total installed storage capacity: 0 TB. Chassis type: Rack (3U), Device class: Large Enterprise Business. Number of storage drives supported: 16, Supported storage drive types: HDD & SSD, Supported storage drive interfaces: SAS, Serial ATA, Serial ATA II, Serial ATA III. Width: 442.4 mm, Depth: 528.3 mm, Height: 130 mm, Weight: 18.1 kg. Product colour: Black

Storage		Design	
Storage drives installed *	✗	Noise level	36.7 dB
Installed storage drive type *	✗	Power	
Total installed storage capacity *	0 TB	Power supply unit (PSU) capacity	650 W
Supported storage drive types *	HDD & SSD	Number of power supply units	1
Number of storage drives supported *	16	Redundant power supply (RPS) support	✓
Maximum supported storage capacity *	1216 TB	Power consumption (typical)	204.4 W
Supported storage drive interfaces	SAS, Serial ATA, Serial ATA II, Serial ATA III	AC input voltage	90-240 V
RAID levels	0, 1, 5, 6	AC input frequency	50 - 60 Hz
Ports & interfaces		Weight & dimensions	
USB connectivity	✗	Width	442.4 mm
Host ports	4	Depth	528.3 mm
Serial interface type	SATA	Height	130 mm
SAS host port	✓	Weight	18.1 kg
Design		Packaging data	
Device class *	Large Enterprise Business	Package weight	25.9 kg
Chassis type *	Rack (3U)	Packaging content	
Product colour	Black	Cables included	AC, SAS
LED indicators	Fan fail, HDD, LAN, Status, System	Operational conditions	
Number of fans	3 fan(s)	Operating temperature (T-T)	0 - 40 °C
		Operating relative humidity (H-H)	5 - 95%
		Logistics data	
		Harmonized System (HS) code	84717020



4712511127836

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.