

## Epson WorkForce DS-80W

**Brand :** Epson

**Product family:** WorkForce

**Product code:** B11B253402

**Product name :** WorkForce DS-80W



- Scan anywhere: Small, lightweight design
- USB cable or integrated battery power: Scan up to 300 pages between battery charges
- Fast scanning speeds: At up to four seconds per page (8.5ppm)
- Simplify your workload: Continuous scanning with automatic feed mode
- Includes a range of software: Document Capture Pro 2, Epson Scan 2.0 and TWAIN driver support

Epson WorkForce DS-80W. Maximum scan size: 216 x 1828 mm, Optical scanning resolution: 600 x 600 DPI, Input colour depth: 48 bit. Scanner type: Handheld scanner, Product colour: White, Display: LCD. Sensor type: CIS, Daily duty cycle (max): 300 pages, Light source: ReadyScan LED. Auto document feeder (ADF) input capacity: 1 sheets. Maximum ISO A-series paper size: A4, Scanning media types supported: Business Card, Plastic Card, Post Card(JPN), Paper tray media weight: 35 - 270 g/m<sup>2</sup>

<b>Scanning</b>		<b>Packaging data</b>	
Maximum scan size *	216 x 1828 mm	Package depth	330 mm
Optical scanning resolution *	600 x 600 DPI	Package height	67 mm
Colour scanning	✓	Package weight	597 g
Duplex scanning *	✗	<b>Packaging content</b>	
Input colour depth	48 bit	Cables included	USB
Output colour depth	24 bit	Bundled software	Document Capture Pro 2.0, Epson Scan 2
Input greyscale depth	16 bit	<b>System requirements</b>	
Output greyscale depth	8 bit	Compatible operating systems	Mac OS 10.6+, Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Server 2003, Windows Server 2008 (32/64 Bit), Windows Server 2012 R2, Windows Server 2016, Windows Vista, Windows XP
Output monochrome depth	8 bit		Windows operating systems supported
Scan speed (b/w, low res, A4)	4 sec/page	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Scan speed (colour, low res, A4)	4 sec/page		Server operating systems supported
<b>Design</b>		<b>Operational conditions</b>	
Scanner type *	Handheld scanner	Operating temperature (T-T)	5 - 35 °C
Product colour *	White	Storage temperature (T-T)	-25 - 60 °C
Display	LCD	Operating relative humidity (H-H)	10 - 85%
Colour display	✗	Storage relative humidity (H-H)	10 - 90%
Built-in display *	✓	<b>Other features</b>	
<b>Performance</b>		Output resolutions	600 dpi
Sensor type *	CIS	Image formats supported	BMP, JPEG, TIFF, PNG
Light source	ReadyScan LED		
Scan file formats	BMP, JPEG, PDF, PNG, TIFF		
Daily duty cycle (max) *	300 pages		
Scan drivers	TWAIN, WIA, SANE, ICA		
<b>Input capacity</b>			
Auto document feeder (ADF) input capacity	1 sheets		
<b>Paper handling</b>			
Scanning media types supported	Business Card, Plastic Card, Post Card(JPN)		
Maximum ISO A-series paper size *	A4		
Paper tray media weight	35 - 270 g/m <sup>2</sup>		

Paper handling		Logistics data	
Auto Document Feeder (ADF) media weight	35 - 270 g/m <sup>2</sup>	Products per pallet	360 pc(s)
<b>Ports &amp; interfaces</b>		Country of origin	China
USB port *	✓	Pallet gross weight	0 g
USB version	2.0	Master (outer) case length	360 mm
Standard interfaces	USB 2.0, Wireless LAN	Master (outer) case height	320 mm
<b>Network</b>		Master (outer) case width	350 mm
Wi-Fi	✓	Master (outer) case gross weight	0 g
<b>Power</b>		Pallet gross length	120 cm
Power supply type *	USB	Pallet gross width	80 cm
<b>Weight &amp; dimensions</b>		Pallet gross height	171 cm
Width	272 mm	Products per master (outer) case	10 pc(s)
Depth	47 mm	Products per pallet layer	60 pc(s)
Height	34 mm	Products per pallet layer (UK)	60 pc(s)
Weight	300 g	Products per pallet (UK)	360 pc(s)
<b>Packaging data</b>		Pallet weight (UK)	0 g
Quantity per pack	1 pc(s)	Pallet length (UK)	120 cm
Package width	141 mm	Pallet width (UK)	100 cm
		Pallet height (UK)	171 cm
		Master (outer) case GTIN (EAN/UPC)	8715946663005
		Harmonized System (HS) code	84716070



8715946662848

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.