## APC Smart-UPS SMT2200IC - 8x C13, 1x C19, USB, SmartConnect, 2200VA

Brand : APC

Product code: SMT2200IC

Product name : APC Smart-UPS SMT2200IC - 8x C13, 1x C19, USB, SmartConnect, 2200VA

- 2200VA/1980W line interactive pure sine wave tower UPS

- Ideal for servers, storage, networking, business VoIP and desktops, retail POS

- Automatic Voltage Regulation helps correct utility voltage

- Cloud-based remote power monitoring via SmartConnect Ethernet Port

- Graceful shutdown using serial or USB cables via PowerChute Serial Shutdown

APC Smart-UPS SMT2200IC - 8x C13, 1x C19, USB, SmartConnect, 2200VA

APC Smart-UPS SMT2200IC - 8x C13, 1x C19, USB, SmartConnect, 2200VA. UPS topology: Line-Interactive, Output power capacity: 2.2 kVA, Output power: 1980 W. AC outlets quantity: 9 AC outlet(s), USB port type: USB Type-A. Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 8.7 min, Typical backup time at half load: 25 min. Product colour: Black, Display type: LCD. Compliance certificates: RoHS, Certification: CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE





Features		Battery	
UPS topology *	Line-Interactive	Battery life (max)	5 year(s)
Output power capacity *	2.2 kVA	Battery recharge time	3 h
Output power *	1980 W	Design	
Waveform * Input operation voltage (min) * Input operation voltage (max) * Input frequency *	Sine 151 V 302 V 50/60 Hz	Product colour * Display type LED indicators	Black LCD ✔
Output operation voltage (min)	220 V	Operational conditions	
Output operation voltage (max) Surge energy rating Response time Emergency Power Off (EPO) Output voltage Total Harmonic Distortion (THD) Noise level Power protection features Audible alarm(s) Audible alarm modes	240 V 365 J 6 ms ✓ 5% 45 dB Over voltage, Overload ✓ Alarm when on battery, Low battery alarm, Battery replacement	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude <b>Certificates</b> Compliance certificates Certification	0 - 40 °C -15 - 45 °C 0 - 95% 0 - 95% 0 - 3000 m 0 - 15000 m RoHS CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE
Auto-restart	✓	Packaging content	
Ports & interfaces		Cables included	RS-232, USB cable
AC outlets quantity	9 AC outlet(s)	Sustainability	
USB port	1	Sustainability certificates	Green Premium
USB 2.0 ports quantity	1	Weight & dimensions	
USB port type	USB Type-A	Width	197 mm
Serial interface	✓	Depth	544 mm

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date

Ports & interfaces		Weight & dimensions		
Serial ports quantity	1	Height	435 mm	
Ethernet LAN (RJ-45) ports	1	Weight	48.8 kg	
SmartSlot	1	Packaging data	Packaging data	
Battery		Software CD	1	
Battery technology	Sealed Lead Acid (VRLA)	Package width	381 mm	
Typical backup time at full load	8.7 min	Package depth	762 mm	
Typical backup time at half load	25 min	Package height	699 mm	
		Package weight	61.9 kg	
		Logistics data		
		Products per pallet	9 pc(s)	

Harmonized System (HS) code 85078000 Total carbon footprint (kg of CO2e) 3715.93





731304337317

0731304337317

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.