ATEN

ATEN CM1284 KVM-kytkin Telineasennus musta

Tuotemerkki : ATEN Tuotekoodi: CM1284-AT-G

Tuotteen nimi: CM1284



ATEN CM1284. Näppäimistöportin liitin: USB, Hiiriportin liitin: USB, Videoportin tyyppi: HDMI. HD-tyyppi: 4K Ultra HD, Enimmäiserottelutarkkuus: 4096 x 2160 pikseliä, Videokaistanleveys: 30 Hz. Tuotteen väri: musta, Telineen kapasiteetti: 1U, Kotelon materiaali: Metalli. Voimanlähde: AC, Tulojännite: 110 - 220 V, AC-syöttötaajuus: 50 - 60 Hz. Vaatimustenmukaisuustodistukset: RoHS



Ports & interfaces		Display	
Number of computers controlled *	4	On Screen Display (OSD)	✓
Keyboard port type *	USB		•
Mouse port type *	USB	Power	
Video port type *	НДМІ	Power source	AC
HDMI ports quantity	6	Input voltage	110 - 220 V
USB 2.0 Type-B ports quantity	4	AC input frequency	50 - 60 Hz
Console ports *	3.5mm headphone, HDMI, RJ-45, USB A	Input current Power consumption (typical)	1 A 16 W
Console USB ports quantity	2	Sustainability	
USB hub	✓	Compliance certificates	RoHS
USB 2.0 Type-A hub ports quantity USB connector type	-	Operational conditions	
Audio connections		Operating temperature (T-T)	0 - 40 °C
Headphone outputs		Storage temperature (T-T)	-10 - 60 °C
Number of microphone inputs	6	Operating relative humidity (H-H)	0 - 80%
Network		Weight & dimensions	
Ethernet LAN	1	Width	437.2 mm
Ethernet LAN (RJ-45) ports		Depth	164 mm
	_		44 mm
Performance		Weight	3.86 kg
HD type *	Compliance USB Type-A, USB Type-B Operation Operation Operation Storage te Operating Weight & Width Depth Height Weight 4K Ultra HD 4096 x 2160 pixels 30 Hz 5,10,15,30,60,90 s Package w Package w Package w Package w Manual	Packaging data	
Maximum resolution *		Package width	131 mm
Video bandwidth Scan interval		Package depth	540 mm
HDCP		Package height	233 mm
		Package weight	4.26 kg
Hot-Plug support Daisy chain	/	Packaging content	
Firmware upgradeable	1	Cables included	HDMI, USB
	•	Manual	✓
Design		AC adapter included	✓
Rack mounting *	✓	Rack mount kit	✓
Rack capacity	1U Black	Logistics data	
Product colour *		Master (outer) case net weight	11.6 kg
Housing material	Metal	Harmonized System (HS) code	85176200

Design		Logistics data	
Cascadable	✓	Master (outer) case width 420 mm	
LED indicators	✓	Master (outer) case length 555 mm	
Push button	/	Master (outer) case height 258 mm	
Hot keys		Master (outer) case gross weight 13.8 kg	
not keys	,	Products per master (outer) case 3 pc(s)	
Display			
Built-in display *	X		



4719264647505

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.