



APC Easy 3S UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 30 kVA 30000 W

Tuotemerkki : APC

Tuotekoodi: E3SUPS30KH

Tuotteen nimi : Easy 3S

APC Easy 3S. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 30 kVA, Lähtöteho: 30000 W. Kotelo: Tower, Tuotteen väri: Valkoinen, Näytön tyyppi: LED. Vaatimustenmukaisuustodistukset: RoHS, Sertifiointi: CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE, REACH. Tuotteen leveys: 250 mm, Tuotteen syvyys: 800 mm, Tuotteen korkeus: 770 mm. Pakkauksen leveys: 400 mm, Pakkauksen syvyys: 982 mm, Pakkauksen korkeus: 1015 mm



Features		Design	
UPS topology *	Double-conversion (Online)	International Protection (IP) code	IP20
Output power capacity *	30 kVA	Operational conditions	
Output power *	30000 W	Operating temperature (T-T)	0 - 40 °C
Waveform *	Pure sine	Storage temperature (T-T)	-15 - 40 °C
Input operation voltage (min) *	304 V	Operating relative humidity (H-H)	0 - 95%
Input operation voltage (max) *	477 V	Storage relative humidity (H-H)	0 - 95%
Input frequency *	45/65 Hz	Operating altitude	0 - 984.4 m
Output operation voltage (min)	380 V	Non-operating altitude	0 - 14763.6 m
Output operation voltage (max)	415 V	Certificates	
Output frequency	50/60 Hz	Compliance certificates	RoHS
Maximum current	55 A	Certification	CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE, REACH
Number of input phases	3	Packaging content	
Number of output phases	3	Quick installation guide	✓
Input power factor	0.99	Weight & dimensions	
Crest factor	3:1	Width	250 mm
Output voltage Total Harmonic Distortion (THD)	3%	Depth	800 mm
Input current Total Harmonic Distortion (THD)	3%	Height	770 mm
Noise level	63 dB	Weight	60 kg
Design		Packaging data	
Form factor *	Tower	Package width	400 mm
Product colour *	White		
Display type	LED		

Packaging data

Package depth	982 mm
Package height	1015 mm
Package weight	77 kg

Logistics data

Harmonized System (HS) code	85078000
-----------------------------	----------

Other features

Output voltage	400 V
----------------	-------



0731304339564



731304339564

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.