




## APC Easy 3S uninterruptible power supply (UPS) Double-conversion (Online) 10 kVA 10000 W

Brand : APC

Product code: E3SUPS10KHB1

Product name : Easy 3S

APC Easy 3S. UPS topology: Double-conversion (Online), Output power capacity: 10 kVA, Output power: 10000 W. Battery technology: Sealed Lead Acid (VRLA), Battery voltage: 220 V, Typical backup time at full load: 15 min. Form factor: Tower, Product colour: White, International Protection (IP) code: IP20. Width: 380 mm, Depth: 928 mm, Height: 1400 mm. Output voltage: 400 V




Features		Design	
UPS topology *	Double-conversion (Online)	Form factor *	Tower
Output power capacity *	10 kVA	Product colour *	White
Output power *	10000 W	International Protection (IP) code	IP20
Waveform *	Pure sine	Certification	CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE
Input operation voltage (min) *	304 V	<b>Operational conditions</b>	
Input operation voltage (max) *	477 V	Operating temperature (T-T)	0 - 40 °C
Input frequency *	45/65 Hz	Storage temperature (T-T)	-15 - 40 °C
Output operation voltage (min)	380 V	Operating relative humidity (H-H)	0 - 95%
Output operation voltage (max)	415 V	Storage relative humidity (H-H)	0 - 95%
Output frequency regulation	50/60 Hz	Operating altitude	0 - 999.9 m
Maximum current	18 A	Non-operating altitude	0 - 15000 m
Number of input phases	3	<b>Weight &amp; dimensions</b>	
Number of output phases	3	Width	380 mm
Input power factor	0.99	Depth	928 mm
Output voltage Total Harmonic Distortion (THD)	3%	Height	1400 mm
Input current Total Harmonic Distortion (THD)	3%	Weight	112 kg
Noise level	60 dB	Package width	563 mm
<b>Battery</b>		Package depth	1014 mm
Battery technology	Sealed Lead Acid (VRLA)	Package height	1640 mm
Battery voltage	220 V	Package weight	145 kg
Number of batteries supported	3	<b>Packaging data</b>	
Typical backup time at full load	15 min	Quick installation guide	✓

**Logistics data**

Harmonized System (HS) code	85078000
-----------------------------	----------

**Other features**

Output voltage	400 V
----------------	-------



0731304428152



731304428152



8592978255619

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.