



P1 P2



1 WHITE/ORANGE  
 2 ORANGE  
 3 WHITE/GREEN  
 6 GREEN  
 4 BLUE  
 5 WHITE/BLUE  
 7 WHITE/BROWN  
 8 BROWN



COLOR	LENGTH(mm)	TOLERANCE
Grey; Blue; Green; Yellow; Orange; Purple; Red; Black; White	300	±15
	500	±15
	1000	±20
	1500	±20
	2000	±30
	3000	±30
	5000	±30

**ELECTRICAL TEST:**

- 100% OPEN&SHORT TEST
- CONTACT RESISTANCE:20 Ohm (MAX)
- INSULATION RESISTANCE:10 MOhm (MIN) DC 300V/10ms
- Fluke Channel Test

3	RJ45 PLUG:8P8C 3U" GOLD PLATED TWO-PIECE TOUGH PLUG.	
2	MOLDED: PVC MOLDED BOOT .	
1	CABLE:CAT6A U/UTP 4P/28AWG (7/0.12±0.008BC) OD:3.5±0.2mm LSZH JACKET. MARKING: CATEGORY 6A U/UTP SLIM PATCH CABLE LSZH AWG 28	
NO.	SPECIFICATION	QTY
BOM LIST		

ITEM NO:	CAT6A U/UTP			DRAWER DATE	LY 20160829
TITLE				CHECKED DATE	MTC 20160829
CUSTOMER				APPROVED DATE	
MATERIAL	SCALE				
REV.	A	UNIT	MM		
DRAWING NO:					
ACAD FILE	E:\				

