ATEN

ATEN CS1148D KVM-kytkin musta

Tuotemerkki : ATEN Tuotekoodi: CS1148D-AT-G

Tuotteen nimi: CS1148D

ATEN CS1148D. Näppäimistöportin liitin: USB, Hiiriportin liitin: USB, Videoportin tyyppi: DVI-I. HD-tyyppi: 4K Ultra HD, Enimmäiserottelutarkkuus: 3840 x 2160 pikseliä, Videokaistanleveys: 30 Hz. Tuotteen väri: musta, Kotelon materiaali: Metalli. Voimanlähde: AC, Tulojännite: 100 - 240 V, AC-syöttötaajuus: 50 - 60 Hz. Vaatimustenmukaisuustodistukset: RoHS





| Ports & interfaces | | Power | |
|----------------------------------|-----------------------------------|---|-------------------|
| Number of computers controlled * | 8 | Power consumption (typical) | 17.7 W |
| Keyboard port type * | USB | System requirements | |
| Mouse port type * | USB | Windows operating systems | |
| Video port type * | DVI-I | supported | ✓ |
| DVI-I ports quantity | 16 16 | Sustainability | |
| USB 2.0 Type-B ports quantity | 3.5mm headphone, DVI-I, PS/2, USB | Compliance certificates | RoHS |
| Console ports * | A | Weight & dimensions | |
| Console USB ports quantity | 2 | Width | 204.9 mm |
| USB connector type | USB Type-B | Depth | 432.4 mm |
| PS/2 ports quantity | 2 | Height | 65.5 mm |
| Audio connections | ✓ | Weight | 3.7 kg |
| Headphone outputs | 8 | | 3.7 kg |
| Performance | | Packaging data | |
| HD type * | 4K Ultra HD | Package width | 133 mm |
| Maximum resolution * | 3840 x 2160 pixels | Package depth | 499 mm |
| Video bandwidth | 30 Hz | Package height Package weight | 324 mm 4.34 kg |
| Design | | Packaging content | 4.54 kg |
| Rack mounting * | × | Cables included | AC |
| Product colour * | Black | Quick installation guide | AC ✓ |
| Housing material | Metal | | v |
| LED indicators | ✓ | Manual | • |
| Push button | ✓ | Logistics data | |
| Display | | Master (outer) case net weight | 11.1 kg |
| | | Harmonized System (HS) code | 85176200 |
| Built-in display * | X | Master (outer) case width | 427 mm |
| Power | | Master (outer) case length | 519 mm 348 mm |
| Power source | AC | Master (outer) case height Master (outer) case gross weight | 348 mm 13.9 kg |
| Input voltage | 100 - 240 V | Products per master (outer) case | 3 pc(s) |
| AC input frequency | 50 - 60 Hz | rioducts per muster (outer) case | 5 pc(3) |
| Input current | 1 A | | |



4719264646539

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.