
## D-Link

## D-Link DEM-QX10Q-LR4 lähetin-vastaanotinmoduuli Valokuitu 40000 Mbit/s QSFP+ 1310 nm

Tuotemerkki : D-Link Tuotekoodi: DEM-QX10Q-LR4

Tuotteen nimi: DEM-QX10Q-LR4







Performance		Operational conditions	
SFP transceiver type *	Fiber optic	Operating relative humidity (H-H)	0 - 85%
Maximum data transfer rate *	40000 Mbit/s	Storage relative humidity (H-H)	0 - 85%
Interface type *	QSFP+	Weight & dimensions	
Single-mode fiber (SMF) supported	<b>✓</b>	Width	18.4 mm
Multi-mode fiber (MMF) supported	×	Depth	118 mm
Fiber optic connector	LC	Height	12.9 mm
Fiber cable diameters supported (core/cladding)	9/125 μm	Weight	40 g
SFP transceiver standard	LR4	Packaging content	
Maximum transfer distance	10000 m	Quantity per pack	1 pc(s)
Wavelength	1310 nm	Packaging data	
Tx power (min)	-4 dBmW	Package width	74 mm
Tx power (max)	8.3 dBmW	Package depth	131 mm
Rx power (min)	3.5 dBmW	Package height	49 mm
Rx power (max)	-13.7 dBmW	Package weight	64 g
Link budget	19.8 dB	Logistics data	
Ethernet interface type	400 Gigabit Ethernet IEEE 802.3ba	Shipping (inner) case length	36 cm
Networking standards Fiber ethernet cabling technology	40GBASE	Shipping (inner) case width	26 cm
Duplex system	Full	Shipping (inner) case height	31 cm
Digital Diagnostics Monitoring		Shipping (inner) case net weight	3.2 kg
(DDM)	<b>/</b>	Products per shipping (inner) case	50 pc(s)
Features		Pallet gross weight (air)	272 kg
Product colour	Blue, Silver	Master (outer) cases per pallet (air)	60 pc(s)
Hot-Plug support	✓	Products per pallet (air)	3000 pc(s)
3 11		Pallet gross length	102 cm
Power		Pallet gross width	122 cm
Maximum voltage	3.3 V	Pallet height (air)	199 cm
Maximum current	1.13 A	Pallet gross weight (sea)	272 kg
Certificates		Master (outer) cases per pallet (sea)	
Compliance certificates	RoHS	Products per pallet (sea)	3000 pc(s)
Certification	FCC Class B CE Class B VCCI Class B FDA/CDRH TUV CSA MSA	Pallet height (sea) Shipping (inner) case gross weight	199 cm 4.2 kg
Operational conditions		Harmonized System (HS) code	85369010
Operating temperature (T-T)	0 - 70 °C		
Storage temperature (T-T)	-40 - 85 °C		





790069390630

0790069390630

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.