ATEN

ATEN KE6910 KVM -kytkin Lähetin & vastaanotin

Tuotemerkki : ATEN Tuotekoodi: KE6910-AX-G

Tuotteen nimi: KE6910

ATEN KE6910. Malli: Lähetin & vastaanotin, Yhteysteknologia: Langallinen, Suurin siirtoetäisyys: 10000 m. Lähettimen videoportin tyyppi: DVI-D, Lähettimen paikallisen videoportin tyyppi: DVI-D, Lähettimen paikallisen näppäimistön/hiiren porttityyppi: USB. Vastaanottimen paikallisen videoportin tyyppi: DVI-D, Vastaanottimen paikallisen näppäimistön/hiiren porttityyppi: USB. USB-portin tyyppi: USB A-tyyppi. AC-adapterin lähtöjännite: 5 V, Tehonkulutus (lähetin) (max): 10,02 W, Tehonkulutus (vastaanotin) (max): 9,02 W





Features		Power	
Type * Connectivity technology *	Transmitter & receiver Wired	Power consumption (transmitter) (max)	10.02 W
Maximum transfer distance	10000 m	Power consumption (receiver) (max)	9.02 W
Cable types supported	Cat5	Weight & dimensions	
Rack mounting Maximum digital resolution KVM port selection On Screen Display (OSD) Product colour Material LED indicators Certification	✓ 2560 x 2048 pixels Push-buttons ✓ Black Metal ✓ ROHS	Transmitter width Transmitter depth Transmitter height Transmitter weight Receiver width Receiver depth Receiver height Receiver weight	16.3 cm 21.5 cm 4.18 cm 1.13 kg 17.2 cm 22.8 cm 5.48 cm 1.26 kg
Transmitter		Packaging data	
Transmitter video port type Transmitter local video port Transmitter local video port type Transmitter local keyboard/mouse	DVI-D ✓ DVI-D	Package width Package depth Package height Package weight	247 mm 556 mm 153 mm 4.61 kg
port type	USB	Packaging content	
RJ-45 ports quantity (transmitter) Receiver	1	AC adapter included Cables included	✓ AC, KVM
Receiver local video port type	DVI-D	Manual	✓
Receiver local keyboard/mouse port type	USB	Operational conditions	
RJ-45 ports quantity (receiver) Ports & interfaces	1	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	0 - 50 °C -20 - 60 °C 0 - 95%
USB port type	USB Type-A	Technical details	
USB 2.0 ports quantity RS-232 ports	2	Weight	3.62 kg
RJ-45 ports quantity	2	Logistics data	
PC Audio in	✓	Master (outer) case net weight	3.62 kg
PC Audio out	✓	Harmonized System (HS) code	84733080
Power		Master (outer) case width	247 mm
AC adapter output voltage	5 V	Master (outer) case length	556 mm

Logistics data

Master (outer) case height153 mmMaster (outer) case gross weight4.61 kgProducts per master (outer) case1 pc(s)



4719264648267

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.