



APC BV1000I UPS-virtalähde Linjainteraktiivinen 1 kVA 600 W 1 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: BV1000I

Tuotteen nimi : BV1000I


APC BV1000I. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 1 kVA, Lähtöteho: 600 W. Pistorasian tyypit: C13 liitin, Ulostulojen määrä: 1 AC-pistorasia(a). Akun kapasiteetti: 9 VAH, Akun kestoikä (maks.): 5 vuosi/vuosisia, Akun latausaika: 8 h. Tuotteen väri: musta, Johdon pituus: 1,52 m. Vaatimustenmukaisuustodistukset: RoHS, Sertifointi: CE



| Features | | Battery | |
|---|-----------------------------------|-----------------------------------|-----------|
| UPS topology * | Line-Interactive | Battery capacity | 9 VAh |
| Output power capacity * | 1 kVA | Battery life (max) | 5 year(s) |
| Output power * | 600 W | Battery recharge time | 8 h |
| Waveform * | Sine | Design | |
| Input operation voltage (min) * | 170 V | Cable length | 1.52 m |
| Input operation voltage (max) * | 280 V | Product colour * | Black |
| Input frequency * | 50/60 Hz | Operational conditions | |
| Output operation voltage (min) | 0 V | Operating temperature (T-T) | 0 - 40 °C |
| Output operation voltage (max) | 0 V | Operating relative humidity (H-H) | 0 - 90% |
| Output frequency | 50/60 Hz | Certificates | |
| Output frequency regulation | 50/60 Hz | Compliance certificates | RoHS |
| Output voltage regulation | 10% | Certification | CE |
| Automatic Voltage Regulation (AVR) | ✓ | Packaging content | |
| Surge energy rating | 156 J | Manual | ✓ |
| Transfer time (Line Mode to Battery Mode) | 6 ms | Weight & dimensions | |
| Noise level | 40 dB | Width | 160 mm |
| Surge protection | ✓ | Depth | 305 mm |
| Audible alarm(s) | ✓ | Height | 92 mm |
| Audible alarm modes | Low battery alarm, Overload alarm | Weight | 5.7 kg |
| Ports & interfaces | | Packaging data | |
| AC outlet types | C13 coupler | Package width | 143 mm |
| AC outlets quantity | 1 AC outlet(s) | Package depth | 373 mm |
| | | Package height | 237 mm |
| | | Package weight | 6 kg |
| | | Logistics data | |
| | | Harmonized System (HS) code | 85078000 |
| | | Other features | |
| | | Battery type | leakproof |
| | | Output voltage | 230 V |



0731304338222



731304338222

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.