

## APC BV1000I-GR UPS-virtalähde Linjainteraktiivinen 1 kVA 600 W 4 AC-pistorasia(a)

Tuotemerkki : APC Tuotekoodi: BV1000I-GR

Tuotteen nimi: BV1000I-GR

APC BV1000I-GR. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 1 kVA, Lähtöteho: 600 W. Pistorasian tyypit: Tyyppi F, Ulostulojen määrä: 4 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 9 ah, Akun jännite: 12 V. Kotelo: Kompakti, Tuotteen väri: musta, Johdon pituus: 1,52 m. Vaatimustenmukaisuustodistukset: RoHS, Sertifiointi: CE REACH





	Design	
UPS topology * Line-Interactive  Output power capacity * 1 kVA  Output power * 600 W  Waveform * Sine  Input operation voltage (min) * 170 V  Input operation voltage (max) * 280 V  Input frequency * 50/60 Hz  Output frequency 50/60 Hz  Automatic Voltage Regulation (AVR) ✓  Surge energy rating 156 J  Transfer time (Line Mode to Battery Mode) 6 ms	Form factor * Cable length Product colour * LED indicators	Compact 1.52 m Black ✓
	International Protection (IP) code  Operational conditions  Operating temperature (T-T)  Operating relative humidity (H-H)	0 - 40 °C 0 - 90%
	Certificates Compliance certificates	0 - 2032.1 m  RoHS CE REACH
1 40 dB	Weight & dimensions Width Depth Height	160.5 mm 305 mm 92.5 mm 5.7 kg
alarm, Overload alarm	Packaging data	
Type F 4 AC outlet(s)	Package width Package depth Package height Package weight	373 mm 143 mm 237 mm 6 kg
Sealed Lead Acid (VRLA)  9 Ah  12 V  8 h	Logistics data Harmonized System (HS) code Warranty period Other features Nominal output voltage	85078000 2 year(s)
	1 kVA 600 W Sine 170 V 280 V 50/60 Hz 50/60 Hz  156 J 6 ms 1 1 40 dB  Alarm when on battery, Low battery alarm, Overload alarm  Type F 4 AC outlet(s)  Sealed Lead Acid (VRLA) 9 Ah 12 V 8 h	1 kVA 600 W Product colour * Sine LED indicators 170 V International Protection (IP) code 280 V 50/60 Hz 50/60 Hz Operating temperature (T-T) Operating relative humidity (H-H) Operating altitude  Certificates Compliance certificates Certification  Weight & dimensions Width Depth Height Weight Weight  Alarm when on battery, Low battery alarm, Overload alarm  Packaging data  Type F 4 AC outlet(s) Package weight Sealed Lead Acid (VRLA) 9 Ah 12 V 8 h  Cable length Product colour * Perduct colour * Poduct colour * Perduct Colour * P





731304338246

0731304338246

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.