



## APC Smart-UPS SMT750RMI2UC - 4x C13, USB, Rackmount 2U, SmartConnect, 750VA

Brand : APC

Product code: SMT750RMI2UC

Product name : APC Smart-UPS SMT750RMI2UC - 4x C13, USB, Rackmount 2U, SmartConnect, 750VA



APC Smart-UPS SMT750RMI2UC - 4x C13, USB, Rack Mountable, SmartConnect, 750VA  
APC Smart-UPS SMT750RMI2UC - 4x C13, USB, Rackmount 2U, SmartConnect, 750VA. UPS topology: Line-Interactive, Output power capacity: 0.75 kVA, Output power: 500 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 4 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 168 VAh, Typical backup time at full load: 5.5 min. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Compliance certificates: RoHS, Certification: CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, TUV, UL 1778, VDE, REACH, PEP, EOLI




Features		Battery	
UPS topology *	Line-Interactive	Automatic battery test	✓
Output power capacity *	0.75 kVA	Cold start	✓
Output power *	500 W		
Waveform *	Pure sine		
Input operation voltage (min) *	151 V		
Input operation voltage (max) *	302 V		
Input frequency *	50/60 Hz		
Output operation voltage (min)	220 V		
Output operation voltage (max)	240 V		
Automatic Voltage Regulation (AVR)	✓		
Surge energy rating	459 J		
Hold time (max)	2 ms		
Efficiency	97.7%		
Noise level	42 dB		
Surge protection	✓		
Audible alarm(s)	✓		
Auto-restart	✓		
Ports & interfaces		Design	
AC outlet types	C13 coupler	Form factor *	Rackmount
Power plug	C14 coupler	Rack capacity	2U
AC outlets quantity	4 AC outlet(s)	Product colour *	Black
Number of output IEC jumpers	2	LED indicators	Battery replacement
USB port	✓		
Serial interface	✓		
Serial interface type	RJ-45		
SmartSlot	✓		
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Storage temperature (T-T)	-15 - 45 °C
		Operating relative humidity (H-H)	0 - 95%
		Storage relative humidity (H-H)	0 - 95%
		Operating altitude	0 - 3000 m
		Non-operating altitude	0 - 15000 m
		Certificates	
		Compliance certificates	RoHS
		Certification	CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, TUV, UL 1778, VDE, REACH, PEP, EOLI
		Packaging content	
		Rack mount kit	✓
		Cables included	RS-232, USB cable
		Quick installation guide	✓
		Sustainability	
		Sustainability certificates	Green Premium

Battery		Weight & dimensions	
Battery technology	Sealed Lead Acid (VRLA)	Width	432 mm
Battery capacity	168 VAh	Depth	406 mm
Typical backup time at full load	5.5 min	Height	89 mm
Typical backup time at half load	16 min	Weight	17.3 kg
Battery life (max)	5 year(s)	<b>Packaging data</b>	
Battery recharge time	3 h	Software CD	✓
Hot-swap battery	✓	Package width	546 mm
		Package depth	584 mm
		Package height	241 mm
		Package weight	21.2 kg
		<b>Logistics data</b>	
		Products per pallet	16 pc(s)
		Harmonized System (HS) code	85078000
		Total carbon footprint (kg of CO2e)	821.3



0731304340324



731304340324

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.