
ZYXEL

Zyxel GS1350-12HP-EU0101F verkkokytkin Hallittu L2 Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki Harmaa

Tuotemerkki : Zyxel Tuotekoodi: GS1350-12HP-EU0101F

Tuotteen nimi: GS1350-12HP-EU0101F







Management features		Security	
Switch type * Switch layer	Managed L2	Queue scheduling algorithms	SPQ, WFQ, Weighted Round Robin (WRR)
Web-based management	✓	Multicast features	
Configuring Location Settings (CLI)	✓	Multicast support	✓
System event log	RFC 1066, RFC 1213, 1157, RFC 1493, RFC 1643, RFC 1757, RFC 2011, 2012, 2013, RFC 2233, RFC 2358, RFC 2674, RFC 2819, 2925, RFC 3621, RFC 4293, RFC 4292, RFC 4022, RFC 4113	Design	
MIB support		Rack mounting *	✓
		Product colour	Grey
		LED indicators	✓
		Performance	
Ports & interfaces		Noise level	27.3 dB
Basic switching RJ-45 Ethernet ports quantity *	10	Firmware upgradeable	✓
		Mean time between failures (MTBF)	1065025.45 h
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power	
SFP module slots quantity	2	AC input voltage	100 - 240 V
Network		AC input frequency	50 - 60 Hz
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Power consumption (max)	160.3 W
		Power over Ethernet (PoE)	
		Power over Ethernet (PoE) *	✓
		Power over Ethernet (PoE) ports quantity	8
10G support *	×	Total Power over Ethernet (PoE)	130 W
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T	budget	
Port mirroring	/	Operational conditions	
Flow control support	/	Operating temperature (T-T)	-20 - 50 °C
Broadcast storm control		Storage temperature (T-T) Operating relative humidity (H-H)	-40 - 70 °C 5 - 95%

Network		Operational conditions	
Spanning tree protocol	✓	Storage relative humidity (H-H)	5 - 95%
VLAN support	✓	Heat dissipation	546.62 BTU/h
Virtual LAN features	MAC address-based VLAN, Port- based VLAN 256	Weight & dimensions	
Number of VLANs		Width Depth	267 mm 162 mm
Optical fiber		Height	44 mm
Fiber ethernet cabling technology	1000BASE-X	Weight	1.63 kg
Data transmission		Packaging content	
Switching capacity *	24 Gbit/s	Cables included	AC
Forwarding rate	17.8 Mpps	Rack mount kit	✓
MAC address table *	8000 entries	Logistics data	
Packet buffer memory	0.525 MB	Harmonized System (HS) code	85176990
Security			
DHCP features	DHCP client, DHCP relay, DHCP snooping		
IGMP snooping	✓		
IGMP proxy	✓		
Security algorithms	SNMP, SNMPv3, SSH, SSL/TLS		
MAC address filtering	✓		
Loop protection	✓		



4718937604388

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.