



## APC SMT3000RMI2UC UPS-virtalähde Linjainteraktiivinen 3 kVA 2700 W 9 AC-pistorasia(a)

**Tuotemerkki :** APC

**Tuotekoodi:** SMT3000RMI2UC

**Tuotteen nimi :** SMT3000RMI2UC



APC SMT3000RMI2UC. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 3 kVA, Lähtöteho: 2700 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: C20 liitin, Ulostulojen määrä: 9 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 547 VAH, Tyypillinen varmuuskopioaika täydellä kuormituksella: 3,2 min. Kotelo: Telineasennettava, Tuotteen väri: musta, Telineen kapasiteetti: 2U. Tuotteen leveys: 432 mm, Tuotteen syvyys: 683 mm, Tuotteen korkeus: 86 mm



Features		Battery	
UPS topology *	Line-Interactive	Cold start	✓
Output power capacity *	3 kVA	<b>Design</b>	
Output power *	2700 W	Form factor *	Rackmount
Waveform *	Sine	Rack capacity	2U
Input operation voltage (min) *	151 V	Cable length	2 m
Input operation voltage (max) *	302 V	Product colour *	Black
Input frequency *	50/60 Hz	Display type	LCD
Output operation voltage (min)	220 V	LED indicators	Status
Output operation voltage (max)	240 V	Certification	CE, EAC, EN 60950, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE, REACH, PEP, EOL
Automatic Voltage Regulation (AVR)	✓	<b>Operational conditions</b>	
Surge energy rating	320 J	Operating temperature (T-T)	0 - 40 °C
Hold time (min)	4 ms	Storage temperature (T-T)	-15 - 45 °C
Hold time (max)	8 ms	Operating relative humidity (H-H)	0 - 95%
Efficiency	98.9%	Storage relative humidity (H-H)	0 - 95%
Noise level	55 dB	Operating altitude	0 - 3000 m
Audible alarm(s)	✓	Non-operating altitude	0 - 15000 m
Auto-restart	✓	<b>Technical details</b>	
<b>Ports &amp; interfaces</b>		Sustainability certificates	Green Premium
AC outlet types	C13 coupler, C19 coupler	Compliance certificates	RoHS
Power plug	C20 coupler	<b>Weight &amp; dimensions</b>	
AC outlets quantity	9 AC outlet(s)	Width	432 mm
Number of output IEC jumpers	3	Depth	683 mm
USB port	✓	Height	86 mm
Serial interface	✓	Weight	44.3 kg
Serial interface type	RJ-45	Package width	600 mm
Ethernet LAN (RJ-45) ports	1		
SmartSlot	✓		

Battery		Weight & dimensions	
Battery technology	Sealed Lead Acid (VRLA)	Package depth	980 mm
Battery capacity	547 VAh	Package height	254 mm
Typical backup time at full load	3.2 min	Package weight	51.7 kg
Typical backup time at half load	11.5 min	<b>Packaging data</b>	
Battery life (max)	5 year(s)	Rack mount kit	✓
Battery recharge time	3 h	Cables included	RS-232, USB cable
Hot-swap battery	✓	Quick installation guide	✓
Automatic battery test	✓	Software CD	✓
		Bundled software	Powershute Business Edition
		<b>Logistics data</b>	
		Harmonized System (HS) code	85078000
		<b>Other features</b>	
		Nominal output voltage	230 V
		Nominal input voltage	230 V



0731304337348



731304337348

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.