

ZYXEL

Zyxel GS1350-18HP-EU0101F verkkokytkin Hallittu L2 Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki Harmaa

Tuotemerkki : Zyxel

Tuotekoodi: GS1350-18HP-EU0101F

Tuotteen nimi : GS1350-18HP-EU0101F

Zyxel GS1350-18HP-EU0101F. Kytkin tyyppi: Hallittu, Kytinkerros: L2. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 16. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 36 Gbit/s. Verkkostandardit: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1w, IEEE 802.3, IEEE 802.3ad, IEEE.... Power over Ethernet -tuki. Telineasennus



Management features		Security	
Switch type *	Managed	Queue scheduling algorithms	SPQ, WFQ, Weighted Round Robin (WRR)
Switch layer	L2	Multicast features	
Web-based management	✓	Multicast support	✓
Configuring Location Settings (CLI)	✓	Design	
System event log	✓	Rack mounting *	✓
MIB support	RFC 1066, RFC 1213, 1157, RFC 1493, RFC 1643, RFC 1757, RFC 2011, 2012, 2013, RFC 2233, RFC 2358, RFC 2674, RFC 2819, 2925, RFC 3621, RFC 4293, RFC 4292, RFC 4022, RFC 4113	Product colour	Grey
Ports & interfaces		LED indicators	✓
Basic switching RJ-45 Ethernet ports quantity *	16	Electromagnetic compatibility	CE, FCC, C-Tick, A; BSMI CNS13438
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Performance	
Combo SFP ports quantity	2	Noise level	39 dB
Network		Firmware upgradeable	✓
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1w, IEEE 802.3, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Mean time between failures (MTBF)	1699692.18 h
10G support *	✗	Power	
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T	AC input voltage	100 - 240 V
Port mirroring	✓	AC input frequency	50 - 60 Hz
Flow control support	✓	Power consumption (max)	300.9 W
Broadcast storm control	✓	Power over Ethernet (PoE)	
		Power over Ethernet (PoE) *	✓
		Power over Ethernet (PoE) ports quantity	16
		Total Power over Ethernet (PoE) budget	250 W
		Operational conditions	
		Operating temperature (T-T)	-20 - 50 °C
		Storage temperature (T-T)	-40 - 70 °C

Network		Operational conditions	
Rate limiting	✓	Operating relative humidity (H-H)	5 - 95%
Spanning tree protocol	✓	Storage relative humidity (H-H)	5 - 95%
VLAN support	✓	Heat dissipation	1026.07 BTU/h
Virtual LAN features	MAC address-based VLAN, Port-based VLAN	Weight & dimensions	
Number of VLANs	256	Width	330 mm
		Depth	230 mm
		Height	44 mm
		Weight	2.42 kg
Optical fiber		Packaging content	
Fiber ethernet cabling technology	1000BASE-X	Cables included	AC
		Rack mount kit	✓
Data transmission		Logistics data	
Switching capacity *	36 Gbit/s	Harmonized System (HS) code	85176990
Forwarding rate	26.7 Mpps		
MAC address table *	8000 entries		
Packet buffer memory	0.525 MB		
Security			
DHCP features	DHCP client, DHCP relay, DHCP snooping		
IGMP snooping	✓		
IGMP proxy	✓		
Security algorithms	SNMP, SNMPv3, SSH, SSL/TLS		
MAC address filtering	✓		
Loop protection	✓		



4718937604425



4718937604449

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.