

TP-Link TL-SL1218MP Hallitsematon Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki 1U musta

Tuotemerkki : TP-Link Tuotekoodi: TL-SL1218MP V1

Tuotteen nimi: TL-SL1218MP



TP-Link TL-SL1218MP. Kytkin tyyppi: Hallitsematon. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 20. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 7,2 Gbit/s. Verkkostandardit: IEEE 802.3af, IEEE 802.3at. Power over Ethernet -tuki. Telineasennus, Kotelo: 1U



Management features		Power	
Switch type *	Unmanaged	Power source *	AC
Ports & interfaces		Power supply included *	✓
Basic switching RJ-45 Ethernet ports quantity * Basic switching RJ-45 Ethernet ports		AC input voltage AC input frequency Power consumption (max)	100 - 240 V 50 - 60 Hz 217.22 W
type *	Gigabit Ethernet (10/100/1000)	, , ,	217.22 **
Fast Ethernet (copper) ports quantity	16	Power over Ethernet (PoE) Power over Ethernet (PoE) *	·
Gigabit Ethernet (copper) ports quantity	2	Power over Ethernet plus (PoE+) ports quantity	16
Combo SFP ports quantity	2	Power over Ethernet (PoE) power	30 W
Network		per port Total Power over Ethernet (PoE)	
Networking standards *	IEEE 802.3af, IEEE 802.3at	budget	192 W
10G support *	X	Operational conditions	
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T	Operating temperature (T-T)	0 - 40 °C
Auto MDI/MDI-X	✓	Storage temperature (T-T)	-40 - 70 °C
Auto-negotiation	✓	Operating relative humidity (H-H) Storage relative humidity (H-H)	10 - 90% 5 - 90%
MAC address auto-learning supported	✓	Heat dissipation	741.15 BTU/h
MAC address auto-aging supported	✓	Weight & dimensions	
Data transmission		Width	440 mm
Switching capacity * Forwarding rate	7.2 Gbit/s 5.36 Mpps	Depth Height	180 mm 44 mm
MAC address table *	8000 entries	Packaging content	
Store-and-forward	✓	Cables included	LAN (RJ-45)
Jumbo frames support	✓	Manual	✓
Jumbo frames	10000		

Data transmission		Packaging data	
Packet buffer memory	4.1 MB	Package type	Box
Design		Package width	250 mm
Rack mounting *	,	Package depth	528 mm
Rack mounting **	•	Package height	80 mm
Stackable *	Package weight	2.96 kg	
Form factor	1U Black LAN, PoE, Status 2 fan(s)	Certificates	
Product colour			
LED indicators		Certification	CE, FCC, RoHS
Number of fans		Logistics data	
		Harmonized System (HS) code	85176990













Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.