## D-Link

## D-Link DUB-E130 verkkokortti Ethernet 1000 Mbit/s

Tuotemerkki : D-Link Tuotekoodi: DUB-E130

Tuotteen nimi: DUB-E130

D-Link DUB-E130. Yhteysteknologia: Langallinen, Isäntäkoneen käyttöliittymä: USB Type-C, Käyttöliittymä: Ethernet. Tiedonsiirron enimmäisnopeus: 1000 Mbit/s. USB-virta. Tuotteen väri: Valkoinen






Ports & interfaces		Operational conditions	
Connectivity technology *	Wired	Operating relative humidity (H-H)	20 - 80%
Host interface *	USB Type-C	Storage relative humidity (H-H)	5 - 90%
Interface *	Ethernet	Weight & dimensions	
Ethernet LAN (RJ-45) ports USB version	1 2.0/3.2 Gen 2 (3.1 Gen 2)	Width	26.5 mm
	2.0/3.2 GCH 2 (3.1 GCH 2)	Depth	205 mm
Network	4000 MI '' /	Height	15 mm
Maximum data transfer rate *	1000 Mbit/s	Weight	28 g
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u	Packaging data	
Ethernet LAN	✓	Package width	138 mm
Ethernet interface type	Gigabit Ethernet	Package depth	138 mm
Ethernet LAN data rates	10,100,1000 Mbit/s	Package height	30 mm 99 q
Wake-on-LAN ready	✓	Package weight	99 g
Full duplex	✓	Logistics data	
Design		Harmonized System (HS) code	85176990
Product colour	White	Shipping (inner) case net weight	1.4 kg
Internal *	×	Shipping (inner) case length Shipping (inner) case height	33.5 cm 30.2 cm
Plug and Play	··	Shipping (inner) case width	28.6 cm
LED indicators	Link, Speed	Products per shipping (inner) case	40 pc(s)
Certification	CE, FCC	Pallet gross weight (air)	166.8 kg
Power		Master (outer) cases per pallet (air)	27 pc(s)
Input current	0.5 A	Products per pallet (air)	1080 pc(s)
Output voltage	5 V	Pallet height (air)	120 cm
Power consumption	176 mA	Pallet gross weight (sea)	298.8 kg
USB powered	<b>✓</b>	Master (outer) cases per pallet (sea)	
System requirements		Products per pallet (sea) Pallet height (sea)	2040 pc(s) 192 cm
Windows operating systems	Windows 10, Windows 7, Windows	Pallet gross width	110 cm
supported	8, Windows Vista, Windows XP Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12	Pallet gross length	120 cm
Mac operating systems supported	Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks		
Operational conditions			
Operating temperature (T-T)	0 - 40 °C		
Storage temperature (T-T)	-20 - 70 °C		









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.