



## ATEN CS1964-AT-G KVM-kytkin musta

**Tuotemerkki :** ATEN

**Tuotekoodi:** CS1964-AT-G

**Tuotteen nimi :** CS1964-AT-G



ATEN CS1964-AT-G. Näppäimistöportin liitin: USB, Hiiriportin liitin: USB, Videoportin tyyppi: DisplayPort. HD-tyyppi: 4K Ultra HD, Enimmäiserottelutarkkuus: 4096 x 2160 pikseliä, Videokaistanleveys: 60 Hz. Tuotteen väri: musta, Kotelon materiaali: Metall. Voimanlähde: DC, Tulojännite: 12 V, Virrankulutus: 15,49 W. Tuotteen leveys: 335 mm, Tuotteen syvyys: 156 mm, Tuotteen korkeus: 65,5 mm



<b>Ports &amp; interfaces</b>		<b>Power</b>	
Number of computers controlled *	4	Power consumption (typical)	15.49 W
Keyboard port type *	USB	<b>System requirements</b>	
Mouse port type *	USB	Windows operating systems supported	✓
Video port type *	DisplayPort	<b>Operational conditions</b>	
DisplayPorts quantity	12	Operating temperature (T-T)	0 - 50 °C
USB 3.2 Gen 1 (3.1 Gen 1) Type-B ports quantity	4	Storage temperature (T-T)	-20 - 60 °C
Console ports *	3.5mm headphone, 3.5mm mic, DisplayPort, HDMI, USB A	Operating relative humidity (H-H)	0 - 80%
Console USB ports quantity	2	Storage relative humidity (H-H)	0 - 80%
USB hub	✓	<b>Weight &amp; dimensions</b>	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A hub ports quantity	2	Width	335 mm
USB connector type	USB Type-A, USB Type-B	Depth	156 mm
Audio connections	✓	Height	65.5 mm
Headphone outputs	6	Weight	3.57 kg
Number of microphone inputs	6	<b>Packaging data</b>	
DC-in jack	✓	Package width	131 mm
<b>Performance</b>		Package depth	540 mm
HD type *	4K Ultra HD	Package height	233 mm
Maximum resolution *	4096 x 2160 pixels	Package weight	4.03 kg
Video bandwidth	60 Hz	<b>Packaging content</b>	
Scan interval	1,5,99 s	Quick installation guide	✓
<b>Design</b>		Manual	✓
Product colour *	Black	<b>Logistics data</b>	
Housing material	Metal	Master (outer) case net weight	10.7 kg
LED indicators	✓	Harmonized System (HS) code	85176200
Push button	✓	Master (outer) case width	420 mm
Hot keys	✓	Master (outer) case length	555 mm
<b>Display</b>		Master (outer) case height	258 mm
Built-in display *	✗	Master (outer) case gross weight	13 kg
<b>Power</b>		Products per master (outer) case	3 pc(s)
Power source	DC		

**Power**

Input voltage 12 V



4719264647536

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 10-JAN-2025. Prints or copies of Information are only valid on the printed Publication date