KYOCERA

KYOCERA ECOSYS P3260dn 1200 x 1200 DPI A4

Tuotemerkki : KYOCERA

Tuotteen nimi : ECOSYS P3260dn

Tuotekoodi: 1102WD3NL0

KYOCERA ECOSYS P3260dn. Tulostustekniikka: Laser. Värikasettien määrä: 1, Suurin toimintajakso: 300000 sivua kuukaudessa. Suurin resoluutio: 1200 x 1200 DPI. Suurin ISO A-luokan paperikoko: A4. Tulostusnopeus (musta, normaalilaatu, A4/US Letter): 60 ppm, Kaksipuolinen tulostus. Näyttö: LCD. Verkkovalmius. Tuotteen väri: musta, Valkoinen

Printing

Duplex printing mode	Auto
Print resolution black	1200 x 1200 DPI
Print speed (black, draft quality, A4/US Letter)	60 ppm
Colour *	✘
Print technology *	Laser
Duplex printing *	✔
Maximum resolution *	1200 x 1200 DPI
Print speed (black, normal quality, A4/US Letter) *	60 ppm
Duplex print speed (black, normal quality, A4/US Letter)	43 ppm
Warm-up time	25 s
Time to first page (black, normal)	4.5 s
Print margins (top, bottom, right, left)	4 mm

Features

Maximum duty cycle *	300000 pages per month
Recommended duty cycle	15000 - 25000 pages per month
Printing colours *	Black
Number of print cartridges *	1
Page description languages *	Epson LQ, PCL 5e, PCL 6, PCL XL, PDF 1.7, PostScript 3, TIFF, XPS
Number of printer fonts	93
Average cartridge yield (black)	40000 pages

Performance

Maximum internal memory	2500 MB
Memory slots	2
Memory type	DDR3
Card reader integrated	✔
Compatible memory cards	SD, SDHC
Built-in processor	✔
Processor family	ARM Cortex
Processor model	A9
Processor frequency	1200 MHz
Processor cores	2
Sound pressure level (printing)	56 dB
Sound pressure level (quiet mode)	50.4 dB

Design

Market positioning *	Business
Product colour *	Black, White
Built-in display *	✔
Display	LCD
Colour display	✘
Touchscreen	✘
Display number of lines	5 lines
Control type	Buttons
Certification	TUV-GS, CE

Features

Replacement cartridges	TK-3160 (toner, 12.500 afdrukken 5% dekking) TK-3170 (toner, 15.500 afdrukken 5% dekking) TK-3190 (toner, 25.000 afdrukken 5% dekking) TK-3200 (toner, 40.000 afdrukken 5% dekking)

Input & output capacity

Total number of input trays *	1
Total input capacity *	500 sheets
Total output capacity *	500 sheets
Paper tray 1 input capacity	500 sheets
Paper input type	Paper tray
Multi-Purpose tray	✔
Multi-Purpose tray input capacity	100 sheets
Maximum number of input trays	5
Maximum input capacity	2600 sheets
Maximum output capacity	500 sheets

Paper handling

Maximum ISO A-series paper size *	A4
Maximum print size	216 x 356 mm
Paper tray media types *	Plain paper
Multi-purpose tray media types	Banner
ISO A-series sizes (A0…A9) *	A4, A5, A6
ISO B-series sizes (B0…B9)	B5
Non-ISO print media sizes	Legal, Letter
Custom media width	105 - 216 mm
Custom media length	148 - 356 mm
Paper tray media weight	60 - 120 g/m²
Multi-Purpose Tray media weight	60 - 220 g/m²
Duplex media weight	60 - 120 g/m²
Maximum media length	91.5 cm

Ports & interfaces

Direct printing *	✔
USB port *	✔
Number of expansion slots	1
Optional connectivity	Ethernet, Parallel, Wireless LAN

Network

Network ready	✔
Wi-Fi *	✘
Ethernet LAN *	✔
Cabling technology	10/100/1000Base-T(X)
Ethernet LAN data rates	10,100,1000 Mbit/s
Security algorithms	HTTPS, IPPS, IPSEC, IPSec, SNMPv3
Management protocols	IPsec, HTTPS, IPPS, POP over SSL, SMTP over SSL
Mobile printing technologies	Apple AirPrint, Google Cloud Print, Kyocera Mobile Print, Mopria Print Service

Performance

Internal memory *	512 MB

Certificates

Waste Electrical and Electronic Equipment (WEEE) compliance	✔

Power

Power consumption (printing) *	721 W
Power consumption (max)	1242 W
Power consumption (ready)	11 W
Power consumption (PowerSave)	0.7 W
Power consumption (off)	0.07 W
Energy Star Typical Electricity Consumption (TEC)	2.99 kWh/week
AC input voltage	220 - 240 V
AC input frequency	50 Hz

System requirements

Windows operating systems supported	✔
Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.9 Mavericks
Linux operating systems supported	✔

Operational conditions

Operating temperature (T-T)	10 - 32.5 °C
Storage temperature (T-T)	-20 - 40 °C
Operating relative humidity (H-H)	15 - 80%
Storage relative humidity (H-H)	10 - 90%
Operating altitude	0 - 3500 m
Non-operating altitude	0.6 - 15000 m

Sustainability

Sustainability certificates	Blue Angel, EPEAT Silver, ENERGY STAR

Weight & dimensions

Width	410 mm
Depth	416 mm
Height	363 mm
Weight	15.9 kg

Packaging data

Package width	549 mm
Package depth	517 mm
Package height	455 mm
Package weight	20 kg

Packaging content

Cartridge(s) included	✔
Included cartridge capacity (black)	11000 pages
Drivers included	✔
Quick start guide	✔
Cables included	AC

Logistics data

Harmonized System (HS) code	84433210

Technical details

Compliance certificates	CE, REACH, RoHS

0632983059043

632983059043