## brother at your side

## Brother DS-640 CDF + Arkin syöttö -skanneri 1200 x 1200 DPI A4 Valkoinen

Tuotemerkki : Brother


Tuotekoodi: DS640TK1

Tuotteen nimi : DS-640

Brother DS-640. Skannauksen enimmäiskoko: 215,9 x 1828,8 mm, Optinen skannauserottelutarkkuus: 1200 x 1200 DPI, ADF-skannausnopeus (mustavalkoinen, A4): 15 ppm. Skannerityyppi: CDF + Arkin syöttö -skanneri, Tuotteen väri: Valkoinen, Ohjaustyyppi: Painikkeet. Anturin tyyppi: CIS, Skannaa: Sähköposti, Tiedosto, Kuva, OCR, Skannauksen äänentaso skannatessa: 53 dB. Suurin ISO A-luokan paperikoko: A4, Kortin paksuus (maksimi): 1,24 mm, Paperikasetin tulsotusmateriaalin paino: 35 - 270 g/m<sup>2</sup>. USB-versio: 3.2 Gen 1 (3.1 Gen 1), USB-liitin: Micro-USB B



Scanning		Ports & interfaces	
Maximum scan size *215.9 x 1828.8 mmOptical scanning resolution *1200 x 1200 DPIColour scanning	USB port * USB version USB connector type	<ul> <li>✓</li> <li>3.2 Gen 1 (3.1 Gen 1)</li> <li>Micro-USB B</li> </ul>	
Duplex scanning * Greyscale levels ADF scan speed (b/w, A4) ADF scan speed (greyscale, A4) ADF scan speed (colour, A4)	× 256 15 ppm 15 ppm 15 ppm	Power Power supply type * Power consumption (typical) Power consumption (standby) Power consumption (off)	USB 2.3 W 1.3 W 0.01 W
Design		Weight & dimensions	0.01 W
Scanner type * Product colour * Control type Built-in display *	CDF + Sheet-fed scanner White Buttons X	Width Depth Height Weight	301 mm 50.6 mm 36.8 mm 466 g
Performance		Packaging content	
Sensor type * Scan to Scanning noise level	CIS E-mail, File, Image, OCR 53 dB	Packaging content	DSmobile DS-640 Scanner, Micro USB Cable, Warranty, Quick setup giude, Product safety guide
Sound pressure level (max)	42 dB	System requirements	
Paper handling		Windows operating systems supported	1
Maximum ISO A-series paper size * Card thickness (max)	A4 1.24 mm	Mac operating systems supported	1
Paper tray media weight	35 - 270 g/m <sup>2</sup>	Operational conditions	
Maximum scan width Maximum scan length	21.6 cm 182.9 cm	Operating temperature (T-T) Operating relative humidity (H-H)	5 - 35 °C 20 - 80%



4977766800518

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.