# StarTech.com DK30CHDPDUE kannettavien tietokoneiden telakka ja porttitoistin Langallinen USB 3.2 Gen 1 (3.1 Gen 1) Type-C musta

Tuotemerkki : StarTech.com   **Tuotekoodi:** DK30CHDPDUE

Tuotteen nimi : DK30CHDPDUE

StarTech.com DK30CHDPDUE. Yhteysteknologia: Langallinen, Isäntäkoneen käyttöliittymä: USB 3.2 Gen 1 (3.1 Gen 1) Type-C, USB Power Delivery asti: 100 W. Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s, Verkkostandardit: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u. Tuotteen väri: musta, Tiedonsiirtonopeus: 5 Gbit/s, Digitaalinen enimmäistarkkuus: 4096 x 2160 pikseliä. AC-syöttöjännite: 100 - 240 V, Syöttöjännite: 2 A, Ulostulojännite: 20 V. Windows-käyttöjärjestelmätuki: Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10..., Mac-käyttöjärjestelmätuki: Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14...

Ports & interfaces

Connectivity technology *	Wired
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-C
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	4
USB Power Delivery (USB PD)	✔
USB Power Delivery revision	2.0
USB Power Delivery up to	100 W
HDMI ports quantity *	1
Headphone outputs *	1
Headphone connectivity	3.5 mm
DC-in jack	✔

Network

Ethernet LAN *	✔
Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rates	10,100,1000 Mbit/s
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u
Auto MDI/MDI-X	✔
Full duplex	✔
10G support	✘

Performance

Data transfer rate	5 Gbit/s
Maximum digital resolution	4096 x 2160 pixels
Product colour *	Black
On/off switch	✔
UASP support	✔
Housing material	Plastic

Software

Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64
Mac compatibility	✔
Mac operating systems supported	Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 13.0 Ventura

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-10 - 70 °C
Operating relative humidity (H-H)	5 - 95%

Performance

Certification	CE, FCC, REACH

Power

AC input voltage	100 - 240 V
Input current	2 A
Output voltage	20 V
Output current	5 A
Power consumption (typical)	100 W
Power plug type	Type N
Compatible power plug types	EU, UK

Weight & dimensions

Width	91 mm
Depth	98 mm
Height	32 mm
Weight	200 g

Packaging data

Package width	185 mm
Package depth	165 mm
Package height	95 mm
Package weight	1 kg

Packaging content

Cables included	USB Type-C
AC adapter included	✔
Quick start guide	✔

Technical details

Compliance certificates	RoHS

Logistics data

Products per master (outer) case	6 pc(s)
Master (outer) case width	200 mm
Master (outer) case length	310 mm
Master (outer) case height	360 mm
Harmonized System (HS) code	84733020

Other features

Chipset	Parade - PS176, Realtek - RTL8153, Realtek - RTS5411, C-Media - CM6533

0065030875660

065030875660