Features

StarTech.com DP2DVIS videokaapeli-adapteri 0,2 m DisplayPort DVI-D musta

Tuotemerkki : StarTech.com

Tuotekoodi: DP2DVIS

Tuotteen nimi : DP2DVIS

StarTech.com DP2DVIS. Johdon pituus: 0,2 m, Liitin 1: DisplayPort, Liitin 2: DVI-D. Paino: 48 g, Tuotteen leveys: 44 mm, Tuotteen syvyys: 200 mm. Pakkauksen leveys: 200 mm, Pakkauksen syvyys: 220 mm, Pakkauksen korkeus: 20 mm. Tukkupakkauksen leveys: 337 mm, Tuotepakkauksen pituus: 496 mm, Tukkupakkauksen korkeus: 226 mm





Connector 1 form factorStraightStorage relative humidity (H-H)80 - 90%Connector 2 form factorStraightWeight & dimensionsCable length *0.2 mWeight & dimensionsConnector 1 *DisplayPortWeight48 gConnector 2 *DVI-DDepth200 mmConnector 1 gender *MaleHeight20 mmConnector 2 gender *Female20 mm200 mmHDCPPackaging data200 mmHDCP version1.3Package depth200 mmDisplayPort version1.2Package depth20 mmDual Link DVIXPackage weight20 mmProduct colourBlackPackage weight57 gConverter typeActive video converterHarmonized System (HS) code84733080Operating temperature (T-T)0 - 40 °CMaster (outer) case width337 mmOperating relative humidity (H-H)80 - 90%Products per master (outer) case90 pc(s)				
Cable length *0.2 mWeight & dimensionsCable length *0.2 mWeight & dimensionsConnector 1 *DisplayPortWeight48 gConnector 2 *DVI-DDepth44 mmConnector 1 gender *MaleDepth200 mmConnector 2 gender *FemaleHeight20 mmHDCP✓Packaging data200 mmHDCP version1.3Package width200 mmDisplayPort version1.2Package depth220 mmDual Link DVIXPackage height200 mmProduct colourBlackPackage weight57 gChipsetParade PS 161Logistics dataConverter typeActive video converterHarmonized System (HS) code84733080Operational conditions0 - 40 °CMaster (outer) case length337 mmOperating temperature (T-T)0 - 70 °CParcet outer) case height226 mm	Connector 1 form factor	Straight	Storage relative humidity (H-H)	80 - 90%
Connector 1*DisplayPortWeight48 gConnector 2 *DVI-DWidth44 mmConnector 1 gender *MaleDepth200 mmConnector 2 gender *FemaleHeight20 mmHDCPPackaging data200 mmHDCP version1.3Package width200 mmDisplayPort version1.2Package depth200 mmDual Link DVIXPackage height20 mmProduct colourBlackPackage weight57 gChipsetParade PS 161Logistics dataConverter typeActive video converterHarmonized System (HS) code84733080Operating temperature (T-T)0 - 40 °CMaster (outer) case length337 mmOperating temperature (T-T)0 - 70 °CPackage not converter case height226 mmBrownet r exter (outer) case height226 mm226 mmOperating temperature (T-T)0 - 70 °CMaster (outer) case height226 mmConverter type0 - 70 °CPackage not converter case height226 mmBrownet r (aver) case height226 mmPackage not converter case height226 mmDeparter (aver) case height226 mmPackage not converter case height226 mmDeparter (aver) case height226 mmPackage not converter case height226 mmDeparter (aver) case height226 mmPackage not converter case height226 mmDistarter pace meter (aver) case height226 mmPackage not converterPackage not converter <td></td> <td rowspan="3">0.2 m DisplayPort DVI-D Male Female</td> <td>Weight & dimensions</td> <td></td>		0.2 m DisplayPort DVI-D Male Female	Weight & dimensions	
Connector 2 gender *FemaleFemaleHDCP✓Packaging dataHDCP version1.3Package width200 mmDisplayPort version1.2Package depth220 mmDual Link DVIXPackage height20 mmProduct colourBlackPackage weight57 gChipsetParade PS 161Logistics dataConverter typeActive video converterHarmonized System (HS) code84733080Operating temperature (T-T)0 - 40 °CMaster (outer) case length337 mmOperating temperature (T-T)0 - 70 °CPackage meater (nuter) case90 pr(c)	Connector 1 * Connector 2 * Connector 1 gender *		Width Depth	44 mm 200 mm
HDCP version1.3Package width200 mmDisplayPort version1.2Package depth220 mmDual Link DVIXPackage height20 mmProduct colourBlackPackage weight57 gChipsetParade PS 161Logistics dataVConverter typeActive video converterHarmonized System (HS) code84733080Operating temperature (T-T)0 - 40 °CMaster (outer) case length337 mmStorage temperature (T-T)0 - 70 °CPackage outer master (outer) case90 pr(c)			5	
ChipsetParade PS 161Logistics dataConverter typeActive video converterHarmonized System (HS) code84733080Operational conditionsMaster (outer) case width337 mmOperating temperature (T-T)0 - 40 °CMaster (outer) case length496 mmStorage temperature (T-T)0 - 70 °CProducts per master (outer) case90 pc(c)	DisplayPort version Dual Link DVI	1.2 ×	Package depth Package height	220 mm 20 mm
Operational conditions Master (outer) case width 337 mm Operating temperature (T-T) 0 - 40 °C Master (outer) case length 496 mm Storage temperature (T-T) 0 - 70 °C Master (outer) case height 226 mm	Chipset	Parade PS 161	Logistics data	
Operating temperature (T-T)0 - 40 °CMaster (outer) case length496 mmStorage temperature (T-T)0 - 70 °CMaster (outer) case height226 mmProducts per master (outer) case00 pc(c)	Converter type	Active video converter	Harmonized System (HS) code	84733080
Storage temperature (T-T) 0 - 70 °C Master (outer) case height 226 mm	Operational conditions		· · ·	
	Storage temperature (T-T)	0 - 70 °C	Master (outer) case height	226 mm

Operational conditions





065030842327

0065030842327

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.