

Epson EB-1485Fi data projector Ultra short throw projector 5000 ANSI lumens 3LCD 1080p (1920x1080) White

Brand : Epson

Product code: V11H919040

Product name : EB-1485Fi



- Flexible display options and sizes: Cater for user needs in any working environment
 - All-in-one interactive meeting display: Combines multiple resources in one interactive collaboration device
 - Increase productivity & agile working: Share and display content from a range of devices simultaneously
 - Sliding split screen: Up to four displays in one image - project images from different sources
 - Easy installation: Quick set-up with auto-adjusting calibration function
- Laser, 3LCD, LCD Panel 0.62", 5000 Lumen, Full HD, 16:9, 2500000:1, 10 Bits, 192Hz-240Hz, Optical Lens, 8.68 : 1, 366W, 9.8kg

Projector		Features	
Supported aspect ratios	16:9	Interactive *	✓
Screen size compatibility *	1651 - 2540 mm (65 - 100")	Interactive input supported	Interactive pen/Touch
Projection distance	0 - 0.78 m	Noise level (economic mode)	27 dB
Projection distance (wide)	0 - 0.4 m	On Screen Display (OSD)	✓
Projection distance (tele)	0 - 0.6 m	Screen mirroring	✓
Projector brightness *	5000 ANSI lumens	Noise level *	36 dB
Projection technology *	3LCD	Air filter	✓
Projector native resolution *	1080p (1920x1080)	Composite sync	✓
Contrast ratio (typical) *	2500000:1	Country of origin	China
Native aspect ratio *	16:9	Password protection	✓
Number of colours	1.07 billion colours	Compatible operating systems	Linux, Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Ubuntu 14.10, Ubuntu 15.04, Windows 10, Windows 10 (32/64 bit), Windows 2000
Projector brightness (economic mode)	3500 ANSI lumens		
Vertical scan range	192 - 240 Hz		
Keystone correction, horizontal	-3 - 3°		
Keystone correction, vertical	-3 - 3°		
Matrix size	1.57 cm (0.62")		
Heat dissipation	1244 BTU/h		
Light source		Multimedia	
Light source type *	Laser	Built-in speaker(s) *	✓
Service life of light source *	20000 h	RMS rated power	16 W
Service life of light source (economic mode)	30000 h	Number of built-in speakers	2
Lens system		Design	
Focus *	Manual	Market positioning *	Business
Fixed focal length	3.9 mm	Product type *	Ultra short throw projector
Zoom capability	✓	Product colour *	White
Zoom type	Auto	Placement	Wall
Zoom ratio	1.35:1	Cable lock slot	✓
Throw ratio	0.27 - 0.37:1	Cable lock slot type	Kensington
Video		Power	
Full HD *	✓	Power source *	AC
3D *	✗	Power consumption (typical) *	366 W
Supported graphics resolutions	1920 x 1080 (HD 1080)	Power consumption (standby) *	0.5 W
		Power consumption (economy mode)	262 W
		AC input voltage	220-240 V
		AC input frequency	50 - 60 Hz

Video		Software	
Supported video modes	1080p		via: AMX, Crestron (Network), Extron, Crestron (RS-232C only), Crestron Integrated Partner, Crestron RoomView, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol
Video processing	10 bit		
Video colour modes	Blackboard, Cinema, Dynamic, Presentation, sRGB, DICOM simulation mode	Software support	
Adjustable colour temperature	✓	Windows operating systems supported	Windows 10, Windows 10 x64, Windows 2000
Ports & interfaces		Operational conditions	
HDMI connector type	Full-size	Storage temperature (T-T)	-10 - 60 °C
HDBaseT port	✓	Weight & dimensions	
USB 2.0 ports quantity	2	Width	458 mm
USB 2.0 Type-B ports quantity	2	Depth	375 mm
Headphone outputs	1	Height	210 mm
Microphone in	✓	Weight *	9.3 kg
Serial interface type *	RS-232C	Package width	472 mm
PC Audio in	✓	Package depth	590 mm
PC Audio out	✓	Package height	640 mm
VGA (D-Sub) ports quantity *	2	Package weight	27.7 kg
HDMI ports quantity *	3	Packaging content	
Component video (YPbPr/YCbCr) in *	1	Remote control included *	✓
DVI port *	✗	Batteries included	✓
DC-in jack	✓	Cables included	AC
Network		Manual	✓
Smart TV *	✗	Mounting brackets included	✓
Ethernet LAN *	✓	AC adapter included	✓
Wi-Fi *	✓	WLAN adapter included	✓
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)	Bundled software	Easy Interactive Tools, EasyMP Multi PC Projection, Epson Projektor Management
Miracast	✓	Technical details	
Storage		Sustainability certificates	TCO
Card reader integrated *	✗	Logistics data	
		Quantity per pack	1 pc(s)
		Products per pallet	6 pc(s)
		Pallet gross weight	0 g
		Products per pallet (UK)	12 pc(s)
		Pallet weight (UK)	0 g
		Harmonized System (HS) code	85286200
		Other features	
		Supported network protocols	HTTPS, IPv4, IPv6, SNMP, ESC/VP.net, PJLink



8715946674070

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-DEC-2024. Prints or copies of Information are only valid on the printed Publication date