## Canon

## Canon PIXMA TS3352 Mustesuihku A4 4800 x 1200 DPI Wi-Fi

Tuotemerkki : Canon Tuoteperhe: PIXMA Tuotekoodi: 3771C046

Tuotteen nimi: TS3352

Canon PIXMA TS3352. Tulostustekniikka: Mustesuihku, Tulostus: Väritulostus, Suurin resoluutio: 4800 x 1200 DPI. Kopiointi: Värikopiointi. Skannaus: Väriskannaus, Optinen skannauserottelutarkkuus: 600 x 1200 DPI. Suurin ISO A-luokan paperikoko: A4. Wi-Fi. Tuotteen väri: Punainen





Printing		Network	
Duplex printing mode Print technology * Printing * Duplex printing * Maximum resolution *	Manual Inkjet Colour printing X 4800 x 1200 DPI	Ethernet LAN * Wi-Fi standards Security algorithms Mobile printing technologies	X 802.11b, 802.11g, Wi-Fi 4 (802.11n) WEP, WPA-PSK, WPA2-PSK Apple AirPrint, Google Cloud Print, Mopria Print Service
Borderless printing	✓	Performance	
Copying		Sound pressure level (printing)	53.5 dB
Copying * Maximum number of copies	Colour copying 20 copies	Design Product colour *	Red
Scanning		Market positioning *	Home & office
Scanning * Optical scanning resolution * Scanner type *	Colour scanning 600 x 1200 DPI Flatbed scanner	Built-in display * Display Display resolution	LCD 1024 x 768 pixels
Input colour depth	16 bit	Power	
Output colour depth Input greyscale depth Output greyscale depth	8 bit 16 bit 8 bit	Power consumption (copying) Power consumption (standby) Power consumption (off)	11 W 1.7 W 0.3 W
Input greyscale depth	16 bit	Power consumption (standby) Power consumption (off) AC input voltage	1.7 W 0.3 W 100 - 240 V
Input greyscale depth Output greyscale depth	16 bit	Power consumption (standby) Power consumption (off) AC input voltage AC input frequency	1.7 W 0.3 W
Input greyscale depth Output greyscale depth Fax	16 bit 8 bit	Power consumption (standby) Power consumption (off) AC input voltage AC input frequency  System requirements	1.7 W 0.3 W 100 - 240 V 50 - 60 Hz
Input greyscale depth Output greyscale depth  Fax Faxing * Features Ink tank system	16 bit 8 bit	Power consumption (standby) Power consumption (off) AC input voltage AC input frequency	1.7 W 0.3 W 100 - 240 V 50 - 60 Hz Windows 10, Windows 7, Windows 8.1
Input greyscale depth Output greyscale depth  Fax Faxing * Features Ink tank system Number of print cartridges *	16 bit 8 bit	Power consumption (standby) Power consumption (off) AC input voltage AC input frequency  System requirements Windows operating systems	1.7 W 0.3 W 100 - 240 V 50 - 60 Hz Windows 10, Windows 7, Windows 8.1 Mac OS X 10.11 El Capitan, Mac OS
Input greyscale depth Output greyscale depth  Fax Faxing * Features Ink tank system Number of print cartridges * Input & output capacity	16 bit 8 bit  X  2	Power consumption (standby) Power consumption (off) AC input voltage AC input frequency  System requirements Windows operating systems supported	1.7 W 0.3 W 100 - 240 V 50 - 60 Hz  Windows 10, Windows 7, Windows 8.1  Mac OS X 10.11 El Capitan, Mac OS X 10.14 Mojave
Input greyscale depth Output greyscale depth  Fax Faxing * Features Ink tank system Number of print cartridges *	16 bit 8 bit	Power consumption (standby) Power consumption (off) AC input voltage AC input frequency  System requirements Windows operating systems supported  Mac operating systems supported	1.7 W 0.3 W 100 - 240 V 50 - 60 Hz  Windows 10, Windows 7, Windows 8.1  Mac OS X 10.11 El Capitan, Mac OS X 10.14 Mojave

Paper handling		Operational conditions	
Maximum ISO A-series paper size *	A4 216 x 297 mm Envelopes, Photo paper, Plain paper A4, A5 B5 10x15,13x18,13x13 10x15, 13x18, 13x13 101.6 - 215.9 mm	Operating temperature (T-T)	15 - 30 °C
Maximum print size Paper tray media types *		Weight & dimensions	
ISO A-series sizes (A0A9) * ISO B-series sizes (B0B9) Photo paper sizes Borderless printing media sizes		Width Depth Height Weight	435 mm 316 mm 145 mm 3.9 kg
Custom media width		Packaging content	
Custom media length	127 - 676 mm	Cartridge(s) included	✓
Ports & interfaces		Included cartridge capacity (black)	180 pages
Direct printing * USB port	×	Included cartridge capacity (CMY) Manual	180 pages ✓
USB connector	USB Type-B	Logistics data	
Network		Harmonized System (HS) code	84433100
Wi-Fi *	✓		



4549292144024

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.