ATEN

ATEN CS1716A-AT-G KVM-kytkin Telineasennus musta

Tuotemerkki : ATEN

Tuotekoodi: CS1716A-AT-G

Tuotteen nimi : CS1716A-AT-G

ATEN CS1716A-AT-G. Näppäimistöportin liitin: USB, PS/2, Hiiriportin liitin: USB, PS/2, Videoportin tyyppi: VGA. HD-tyyppi: QXGA, Enimmäiserottelutarkkuus: 2048 x 1536 pikseliä, Skannausväli: 1,255 s. Tuotteen väri: musta, Telineen kapasiteetti: 1U, Kotelon materiaali: Metalli. Voimanlähde: DC, Tulojännite: 5.3 V, Virrankulutus: 6,6 W. Vaatimustenmukaisuustodistukset: RoHS






Ports & interfaces

Ports & interfaces		System requirements	
Number of computers controlled * Keyboard port type * Mouse port type * Video port type * VGA (D-Sub) ports quantity Console ports *	512 USB, PS/2 USB, PS/2 VGA 17 USB A, VGA (D-Sub)	Linux operating systems supported	
		Mac operating systems supported	1
		Sustainability	
		Compliance certificates	RoHS
		Operational conditions	
Console USB ports quantity	1	Operating temperature (T-T)	0 - 50 °C
DC-in jack	1	Storage temperature (T-T)	-20 - 60 °C
Performance		Operating relative humidity (H-H)	0 - 80%
HD type *	QXGA	Weight & dimensions	
Maximum resolution *	2048 x 1536 pixels	Width	437.2 mm
Scan interval	1,255 s	Depth	159.9 mm
DDC2B support	1	Height	44 mm
Hot-Plug support	1	Weight	3.61 kg
Daisy chain	 Image: A start of the start of	Packaging data	
Firmware upgradeable	 Image: A set of the set of the	Package width	116 mm
Design		Package depth	540 mm
Rack mounting *	1	Package height Package weight	233 mm 4 kg
Rack capacity	10		4 Ky
Product colour *	Black	Packaging content	
Housing material	Metal	Cables included	KVM
LED indicators	 Image: A start of the start of	Quick installation guide	1
Push button	 Image: A set of the set of the	AC adapter included	
Hot keys	 Image: A set of the set of the	Rack mount kit	1
Display		Logistics data	
Built-in display *	×	Master (outer) case net weight	10.8 kg
On Screen Display (OSD)	 Image: A set of the set of the	Harmonized System (HS) code	85176200
Power		Master (outer) case width Master (outer) case length	375 mm 565 mm
Power source	DC	Master (outer) case height	258 mm
Input voltage	5.3 V	Master (outer) case gross weight	12.6 kg
Power consumption (typical)	6.6 W	Products per master (outer) case	3 pc(s)

Windows operating systems supported

1



4710423775329

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.