



## Canon i-SENSYS MF3010 Laser A4 1200 x 600 DPI 18 ppm

Brand : Canon

Product family: i-SENSYS

Product code: 5252B034

Product name : MF3010

Print/Scan/Copy, Laser, 600 x 400 dpi, A4, USB 2.0, 60~163g/m<sup>2</sup>, 8.2 kg, 960W + 2 x 725 cartridges  
Canon i-SENSYS MF3010. Print technology: Laser, Printing: Mono printing, Maximum resolution: 1200 x 600 DPI. Copying: Mono copying, Maximum copy resolution: 600 x 600 DPI. Scanning: Colour scanning, Optical scanning resolution: 600 x 600 DPI. Maximum ISO A-series paper size: A4. Product colour: Black



Printing		Paper handling	
Print technology *	Laser	ISO B-series sizes (B0...B9)	B5
Printing *	Mono printing	Non-ISO print media sizes	Executive, Statement
Duplex printing *	✗	Envelopes sizes	10, B5, C5, DL
Maximum resolution *	1200 x 600 DPI	Custom media width	76 - 216 mm
Print speed (black, normal quality, A4/US Letter) *	18 ppm	Custom media length	127 - 356 mm
Warm-up time	10 s	Paper tray media weight	60 - 163 g/m <sup>2</sup>
Time to first page (black, normal)	7.8 s	<b>Ports &amp; interfaces</b>	
Print margins (top, bottom, right, left)	5 mm	Standard interfaces	USB 2.0
Economical printing	✓	USB port	✓
<b>Copying</b>		USB 2.0 ports quantity	1
Duplex copying *	✗	<b>Network</b>	
Copying *	Mono copying	Wi-Fi *	✗
Maximum copy resolution *	600 x 600 DPI	Ethernet LAN *	✗
Copy speed (black, normal quality, A4)	18 cpm	<b>Performance</b>	
Time to first copy (black, normal)	12 s	Card reader integrated	✗
Maximum number of copies	9 copies	Internal memory *	64 MB
Copier resize	50 - 200%	Sound pressure level (printing)	65.3 dB
N-in-1 copy function (N=)	2	Sound power level (standby)	43 dB
<b>Scanning</b>		<b>Design</b>	
Duplex scanning *	✗	Product colour *	Black
Scanning *	Colour scanning	Market positioning *	Home & office
Optical scanning resolution *	600 x 600 DPI	<b>Power</b>	
Maximum scan resolution	9600 x 9600 DPI	Power consumption (max)	960 W
Maximum scan area	A4 / Letter (216 x 297)	Power consumption (average operating)	450 W
Scanner type *	Flatbed scanner	Power consumption (PowerSave)	450 W
Input colour depth	24 bit	Power consumption (standby)	1.4 W
Output colour depth	24 bit	Energy Star Typical Electricity Consumption (TEC)	0.6 kWh/week
Greyscale levels	256	AC input voltage	220 - 240 V
Scan drivers	TWAIN, WIA	AC input frequency	50 - 60 Hz
<b>Fax</b>			
Duplex faxing	✗		
Faxing *	✗		
<b>Features</b>			
Maximum duty cycle *	8000 pages per month		
Digital sender	✗		
Number of print cartridges *	1		
Printing colours *	Black		

Features		System requirements	
Page description languages	UFRII-LT		
Input & output capacity			
Total input capacity *	150 sheets		
Total output capacity *	100 sheets		
Paper handling			
Maximum ISO A-series paper size *	A4		
Maximum print size	216 x 356 mm		
Paper tray media types *	Card stock, Coated paper, Envelopes, Labels, Plain paper, Recycled paper, Transparencies	Windows operating systems supported	Windows 2000, Windows 2000 Professional, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
ISO A-series sizes (A0...A9) *	A4, A5	Mac operating systems supported	Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion
		Linux operating systems supported	✓
		Operational conditions	
		Operating relative humidity (H-H)	20 - 80%
		Operating temperature (T-T)	10 - 30 °C
		Sustainability	
		Sustainability certificates	ENERGY STAR
		Weight & dimensions	
		Width	372 mm
		Depth	276 mm
		Height	254 mm
		Weight	8.2 kg
		Logistics data	
		Harmonized System (HS) code	84433100



8714574661483

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.