Canon

Canon i-SENSYS MF3010 Laser A4 1200 x 600 DPI 18 ppm

Tuotemerkki : Canon   **Tuoteperhe:** i-SENSYS   **Tuotekoodi:** 5252B034

Tuotteen nimi : MF3010

Canon i-SENSYS MF3010. Tulostustekniikka: Laser, Tulostus: Yksittäistulostus, Suurin resoluutio: 1200 x 600 DPI. Kopiointi: Yksittäiskopiointi, Kopioinnin enimmäistarkkuus: 600 x 600 DPI. Skannaus: Väriskannaus, Optinen skannauserottelutarkkuus: 600 x 600 DPI. Suurin ISO A-luokan paperikoko: A4. Tuotteen väri: musta

Printing

Print technology *	Laser
Printing *	Mono printing
Duplex printing *	✗
Maximum resolution *	1200 x 600 DPI
Print speed (black, normal quality, A4/US Letter) *	18 ppm
Warm-up time	10 s
Time to first page (black, normal)	7.8 s
Print margins (top, bottom, right, left)	5 mm
Economical printing	✔

Copying

Duplex copying *	✗
Copying *	Mono copying
Maximum copy resolution *	600 x 600 DPI
Copy speed (black, normal quality, A4)	18 cpm
Time to first copy (black, normal)	12 s
Maximum number of copies	9 copies
Copier resize	50 - 200%
N-in-1 copy function (N=)	2

Scanning

Duplex scanning *	✗
Scanning *	Colour scanning
Optical scanning resolution *	600 x 600 DPI
Maximum scan resolution	9600 x 9600 DPI
Maximum scan area	A4 / Letter (216 x 297)
Scanner type *	Flatbed scanner
Input colour depth	24 bit
Output colour depth	24 bit
Greyscale levels	256
Scan drivers	TWAIN, WIA

Fax

Duplex faxing	✗
Faxing *	✗

Features

Maximum duty cycle *	8000 pages per month
Digital sender	✗
Number of print cartridges *	1
Printing colours *	Black

Paper handling

ISO B-series sizes (B0...B9)	B5
Non-ISO print media sizes	Executive, Statement
Envelopes sizes	10, B5, C5, DL
Custom media width	76 - 216 mm
Custom media length	127 - 356 mm
Paper tray media weight	60 - 163 g/m²

Ports & interfaces

Standard interfaces	USB 2.0
USB port	✔
USB 2.0 ports quantity	1

Network

Wi-Fi *	✗
Ethernet LAN *	✗

Performance

Card reader integrated	✗
Internal memory *	64 MB
Sound pressure level (printing)	65.3 dB
Sound power level (standby)	43 dB

Design

Product colour *	Black
Market positioning *	Home & office

Power

Power consumption (max)	960 W
Power consumption (average operating)	450 W
Power consumption (PowerSave)	450 W
Power consumption (standby)	1.4 W
Energy Star Typical Electricity Consumption (TEC)	0.6 kWh/week
AC input voltage	220 - 240 V
AC input frequency	50 - 60 Hz

Features

Page description languages	UFRII-LT

Input & output capacity

Total input capacity *	150 sheets
Total output capacity *	100 sheets

Paper handling

Maximum ISO A-series paper size *	A4
Maximum print size	216 x 356 mm
Paper tray media types *	Card stock, Coated paper, Envelopes, Labels, Plain paper, Recycled paper, Transparencies
ISO A-series sizes (A0...A9) *	A4, A5

System requirements

Windows operating systems supported	Windows 2000, Windows 2000 Professional, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Mac operating systems supported	Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion
Linux operating systems supported	✔

Operational conditions

Operating relative humidity (H-H)	20 - 80%
Operating temperature (T-T)	10 - 30 °C

Sustainability

Sustainability certificates	ENERGY STAR

Weight & dimensions

Width	372 mm
Depth	276 mm
Height	254 mm
Weight	8.2 kg

Logistics data

Harmonized System (HS) code	84433100

8714574661483