

StarTech.com DP2DVI2 videokaapeli-adapteri 0,152 m DisplayPort DVI-I musta

Tuotemerkki : StarTech.com

Tuotekoodi: DP2DVI2

Tuotteen nimi : DP2DVI2

StarTech.com DP2DVI2. Johdon pituus: 0,152 m, Liitin 1: DisplayPort, Liitin 2: DVI-I.

Vaatimustenmukaisuustodistukset: RoHS, Sertifiointi: CE, FCC, REACH. Paino: 43 g, Tuotteen leveys: 42 mm, Tuotteen syvyys: 254 mm. Pakkauksen leveys: 200 mm, Pakkauksen syvyys: 220 mm, Pakkauksen korkeus: 19 mm. Lukumäärä per pakkaus: 1 kpl



| Features | | Operational conditions | |
|--------------------------------|--|-----------------------------------|----------------|
| Connector 1 form factor | Straight | Operating relative humidity (H-H) | 5 - 90% |
| Connector 2 form factor | Straight | Certificates | |
| Cable length * | 0.152 m | Compliance certificates | RoHS |
| Connector 1 * | DisplayPort | Certification | CE, FCC, REACH |
| Connector 2 * | DVI-I | Weight & dimensions | |
| Connector 1 gender * | Male | Weight | 43 g |
| Connector 2 gender * | Female | Width | 42 mm |
| HDCP | ✓ | Depth | 254 mm |
| HDCP version | 1.4 | Height | 17 mm |
| DisplayPort version | 1.2 | Packaging data | |
| Dual Link DVI | ✗ | Package width | 200 mm |
| Maximum resolution | 1920 x 1200 pixels 640 x 480 (VGA), 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 768 (WXGA), 1280 x 800 (WXGA), 1280 x 960, 1360 x 768 (WXGA), 1366 x 768, 1400 x 1050 (SXGA+), 1440 x 900, 1600 x 600, 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA) | Package depth | 220 mm |
| Supported graphics resolutions | | Package height | 19 mm |
| Supported video modes | 480p, 720p, 1080p | Package weight | 52 g |
| Maximum refresh rate | 60 Hz | Packaging content | |
| HBR2 support | ✓ | Quantity per pack | 1 pc(s) |
| Product colour | Black | Logistics data | |
| Plug and Play | ✓ | Harmonized System (HS) code | 84733080 |
| Converter type | Passive video converter | Master (outer) case width | 325 mm |
| Operational conditions | | Master (outer) case length | 500 mm |
| Operating temperature (T-T) | 0 - 70 °C | Master (outer) case height | 220 mm |
| | | Products per master (outer) case | 140 pc(s) |

Operational conditions

Storage temperature (T-T) -10 - 80 °C



0065030836869



065030836869



0132017610139



132017610139

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.