## Chieftec Polaris virtalähdeyksikkö 650 W 20+4 pin ATX PS/2 musta

Tuotemerkki : Chieftec

KKI : Chieftet

Tuoteperhe: Polaris Tuote

Tuotekoodi: PPS-650FC

Tuotteen nimi : Polaris


Chieftec Polaris . Kokonaisteho: 650 W, AC-syöttöjännite: 100 - 240 V, AC-syöttötaajuus: 50 - 60 Hz. Emolevyn virtaliitin: 20+4 pin ATX, Emolevyn virtapiuhan pituus: 65 cm, SATA-virtakaapelin pituus: 150,450 mm. Tarkoitus: PC, Virransyöttöyksikön mitat: PS/2, 80 PLUS certification: 80 PLUS Gold. Tuotteen väri: musta, Jäähdytyksen tyyppi: Aktiivinen, Tuulettimen halkaisija: 12 cm. Tuotteen leveys: 150 mm, Tuotteen syvyys: 140 mm, Tuotteen korkeus: 87 mm





Power		Ports & interfaces	
Total power *650 WAC input voltage *100 - 240 VAC input frequency50 - 60 HzInput current10 APower Factor Correction (PFC) typeActiveCombined power (+3.3V)120 WCombined power (+12V)650 W	PCI Express power cable length CPU power connector (4+4 pin) CPU power cable length Floppy drive power connector Floppy disk drive connector Cabling type	50 cm ✓ 65 cm 1 ✓ Fully-Modular	
Combined power (+5V) Combined power (-12V) Combined power (+5Vsb) Max output current (+3.3V) Max output current (+12V)	120 W 3.6 W 15 W 22 A 54.2 A	Performance 80 PLUS certification * Purpose * Power supply unit (PSU) form factor * ATX version	80 PLUS Gold PC PS/2 2.4
Max output current (+5V) Max output current (-12V) Max output current (+5Vsb) Power protection features	22 A 0.3 A 3 A Over current, Over voltage, Overheating, Overload, Short circuit, Under voltage	Design Product colour Cooling type Fan diameter Number of fans	Black Active 12 cm 1 fan(s)
Ports & interfaces Motherboard power connector * Motherboard power cable length Number of SATA power connectors SATA power cable length Peripheral (Molex) power connectors (4-pin) *	20+4 pin ATX 65 cm 6 150,450 mm 3	Fan location Weight & dimensions Width Depth Height Weight	Top 150 mm 140 mm 87 mm 2.17 kg
Peripheral (Molex) power cable length PCI Express power connectors (6+2 pin)	150,450 mm 4	<b>Packaging data</b> Package weight Package type	2.48 kg Box

Technical details				
Compliance certificates	RoHS			
Logistics data				
Harmonized System (HS) code	84733020			





753263076434

0753263076434

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.