## Epson EcoTank ET-5880 Inkjet A4 4800 x 2400 DPI 25 ppm Wi-Fi

Brand: Epson Product family: EcoTank Product code: C11Cj28401

Product name: ET-5880



- Ultra-low cost, 4-in-1 A4 printer: Economical ink tank system
- Fast print and scan speeds: Print up to 25 ppm and scan up to 27.5 ipm
- Easy to use front ink tank: Enjoy hassle and mess-free refills with enhanced ink bottles
- Mobile printing and connectivity: Wi-Fi, Wi-Fi Direct, Ethernet & free mobile printing apps²
- Designed for business: 2 x 250-sheet front tray, 50-sheet rear feed, 50-sheet ADF, PCL & PS3

A4, 3.8 pl,  $4800 \times 2400$  DPI, 25 ppm, USB, Ethernet, WLAN, 10.9 cm Touchscreen, 19 W,  $425 \times 500 \times 350$  mm, 17.8 Kg

Epson EcoTank ET-5880. Print technology: Inkjet, Printing: Colour printing, Maximum resolution:  $4800 \times 2400 \text{ DPI}$ , Print speed (colour, normal quality, A4/US Letter): 25 ppm. Copying: Colour copying. Scanning: Colour scanning, Optical scanning resolution:  $2400 \times 1200 \text{ DPI}$ . Faxing: Colour faxing. Maximum ISO Aseries paper size: A4. Wi-Fi. Direct printing. Product colour: Black, White

| Printing   |  | Paper handling  |  |  |
|--|--|---|--|--|
| Duplex printing mode Print technology * Printing * Duplex printing *             | Auto Inkjet Colour printing  ✓ 4800 x 2400 DPI | ISO A-series sizes (A0A9) * ISO B-series sizes (B0B9) Non-ISO print media sizes Envelopes sizes Paper tray media weight | A4, A5, A6<br>B5, B6<br>Legal, Letter<br>10, C4, C6, DL<br>64 - 255 g/m <sup>2</sup> |  |
| Maximum resolution * Print speed (black, normal quality,                         |  | Ports & interfaces  |  |  |
| A4/US Letter) *  | 25 ppm   | Direct printing *   |  |  |
| Print speed (colour, normal quality, A4/US Letter)                               | 25 ppm   | USB port  | ✓<br>✓   |  |
| Print speed (ISO/IEC 24734) black  | 25 ppm   | Network   |  |  |
| Print speed (ISO/IEC 24734) colour   | 25 ppm   | Wi-Fi *   | ,  |  |
| Duplex print speed (black, normal quality, A4/US Letter)                         | 21 ppm   | Ethernet LAN *  | 1  |  |
| Duplex print speed (colour, normal quality, A4/US Letter)                        | 21 ppm   | Security algorithms   | 64-bit WEP, 128-bit WEP, WPA-PSK, WPA-TKIP   |  |
| Duplex print speed (ISO/IEC 24734)<br>mono<br>Duplex print speed (ISO/IEC 24734) | 11 ipm   | Management protocols  | SNMP, HTTP, DHCP, BOOTP, APIPA,<br>DDNS, mDNS, SNTP, SLP, WSD,<br>LLTD, Ping         |  |
| colour   | 6 ipm  |   | Epson Connect, Epson iPrint, Epson   |  |
| Duplex print speed (ISO/IEC 24734, A4) black                                     | 21 ppm   | Mobile printing technologies  | Email Print, Epson Remote Print,<br>Apple AirPrint                                   |  |
| Duplex print speed (ISO/IEC 24734, A4) colour                                    | 21 ppm   | Performance   |  |  |
| Time to first page (black, normal)   | 5.5 s  | Card reader integrated  | ×  |  |
| Time to first page (colour, normal)  | 6 s  | Design  |  |  |
| Copying  |  | Product colour *  | Black, White   |  |
| Duplex copying *   | <b>✓</b>                                       | Market positioning *  | Home & office  |  |
| Duplex copying mode  | Auto   | Built-in display *  | ✓  |  |
| Copying *  | Colour copying                                 | Display   | LCD  |  |
| Scanning   |  | Display diagonal  | 10.9 cm (4.3")   |  |
| Duplex scanning *  | 1  | Touchscreen   | ✓  |  |
|  | Auto   | Control type  | Touch  |  |
| Duplex scanning mode Scanning *  | Colour scanning                                | Colour display  | ✓  |  |
| Optical scanning resolution *  | 2400 x 1200 DPI                                | Power   |  |  |
| Scan technology  | CIS  | Power consumption (average  | 10.14  |  |
| Scan to  | Cloud  | operating)  | 19 W   |  |
| Scan speed (black)   | 27.5 inch/min                                  | Power consumption (copying)   | 19 W   |  |
| Scan speed (colour)  | 9 inch/min                                     | Power consumption (ready)   | 9.7 W  |  |
| Image formats supported  | BMP, JPEG, TIFF, PNG                           | Power consumption (sleep)   | 0.8 W  |  |
| Document formats supported   | PDF  | Power consumption (off)   | 0.2 W  |  |
|  |  | Energy Star Typical Electricity<br>Consumption (TEC)  | 0.14 kWh/week  |  |

| Fax  |   | Power                                |  |
|--|---|--------------------------------------|--|
|  | .1  | AC input voltage                     | 220 - 240 V  |
| Duplex faxing Faxing *                         | Colour faxing   | AC input voitage  AC input frequency | 220 - 240 V<br>50 - 60 Hz  |
| Fax transmission speed                         | 3 sec/page  | -                                    |  |
| Modem speed                                    | 33.6 Kbit/s   | System requirements                  | Windows 10, Windows 10, 64   |
| Fax memory                                     | 180 pages   |                                      | Windows 10, Windows 10 x64, Windows 7, Windows 7 x64,  |
| Auto-redialing                                 | ✓   | Windows operating systems            | Windows 8, Windows 8 x64,  |
| Speed dialling                                 | ✓   | supported                            | Windows 8.1, Windows 8.1 x64,<br>Windows Vista, Windows Vista x64,   |
| Fax speed dialing (max numbers)                | 100   |                                      | Windows XP Professional x64,<br>Windows XP   |
| Fax forwarding                                 | ✓   |                                      | Mac OS X 10.10 Yosemite, Mac OS X  |
| Fax forwarding to                              | E-mail, PC  |                                      | 10.11 El Capitan, Mac OS X 10.12   |
| Error Correction Mode (ECM)                    | ✓   | Mac operating systems supported      | Sierra, Mac OS X 10.13 High Sierra,<br>Mac OS X 10.6 Snow Leopard, Mac   |
| Features                                       |   | 3 3/4 1 3 3/4 1                      | OS X 10.7 Lion, Mac OS X 10.8  |
| Recommended duty cycle                         | 200 - 3300 pages per month                                  |                                      | Mountain Lion, Mac OS X 10.9<br>Mavericks  |
| Maximum duty cycle *                           | 66000 pages per month                                       |                                      | Windows Server 2008 R2, Windows  |
| Ink tank system                                | ✓   | Server operating systems supported   | Server 2012 R2, Windows Server 2016, Windows Server 2003 R2,   |
| Number of print cartridges *                   | 4   |                                      | Windows Server 2003  |
| Printing colours *  Page description languages | Black, Cyan, Yellow, Magenta<br>PCL 3, PCL 5c, PostScript 3 | Weight & dimensions                  |  |
| Printer fonts                                  | PCL, PostScript   | Width                                | 425 mm   |
| Country of origin                              | Indonesia   | Depth                                | 500 mm   |
| Input & output capacity                        |   | Height                               | 350 mm   |
| Total number of input trays *                  | 3   | Weight                               | 17.8 kg  |
| Total input capacity *                         | 250 sheets  | Packaging data                       |  |
| Total output capacity *                        | 125 sheets  | Package width                        | 560 mm   |
| Paper tray 1 input capacity                    | 250 sheets  | Package depth                        | 500 mm   |
| Paper tray 2 input capacity                    | 250 sheets  | Package height Package weight        | 445 mm<br>21.2 kg  |
| Auto document feeder (ADF)                     | <b>✓</b>  | Quantity per pack                    | 1 pc(s)  |
| Auto document feeder (ADF) input capacity      | 50 sheets   | Packaging content                    | [ - X. ]   |
| Maximum input capacity                         | 550 sheets  | Cartridge(s) included                | <b>✓</b>   |
| Paper handling                                 |   | Cables included                      | AC   |
| Maximum ISO A-series paper size *              | A4  | Drivers included                     | ✓  |
| Paper tray media types *                       | Envelopes, Plain paper                                      | Warranty card                        | ✓  |
|  |   | Logistics data                       |  |
|  |   | Harmonized System (HS) code          | 84433100   |
|  |   | Pallet gross weight                  | 0 g  |
|  |   | Products per pallet                  | 8 pc(s)  |
|  |   | Pallet weight (UK)                   | 0 g  |
|  |   | Products per pallet (UK)             | 16 pc(s)   |
|  |   | Other features                       |  |
|  |   | Printing method                      | Epson PrecisionCore  |
|  |   |                                      | Mac OS 10.10.x, Mac OS 10.6+, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X 10.12.x, Mac OS X 10.13.x, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2008 R2, Windows Server                  |
|  |   | Compatible operating systems         | 2012 R2, Windows Server 2016,<br>Windows Vista (32/64 Bit), Windows<br>XP Professional x64 Edition SP2 or<br>later, Windows XP SP3 or later (32-<br>bit), Windows Server 2003 R2,<br>Windows Server 2003 SP2 or later,<br>Windows XP Professional x64<br>Edition |
|  |   | Ink drop                             | 3.8  |
|  |   | Fax polling                          | <b>✓</b>   |
|  |   | Print head nozzles                   | 800 nozzles black, 800 nozzles per colour  |

| _ |   |     | _  | _           |       |
|---|---|-----|----|-------------|-------|
| п |   | 200 | +^ | <b>~+</b> : | ıres  |
| u | ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,, | ıeı | 16 | all         | 11 ES |

Supported network protocols

IPv4, IPv6



8715946676654

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.