

## Epson EcoTank ET-5880

**Tuotemerkki :** Epson

**Tuoteperhe:** EcoTank

**Tuotekoodi:** C11CJ28401

**Tuotteen nimi :** ET-5880



- Erittäin edullinen A4-monitoimitustoin: Taloudellinen mustesäiliöjärjestelmä
- Nopea tulostus ja skannaus: Tulosta jopa 25 sivua ja skannaa jopa 27,5 sivua minuutissa
- Helppokäyttöinen mustesäiliö tulostimen etuosassa: Täytä mustesäiliö helposti ja siististi kätevien mustepullojen avulla
- Mobiilitulostus ja liitännät: Wi-Fi, Wi-Fi Direct, Ethernet ja maksuttomat mobiilitulostussovellukset<sup>2</sup>
- Suunniteltu yrityksille: 2 x 250 arkin etulokero, 50 arkin takasyöttö, 50 arkin automaattinen arkisyöttölaite, PCL ja PS3

EcoTank Pro ET-5880

Epson EcoTank ET-5880. Tulostustekniikka: Mustesuihku, Tulostus: Väritulostus, Suurin resoluutio: 4800 x 2400 DPI, Tulostusnopeus (väri, normaaliaatu, A4/US Letter): 25 ppm. Kopiointi: Värikopiointi.

Skannaus: Väriskanuus, Optinen skannauserottelutarkkuus: 2400 x 1200 DPI. Faksaus: Väriefaksaus.

Suurin ISO A-luokan paperikoko: A4. Wi-Fi. Suoratulostus. Tuotteen väri: musta, Valkoinen

Printing		Paper handling	
Duplex printing mode	Auto	ISO A-series sizes (A0...A9) *	A4, A5, A6
Print technology *	Inkjet	ISO B-series sizes (B0...B9)	B5, B6
Printing *	Colour printing	Non-ISO print media sizes	Legal, Letter
Duplex printing *	✓	Envelopes sizes	10, C4, C6, DL
Maximum resolution *	4800 x 2400 DPI	Paper tray media weight	64 - 255 g/m <sup>2</sup>
Print speed (black, normal quality, A4/US Letter) *	25 ppm	Ports & interfaces	
Print speed (colour, normal quality, A4/US Letter)	25 ppm	Direct printing *	✓
Print speed (ISO/IEC 24734) black	25 ppm	USB port	✓
Print speed (ISO/IEC 24734) colour	25 ppm	Network	
Duplex print speed (black, normal quality, A4/US Letter)	21 ppm	Wi-Fi *	✓
Duplex print speed (colour, normal quality, A4/US Letter)	21 ppm	Ethernet LAN *	✓
Duplex print speed (ISO/IEC 24734) mono	11 ipm	Security algorithms	64-bit WEP, 128-bit WEP, WPA-PSK, WPA-TKIP
Duplex print speed (ISO/IEC 24734) colour	6 ipm	Management protocols	SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, Sntp, SLP, WSD, LLTD, Ping
Duplex print speed (ISO/IEC 24734, A4) black	21 ppm	Mobile printing technologies	Epson Connect, Epson iPrint, Epson Email Print, Epson Remote Print, Apple AirPrint
Duplex print speed (ISO/IEC 24734, A4) colour	21 ppm	Performance	
Time to first page (black, normal)	5.5 s	Card reader integrated	✗
Time to first page (colour, normal)	6 s	Design	
Copying		Product colour *	Black, White
Duplex copying *	✓	Market positioning *	Home & office
Duplex copying mode	Auto	Built-in display *	✓
Copying *	Colour copying	Display	LCD
Scanning		Display diagonal	10.9 cm (4.3")
Duplex scanning *	✓	Touchscreen	✓
Duplex scanning mode	Auto	Control type	Touch
Scanning *	Colour scanning	Colour display	✓
Optical scanning resolution *	2400 x 1200 DPI	Power	
Scan technology	CIS	Power consumption (average operating)	19 W
Scan to	Cloud	Power consumption (copying)	19 W
Scan speed (black)	27.5 inch/min	Power consumption (ready)	9.7 W
Scan speed (colour)	9 inch/min	Power consumption (sleep)	0.8 W
Image formats supported	BMP, JPEG, TIFF, PNG	Power consumption (off)	0.2 W
Document formats supported	PDF		

<b>Fax</b>		<b>Power</b>	
Duplex faxing	✓	Energy Star Typical Electricity Consumption (TEC)	0.14 kWh/week
Faxing *	Colour faxing	AC input voltage	220 - 240 V
Fax transmission speed	3 sec/page	AC input frequency	50 - 60 Hz
Modem speed	33.6 Kbit/s	<b>System requirements</b>	
Fax memory	180 pages	Windows operating systems supported	Windows 10, Windows 10 x64, Windows 7, Windows 7 x64, Windows 8, Windows 8 x64, Windows 8.1, Windows 8.1 x64, Windows Vista, Windows Vista x64, Windows XP Professional x64, Windows XP
Auto-redialing	✓		Mac operating systems supported
Speed dialling	✓	Server operating systems supported	
Fax speed dialling (max numbers)	100		
Fax forwarding	✓		
Fax forwarding to	E-mail, PC		
Error Correction Mode (ECM)	✓		
<b>Features</b>		<b>Weight &amp; dimensions</b>	
Recommended duty cycle	200 - 3300 pages per month	Width	425 mm
Maximum duty cycle *	66000 pages per month	Depth	500 mm
Ink tank system	✓	Height	350 mm
Number of print cartridges *	4	Weight	17.8 kg
Printing colours *	Black, Cyan, Yellow, Magenta	<b>Packaging data</b>	
Page description languages	PCL 3, PCL 5c, PostScript 3	Package width	560 mm
Printer fonts	PCL, PostScript	Package depth	500 mm
Country of origin	Indonesia	Package height	445 mm
<b>Input &amp; output capacity</b>		Package weight	21.2 kg
Total number of input trays *	3	Quantity per pack	1 pc(s)
Total input capacity *	250 sheets	<b>Packaging content</b>	
Total output capacity *	125 sheets	Cartridge(s) included	✓
Paper tray 1 input capacity	250 sheets	Cables included	AC
Paper tray 2 input capacity	250 sheets	Drivers included	✓
Auto document feeder (ADF)	✓	Warranty card	✓
Auto document feeder (ADF) input capacity	50 sheets	<b>Logistics data</b>	
Maximum input capacity	550 sheets	Harmonized System (HS) code	84433100
<b>Paper handling</b>		Pallet gross weight	0 g
Maximum ISO A-series paper size *	A4	Products per pallet	8 pc(s)
Paper tray media types *	Envelopes, Plain paper	Pallet weight (UK)	0 g
		Products per pallet (UK)	16 pc(s)
		<b>Other features</b>	
		Printing method	Epson PrecisionCore
		Compatible operating systems	Mac OS 10.10.x, Mac OS 10.6+, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X 10.12.x, Mac OS X 10.13.x, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 Bit), Windows 8.1 (32/64 bit), Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016, Windows Vista (32/64 Bit), Windows XP Professional x64 Edition SP2 or later, Windows XP SP3 or later (32-bit), Windows Server 2003 R2, Windows Server 2003 SP2 or later, Windows XP Professional x64 Edition
		Ink drop	3.8
		Fax polling	✓

#### Other features

Print head nozzles	800 nozzles black, 800 nozzles per colour
Supported network protocols	IPv4, IPv6



8715946676654

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.